General Turning Tools

Catalogue

Turning

2022

ZCC Cutting Tools Europe GmbH

your Partner \ your Value

WELCOME TO ZCC CUTTING TOOLS EUROPE

ZCC-CT, one of the World's leading carbide tooling manufacturers, welcomes you to its products. We are able to offer you a wide product range of high performance cutting tools at economic prices and a good supply service to support the production and productivity at your manufacturing facilities. You will find the main tool types in the various sections of the catalogue, Turning is in section A, Milling in section B and Drilling in section C of the catalogue.

We are looking forward to working with you and developing good cooperation together. Our team at ZCC Cutting Tools Europe is ready to support you in all of your requirements.

Member of Minmetals Group

EUROPEAN HEADQUARTER / HAUPTSITZ IN EUROPA:
ZCC Cutting Tools GmbH, Heltorfer Str.12, 40472 Düsseldorf, Germany
Tel.: +49 (0) 211/989240-0, Fax: +49 (0) 211/ 989240-111
E-Mail: info@zccct-europe.com, www.zccct-europe.com, www.zccct.com

MC 734/MT
STAMA

Contents

A Turning A1-A333

General turning tools	A21-A246
Parting and grooving tools	A247-A290
Threading tools	A291-A325



Turning Tools

General turning tools
Parting and grooving tools
Threading tools

Turning A

Guide to selecting turning tools A2-A5

Turning inserts overview A6-A11

Turning tool holders overview A12-A14

Recommended grade overview for turning insert A19

General turning tools A21-A246

General turning inserts overview A22-A26

Application instruction of general turning tools A27-A49

General turning inserts A50-A152

Cemented carbide and cermet inserts A54-A114

PCBN&PCD inserts A115-A149

Ceramic inserts A150-A152

General turning tools A153-A240

Tool holders for external turning A156-A205

Tool holders for internal turning A206-A240

Application reference for general turning machining A241-A246

Parting and grooving tools A247-A290

Parting and grooving tools overview A250-A252

Parting and grooving inserts A253-A269

Parting and grooving tools A270-A288

Application reference for parting and grooving A289-A290

Threading tools A291-A325

Threading tools overview A294-A295

Threading inserts A296-A311

Threading tools A312-A314

Application reference for threading A315-A325

General technical information for turning A326-A333

Guide to selecting general turning tools

Selection B







DCLNR/L

Approach angle	95°
Page	A166

Step 1 : I want to order tool holders
•Approach angle, •Clamping system

For finishing

DF A54

Step 2 : Details of tool holder
•Tool holder type, Size, •Operation genre
•Applicable inserts

Dimensions(mm)				
L	I.C	S	d	r
12.9	12.7	4.76	5.16	0.4

Step 3 : Details of insert
•Shape, •Size, •Chipbreaker, •Grade, •Stock
Applicable tool holders
•Approach angle, •Page

Applicable tool

PCBNR/L Kr:75° Page A172
PCLNR/L Kr:95° A173

Step 4 : Return to locate tool holder

Guide to selecting parting and grooving tools

Parting and grooving tools

QE□□R/L

QECDR/L

Page A272-273 A273

QF□□RR/LL

QF□DR/L

Page A278-281 A282-283

External parting, grooving and turning tools



R-type shown

Type	Stock R	Stock L	Basic dimensions(mm) H×B	L	S	W	Applicable inserts	Screw	Wrench
QEAD	1212R/L07	▲	12×12	125	11.4	1.5	7	ZCAD015□□	G870-85-M×12	WH3L
	1212R/L12	▲	12×12	125	11.4	1.5	12	ZCAD015□□		
	1616R/L07	▲	16×16	125	15.4	1.5	7	ZCAD015□□	G870-85-M×16	WH4L
	1616R/L12	▲	16×16	125	15.4	1.5	12	ZCAD015□□		
	2020R/L07	▲	20×20	125	19.4	1.5	7	ZCAD015□□		
	2020R/L12	▲	20×20	125	19.4	1.5	12	ZCAD015□□		
QEBD	1212R/L07	▲	12×12	125	11.2	2	7	ZCBD02□□	G870-85-M×12	WH3L
	1212R/L10	▲	12×12	125	11.2	2	10	ZCBD02□□		
	1212R/L14	▲	12×12	125	11.2	2	14	ZCBD02□□		
	1616R/L07	▲	16×16	125	15.2	2	7	ZCBD02□□	G870-85-M×16	WH4L
	1616R/L10	▲	16×16	125	15.2	2	10	ZCBD02□□		
	1616R/L14	▲	16×16	125	15.2	2	14	ZCBD02□□		
	2020R/L07	▲	20×20	125	19.2	2	7	ZCBD02□□		
	2020R/L10	▲	20×20	125	19.2	2	10	ZCBD02□□	G870-85-M×20	WH5L
	2020R/L14	▲	20×20	125	19.2	2	14	ZCBD02□□		
	2525R/L07	▲	25×25	150	24.2	2	7	ZCBD02□□		
	2525R/L10	▲	25×25	150	24.2	2	10	ZCBD02□□		
	2525R/L14	▲	25×25	150	24.2	2	14	ZCBD02□□		
QEED	1616R/L10	▲	16×16	125	15	2.5	10	ZCED02□□	G870-85-M5×20	WH4L
	1616R/L17	▲	16×16	125	15	2.5	17	ZCED02□□		
	2020R/L10	▲	20×20	125	19	2.5	10	ZCED02□□	G870-85-M5×20	WH5L
	2020R/L17	▲	20×20	125	19	2.5	17	ZCED02□□		
	2525R/L10	▲	25×25	150	24	2.5	10	ZCED02□□		
	2525R/L17	▲	25×25	150	24	2.5	17	ZCED02□□		
QEFD	1616R/L10	▲	16×16	125	14.8	3	10	ZcFD03□□	G870-85-M5×20	WH4L
	1616R/L17	▲	16×16	125	14.8	3	17	ZCFD03□□		
	2020R/L10	▲	20×20	125	18.8	3	10	ZCFD03□□	G870-85-M×20	WH5L
	2020R/L17	▲	20×20	125	18.8	3	17	ZCFD03□□		
	2525R/L10	▲	25×25	150	23.8	3	10	ZCFD03□□		
	2525R/L17	▲	25×25	150	23.8	3	17	ZCFD03□□		
QEGD	2020R/L13	▲	20×20	140	18.5	4	13	ZCGD04□□	G870-85-M5×20	WH5L
	2020R/L22	▲	20×20	140	18.5	4	22	ZCGD04□□		
	2525R/L13	▲	25×25	150	23.5	4	13	ZCGD04□□		

▲Stock available △Make-to-order

Parting inserts



Double edges

Single edge

Type	Basic dimensions(mm) W±0.1	R±0.1	Cutting depth La max.	Grade CVD Coating YBC151	CVD Coating YBC251	PVD Coating YBG205	PVD Coating YBG302	Cemented carbide YD101
Double edges ZPAD01502-MG	1.5	0.2	12		○	★	○	
ZPBD0202-MG	2.0	0.2	14		○	★	○	
ZPED02502-MG	2.5	0.2	17		○	★	★	
ZPFD0302-MG	3.0	0.2	17		○	★	○	
ZPGD0402-MG	4.0	0.2	22		○	★	○	
ZPHD0503-MG	5.0	0.3	22		○	★	○	
ZPKD0604-MG	6.0	0.4	22		○	★	○	
Single edge ZPES02502-MG	2.5	0.2			○	★	★	
ZPFS0302-MG	3.0	0.2			○	★	○	
ZPGS0402-MG	4.0	0.2			○	★	○	
ZPHS0503-MG	5.0	0.3			○	★	○	
ZPKS0604-MG	6.0	0.4			○	★	○	

The single-edge insert is only mounted on parting blade.

■Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

1 Selection of tool holder type

2 Tool holder type, Size and applicable inserts

3 Insert type, Chip-breaker, Size and grade

Parting and grooving inserts

Little squirrel series

	ZP□D-MG	ZP□S-MG	ZT□D-MG
Cutting edge width	1.5,2,2.5,3,4,5,6	2.5,3,4,5,6	2.5,3,4,5,6
Page	A259	A259	A260

Parting inserts



Double edges

Single edge

Type	Basic dimensions(mm) W±0.1	R±0.1	Cutting depth La max.	Grade CVD Coating YBC151	CVD Coating YBC251	PVD Coating YBG205	PVD Coating YBG302	Cemented carbide YD101
Double edges ZPAD01502-MG	1.5	0.2	12		○	★	○	
ZPBD0202-MG	2.0	0.2	14		○	★	○	
ZPED02502-MG	2.5	0.2	17		○	★	★	
ZPFD0302-MG	3.0	0.2	17		○	★	○	
ZPGD0402-MG	4.0	0.2	22		○	★	○	
ZPHD0503-MG	5.0	0.3	22		○	★	○	
ZPKD0604-MG	6.0	0.4	22		○	★	○	
Single edge ZPES02502-MG	2.5	0.2			○	★	★	
ZPFS0302-MG	3.0	0.2			○	★	○	
ZPGS0402-MG	4.0	0.2			○	★	○	
ZPHS0503-MG	5.0	0.3			○	★	○	
ZPKS0604-MG	6.0	0.4			○	★	○	

The single-edge insert is only mounted on parting blade.

■Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

1 Selecting insert type

2 Insert type, Chip-breaker, Size and grade

Guide of selecting threading tools

Threading tools

Page A313 A314

1 Selection of tool holder type

External threading tools



Type		Stock	Basic dimensions(mm)					Applicable inserts	Inserts screw	Shim	Shim screw	Wrench
			H	h	b	L	s					
ZSER	1616H16	▲	16	16	16	100	20	Z16ERCDDDD	880 M3.5X12TT	MT16-CDCMN	SM4X8C	WT15IP
	2020K16	▲	20	20	20	125	25					
	2525M16	▲	25	25	25	150	32					
	3225P16	▲	32	32	25	170	32					
	3232P16	▲	32	32	32	170	40					
	2525M22	▲	25	25	25	150	32	Z22ERCDDDD	880 M5X17	MT22-CDCMN	SM5X8.5	WT20IP
	3225P22	▲	32	32	25	170	32					
	3232P22	▲	32	32	32	170	40					
	4040S22	○	40	40	40	250	50					
ZSEL	1616H16	▲	16	16	16	100	20	Z16ELDDDD	880 M3.5X12TT	MT16-CDCMN	SM4X8C	WT15IP
	2020K16	▲	20	20	20	125	25					
	2525M16	▲	25	25	25	150	32					
	3225P16	▲	32	32	25	170	32					
	3232P16	▲	32	32	32	170	40					
	2525M22	▲	25	25	25	150	32	Z22ELDDDD	880 M5X17	MT22-CDCMN	SM5X8.5	WT20IP
	3225P22	▲	32	32	25	170	32					
	3232P22	▲	32	32	32	170	40					
	4040S22	○	40	40	40	250	50					

▲Stock available ○Make-to-order

2 Tool holder type, Size and applicable inserts

ISO metric thread (with end)



Type			Basic dimensions(mm)				Recommended coating grade	
	The right hand tools	The left hand tools	Pitch	S	Ø1.C	ed	YBG205	YBG205
External thread	Z16ER0.5ISO	Z16EL0.5ISO	0.50	3.52	9.525	4.0	★	○
	Z16ER0.75ISO	Z16EL0.75ISO	0.75	3.52	9.525	4.0	★	○
	Z16ER1.0ISO	Z16EL1.0ISO	1.00	3.52	9.525	4.0	★	○
	Z16ER1.25ISO	Z16EL1.25ISO	1.25	3.52	9.525	4.0	★	○
	Z16ER1.5ISO	Z16EL1.5ISO	1.50	3.52	9.525	4.0	★	○
	Z16ER1.75ISO	Z16EL1.75ISO	1.75	3.52	9.525	4.0	★	○
	Z16ER2.0ISO	Z16EL2.0ISO	2.00	3.52	9.525	4.0	★	○
	Z16ER2.5ISO	Z16EL2.5ISO	2.50	3.52	9.525	4.0	★	○
	Z16ER3.0ISO	Z16EL3.0ISO	3.00	3.52	9.525	4.0	★	○
	Z22ER3.5ISO	Z22EL3.5ISO	3.50	4.65	12.7	5.0	★	○
	Z22ER4.0ISO	Z22EL4.0ISO	4.00	4.65	12.7	5.0	★	○
	Z22ER4.5ISO	Z22EL4.5ISO	4.50	4.65	12.7	5.0	★	○
	Z22ER5.0ISO	Z22EL5.0ISO	5.00	4.65	12.7	5.0	★	○
	Z22ER5.5ISO	Z22EL5.5ISO	5.50	4.65	12.7	5.0	★	○
	Z22ER6.0ISO	Z22EL6.0ISO	6.00	4.65	12.7	5.0	★	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

3 Insert type, Chip-breaker, Size and grade

Threading inserts



	External thread	Internal thread	External thread	Internal thread
Pitch/ Number of pitch	0.5~6	0.5~6	0.5~5	0.5~5
Page	A298	A299	A300	A300

1 Selecting insert category

ISO metric thread (with end)



Type			Basic dimensions(mm)				Recommended coating grade	
	The right hand tools	The left hand tools	Pitch	S	Ø1.C	ed	YBG203	YBG205
External thread	Z16ER0.5ISO	Z16EL0.5ISO	0.50	3.52	9.525	4.0	★	○
	Z16ER0.75ISO	Z16EL0.75ISO	0.75	3.52	9.525	4.0	★	○
	Z16ER1.0ISO	Z16EL1.0ISO	1.00	3.52	9.525	4.0	★	○
	Z16ER1.25ISO	Z16EL1.25ISO	1.25	3.52	9.525	4.0	★	○
	Z16ER1.5ISO	Z16EL1.5ISO	1.50	3.52	9.525	4.0	★	○
	Z16ER1.75ISO	Z16EL1.75ISO	1.75	3.52	9.525	4.0	★	○
	Z16ER2.0ISO	Z16EL2.0ISO	2.00	3.52	9.525	4.0	★	○
	Z16ER2.5ISO	Z16EL2.5ISO	2.50	3.52	9.525	4.0	★	○
	Z16ER3.0ISO	Z16EL3.0ISO	3.00	3.52	9.525	4.0	★	○
	Z22ER3.5ISO	Z22EL3.5ISO	3.50	4.65	12.7	5.0	★	○
	Z22ER4.0ISO	Z22EL4.0ISO	4.00	4.65	12.7	5.0	★	○
	Z22ER4.5ISO	Z22EL4.5ISO	4.50	4.65	12.7	5.0	★	○
	Z22ER5.0ISO	Z22EL5.0ISO	5.00	4.65	12.7	5.0	★	○
	Z22ER5.5ISO	Z22EL5.5ISO	5.50	4.65	12.7	5.0	★	○
	Z22ER6.0ISO	Z22EL6.0ISO	6.00	4.65	12.7	5.0	★	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

2 Insert type, Chip-breaker, Size and grade

Cemented carbide and cermet inserts

Negative inserts

For finishing	DNEG-NGF	VNEG-NGF	CNMG-DF	CNMG-SF	CNMG-EF	CNEG-NF	DNMG-DF
Cutting edge length	15	16	09,12	09,12	09,12	12	11,15
Page	A62	A81	A54	A54	A54	A55	A61

	DNMG-SF	DNMG-EF	DNEG-NF	SNMG-DF	SNMG-EF	SNMG-SF	TNMG-DF	TNMG-SF
Cutting edge length	11,15	11,15	15	09,12	09,12,15	09,12,15	16,22	11,16,22
Page	A62	A62	A62	A67	A67	A67	A75	A75

	TNMG-EF	VNMG-DF	VNMG-EF	VNEG-NF	VNMG-SF	WNMG-DF	WNMG-SF	WNMG-EF
Cutting edge length	11,16,22	16	16	16	16	06,08	06,08	06,08
Page	A76	A81	A81	A81	A81	A83	A83	A84

	WNEG-NF	Wiper	For finishing	CNMG-WGF	DNMX-WGF	TNMX-WGF	WNMG-WGF
Cutting edge length	08			12	11,15	16	06,08
Page	A84			A54	A61	A75	A83

For semi-finishing	CNMG-WGM	DNMX-WGM	TNMX-WGM	WNMG-WGM	For semi-finishing	CNMG-PM
Cutting edge length	12	15	16	06,08		09,12,16,19
Page	A55	A63	A76	A84		A55

	CNMG-DM	CNMG-EM	CNMG-NM	DNMG-PM	DNMG-DM	DNMG-EM	DNMG-NM	SNMG-PM
Cutting edge length	09,12,16,19	12,16	12	11,15	11,15	11,15	15	09,12,15,19
Page	A56	A56	A57	A63	A64	A64	A64	A68

	SNMG-DM	SNMG-EM	SNMG-NM	TNMG-PM	TNMG-DM	TNMG-EM	VNMG-PM	VNMG-DM
Cutting edge length	09,12,15,19	12,15	12	11,16,22	11,16,22	16,22	16	16
Page	A68	A69	A69	A76	A77	A77	A82	A82

Negative inserts

VNMG-EM	**VNMG-NM**	**WNMG-PM**	**WNMG-DM**	**WNMG-EM**	**WNMG-NM**	
Cutting edge length: 16	16	06,08	06,08	06,08	08	
Page: A82	A82	A85	A85	A85	A86	

For roughing						
	CNMG-SNR	**DNMG-SNR**	**SNMG-SNR**	**TNMG-SNR**	**VNMG-SNR**	**WNMG-SNR**
Cutting edge length	12,16,19	15	12	16	16	08
Page	A58	A65	A71	A78	A82	A86

CNMM-LR	**DNMM-LR**	**SNMM-LR**	**TNMM-LR**	**CNMG-DR**	**CNMM-DR**	**CNMG-ER**	**CNMM-ER**
Cutting edge length: 12,16,19,25	15	12,15,19,25	16,22	12,16,19	12,16,19,25	12,16,19	25
Page: A57	A65	A69	A77	A58	A58	A58	A58

DNMG-DR	**DNMM-DR**	**DNMG-ER**	**DNMM-ER**	**SNMG-DR**	**SNMM-DR**	**SNMG-ER**	**SNMM-ER**
Cutting edge length: 15	15	15	15	12,15,19	12,15,19,25	12,15,19	25
Page: A65	A65	A65	A65	A70	A70-A71	A71	A71

TNMG-DR	**TNMM-DR**	**TNMG-ER**	**WNMG-DR**				
Cutting edge length: 16,22,27	16,22,27	16,22	06,08				
Page: A78	A78	A78	A86				

For heavy machining							
	CNMM-HPR	**SNMM-HPR**		**CNMM-HDR**	**DNMM-HDR**	**SNMM-HDR**	**TNMM-HDR**
Cutting edge length	19,25	19,25		12,16,19	15	12,15,19,25	16,22,27
Page	A59	A72		A59	A66	A72	A79

				For profiling		All round	
175.32-22/227	**175.32-24**	**175.32-25**	**175.32-28**		**KNUX**		**CNMG**
Cutting edge length: 19	19,30	19	19		16		12,16,19
Page: A88	A88	A88	A88		A87		A60

CNMM	**DNMG**	**SNMG**	**SNMM**	**TNMG**	**TNMM**	**VNMG**
Cutting edge length: 12,19	15,19	09,12,15,19,25	09,12,19,25	11,16,22,27,33	16,22,27	16
Page: A60	A66	A73	A73-74	A79	A80	A82

Negative inserts

Without chipbreaker

	CNMA	DNMA	SNMA	TNMA	WNMA
Cutting edge length	12,16,19	11,15	09,12,15,19	16,22,27	06,08
Page	A59	A66	A74	A80	A86

Positive inserts

For extra finishing -USF

	CCGT-USF	DCGT-USF	TCGT-USF	VCGT-USF	DPGT-USF	VPGT-USF
Cutting edge length	09	07,11	11	08,11	07,11	08,11
Page	A89	A93	A100	A105	A111	A114

	CCGT-SF	DCGT-SF	TCGT-SF	VCGT-SF	VBGT-SF	CPGT-SF	DPGT-SF	TBGH-L
Cutting edge length	06,09	07,11	06,09,11	11	11	06,09	07,11	06
Page	A89	A93	A100	A105	A108	A110	A111	A112

	TPGT-SF	TPGH-L
Cutting edge length	09,11	09,11
Page	A113	A113

For finishing

	VCGT-NGF	VBET-NGF	CCMT-HF	CCMT-EF	DCMT-HF	DCMT-EF	SCMT-HF
Cutting edge length	16	16	06,09,12	06,09,12	07,11	07,11	09
Page	A105	A108	A89	A90	A93	A94	A98

	SCMT-EF	TCMT-HF	TCMT-EF	VCGT-HF	VCGT-NF	VBMT-EF	VBMT-HF	VBET-NF
Cutting edge length	09	06,09,11,16	09,11,16	11	16	11,16	11	16
Page	A98	A101	A102	A105	A105	A108	A108	A108

For semi-finishing

	CCMT-HM	CCMT-EM	DCMT-HM	DCMT-EM	SCMT-HM	SCMT-EM	TCMT-HM
Cutting edge length	06,09,12	06,09,12	07,11	07, 11	09,12	09,12	09,11,16
Page	A90	A90	A94	A94	A98	A98	A103

Positive inserts

	TCMT-EM	VBMT-EM	VBMT-HM
Cutting edge length	09,11,16	11	16
Page	A102	A109	A109

For roughing

	VBMT-SNR	CCMT-HR	DCMT-HR	SCMT-HR	TCMT-HR	VBMT-HR
Cutting edge length	16	06,09,12	11	09,12	09,11,16,22	16
Page	A109	A91	A95	A99	A103	A109

For Al machining

	CCGX-LC	DCGX-LC	SCGX-LC	TCGX-LC	VCGX-LC	CCGX-LH	DCGX-LH
Cutting edge length	06,09,12	07,11	09,12	09,11,16	11,16,22	06,09,12	07,11
Page	A91	A95	A99	A103	A106	A91-92	A95

All round

	RCGX-LH	SCGX-LH	TCGX-LH	VCGX-LH	RCM(G)T	RCMX	SCMT
Cutting edge length	08	09,12	09,11,16	11,16,22	08,10,12,16	08,10,12,16,20,25,32	09,12
Page	A96	A99	A104	A106	A96	A97	A99

Without chipbreaker

	TCMT	WCMX-53	CCMW	DCMW	SCMW	TCMW	SPMW
Cutting edge length	22	04,06,08	06,09,12	07,11	06,09,12	11,16,22	09,12
Page	A104	A107	A92	A95	A99	A104	A112

Negative inserts

New PCBN&PCD inserts

PCBN inserts

	CNGA	DNGA	SNGA	TNGA	VNGA	WNGA
Cutting edge length	12	15	12	16	16	08
Page	A118	A121	A126	A130	A133	A136

PCBN inserts turning case

	CNGN	DNGN	SNGN	TNGN	VNGN	WNGN
Cutting edge length	12	15	12	16	16	08
Page	A120	A125	A129	A132	A135	A138

Positive inserts

PCBN inserts

	CCGW	DCGW	TCGW	VBGW	VCGW
Cutting edge width	06,09,12	07,11	09,11	16	16
Page	A139	A140	A141	A142	A143

PCD 0° Front Angle Blade

	CCGW□□AF	DCGW□□AF	TCGW□□AF	VBGW□□AF	VCGW□□AF
Cutting edge length	06,09,12	07,11	09,11	16	16
Page	A144	A145	A146	A147	A148

PCD 7° Front Angle Blade

	CCMX□□AF	DCMX□□AF	TCMX□□AF	VBMX□□AF	VCMX□□AF
Cutting edge width	06,09,12	07,11	09,11	16	16
Page	A144	A145	A146	A147	A148

Ceramic inserts

	RCGN	RPGN
Cutting edge width	09,12	09,12
Page	A152	A152

Parting and grooving inserts

Little squirrel series — QC series shallow grooving inserts

	QC□□R/L	QC□□R/L□□□R	ZP□D-MG	ZP□S-MG
Cutting edge width	1.1~4.8	1.0~4.0	1.5,2.0,2.5,3,4,5,6	2.5,3,4,5,6
Page	A267-268	A268	A259	A259

	ZT□D-MG	ZT□D-MM	ZT□S-MG	ZT□D-EG	ZT□D-EG	ZIMF-NM	ZIMF-SM
Cutting edge width	2.5,3,4,5,6	1.5,2,3,4,5,6,8	5,6	1-2.4(tailor-made)	2.4-6.5(tailor-made)	3,4,5,6	3,4,5,6
Page	A260	A260	A260	A261	A261	A262	A262

	ZR□D-MG	ZR□D-NM	ZR□D-EG	ZIGQ-NM	ZIGQ-NF	ZR□D-LH	ZILD-LC
Cutting edge width	2.5,3,4,5,6	3,4,5,6	3,4,5,6	3,4,5,6	3,4,5,6	6,8	8
Page	A263	A263	A263	A264	A264	A265	A265

Supplemental series

	ZQMX-1E
Cutting edge width	3.125,4.125,5.125,6.4,7.05
Page	A269

Threading inserts

Right hand type shown	ISO metric thread		General pitch thread		Whitworth thread	
	External thread	Internal thread	External thread	Internal thread	External thread	Internal thread
Pitch/ Number of pitch	0.5~6	0.5~6	0.5~5	0.5~5	8~19	8~19
Page	A298	A299	A300	A300	A301	A301

Right hand type shown	Unified thread		British Standard pipe thread		American standard pipe thread	
	External thread	Internal thread	External thread	Internal thread	External thread	Internal thread
Pitch/ Number of pitch	8~24	8~24	11~28	11~28	8~27	8~27
Page	A302	A302	A303	A303	A304	A304

Right hand type shown	ISO metric thread(Thin type)		General pitch thread(Thin type)		Whitworth thread(Thin type)	
Thin threading inserts series						
	External thread	Internal thread	External thread	Internal thread	External thread	Internal thread
Pitch/ Number of pitch	0.5~3.0	0.5~3.0	0.5~5.0(5~48)	0.5~5.0(5~48)	8~16	8~16
Page	A306	A306	A307	A307	A308	A308

Right hand type shown	Unified thread(Thin type)		British Standard pipe thread(Thin type)		American standard pipe thread (Thin type)	
	External thread	Internal thread	External thread	Internal thread	External thread	Internal thread
Pitch/ Number of pitch	8~20	8~20	11~28	11~28	8~27	8~27
Page	A309	A309	A310	A310	A311	A311

Tool holders for external turning

D-type clamping system

DCLNR/L	DDJNR/L	DSBNR/L	DTGNR/L	DVVNN	DVJNR/L	DWLNR/L
Approach angle 95°	93°	75°	91°	72°30'	93°	95°
Page A166	A167	A168	A169	A170	A170	A171

P-type clamping system

PCBNR/L	PCLNR/L	PDJNR/L	PDPNN	PSBNR/L	PSDNN	PSKNR/L
Approach angle 75°	95°	93°	62°30'	75°	45°	75°
Page A172	A173	A174	A175	A176	A177	A178

PSSNR/L	PTFNR/L	PTTNR/L	PTGNR/L	PWLNR/L
Approach angle 45°	90°	60°	90°	95°
Page A179	A180	A181	A182	A183

S-type clamping system

SCACR/L	SCLCR/L	SDACR/L	SDJCR/L	SDNCN	SVJBR/L	SVABR/L
Approach angle 90°	95°	90°	93°	62°30'	93°	90°
Page A184	A185	A186	A187	A188	A189	A190

SVVBN	SVVCN	SVJCR/L	SSBCR/L	SSDCN	SSKCR/L	SSSCR/L
Approach angle 72°30'	72°30'	93°	75°	45°	75°	45°
Page A191	A192	A193	A194	A195	A196	A197

STACR/L	STFCR/L	STGCR/L	STECR/L	SWACR/L	SRDCN	SRGCR/L
Approach angle 90°	90°	91°	60°	90°		
Page A198	A198	A199	A200	A201	A202	A203

C-type clamping system

CKJNR/L	CKNNR/L
Approach angle 93°	63°
Page A204	A204

Turning tool holders for ceramic inserts

CRDCR/L	CRDPR/L
Approach angle	
Page A205	A205

Turning tool holders for internal machining

P-type clamping system

PCLNR/L	PDPNR/L	PDUNR/L	PSKNR/L	PTFNR/L	PWLNR/L
Approach angle 95°	62°30'	93°	75°	90°	95°
Page A212	A213	A214	A215	A216	A217

S-type clamping system

SCLCR/L	SDQCR/L	SDUCR/L	SDZCR/L	SSKCR/L	STFCR/L	SVQCR/L
Approach angle 95°	107°30'	93°	95°	75°	90°	107°30'
Page A218	A219	A220	A221	A222	A223	A224

SVUCR/L	SVQBR/L	SVUBR/L	SCLPR/L	SDQPR/L	SDUPR/L	STUPR/L
Approach angle 93°	107°30'	93°	95°	107°30'	93°	93°
Page A225	A226	A227	A228	A229	A230	A231

SCFCR	SCLCR
Approach angle 90°	95°
Page A232	A233

Damping tool holders

SCLPR/L	SDQPR/L	SDUPR/L	STUPR/L	SVQCR/L	SVUCR/L
Approach angle 95°	107°30'	93°	93°	107°30'	93°
Page A235	A236	A237	A238	A239	A240

Parting and grooving tools

QE□□R/L	QECDR/L	QX□DR/L	QE□SR/L	QE□S□□N	QZS□	QF□□R/L
Page A272-A273	A273	A274	A274	A275	A275	A276-A277

QF□□RR/LL	QF□DR/L	C□□□-Q□DR/L	C40X-Q□DR/L	QZQ□□R/L	GQCR/L	S□□□-QC□□□□R/L
Page A278-A281	A282-A283	A284	A284	A288	A286	A286

Threading tools

ZSER/L	ZSIR/L
Page A313	A314


-WGM
Wiper
-WGF

-HPR
New Generation of
Roughing Chipbreaker
-LR


-LC chipbreaker
for Al machining

YBM215
Outstanding wear nesrrtance,extends the tool life
achieves high effrcrent processing
Grade for stainless
steel machrning
YBM153
Best choice for cutting stainless steel
with high speed unceer good working condition


ISO
Code
General turning
Coating
CVD
PVD
Cermet
Coated cermet
Ceramic
Cemented carbide
PCBN
PCD
Threading
Coating
PVD
Parting and grooving
Coating
CVD
PVD
Cemented carbide
P Steel
M Stainless steel
K Cast iron
N Non ferrous metal
S Heat resistant alloy & Ti alloy
H Super hard material
01
10
20
30
40
YBC151
YBC251
YBC152
YBC252
YBC351
YBC352
YBG102
YBG202
YNG151
YNG151C
YBG202
YBG203
YBC151
YBC251
YBG205
YBG302
YC10
YC40
YBM151
YBM153
YBM251
YBM253
YBG202
YBM215
YBG205
YNG151
YNG151C
YBG202
YBG203
YBG205
YBG302
YBD052
YBD102
YBD152
YBD252
YNG151
YNG151C
CN3100
YD201
BK1011
BK1021
BK2541
BK2511
YBG202
YBG203
YBG205
YBG302
YD201
DN1021
DN0121
DN3021
YD101
YBG202
YBG203
YD101
YBS103
YBG102
YBG105
YBG212
YBG202
CN3100
YD101
BS1011
BS2011
BS3011
YBG202
YBG203
YBS103
YBG102
YBG105
YBG302
YBG212
YBG202
YD101
BH0121
BH1020
BH2011
BH2511
BH3511
CN3100
YBG202
YBG203

How to select general turning inserts

Turning inserts list

- Turning inserts listed according to shape
- Sequence of listed inserts
  - ▸Negative inserts (with hole – without hole)
  - ▸Positive inserts (with hole – without hole)
- Sequence of listed chipbreaker
  For finishing – For semi-finishing – For roughing – For heavy cutting – Without chipbreaker– Through chipbreaker





TURNING A

General turning inserts

General turning inserts overview A22-A26

Application instruction of general turning inserts A27-A49

General turning inserts A50-A152

General turning inserts code key A50-A51

Metric-Inch comparison table for general turning inserts A52-A53

Cemented carbide and cermet inserts A54-A114

Negative inserts A54-A88

Positive inserts A89-A114

PCBN&PCD inserts A115-A149

PCBN&PCD inserts code key A116-A117

PCBN&PCD inserts A118-A149

Ceramic inserts A150-A152

Ceramic inserts code key A150-A151

Ceramic inserts A152







Negative inserts with hole

Appli-cation	Chipbreaker	Preci-sion	Recommended cutting parameters	Chipbreaker profile	Feature/Shape of insert
For finishing	SF	M			**Recommended chipbreaker for finishing of P-type materials** Double-sided chipbreaker with M-level tolerance has outstanding performance in finishing, achieving good surface quality.
	DF	M			**Recommended chipbreaker for finishing of P- type materials** Double-sided chipbreaker with M-level tolerance has sharp edges, which can effectively cut off stainless steel and avoid adhering and surface hardening, achieving high surface quality.
	EF	M			**Recommended chipbreaker for finishing of M-type materials** Double-sided chipbreaker with M-level tolerance can prevent wear and hardening to achieve high machining precision and good surface quality.
	NF	E			**Recommended chipbreaker for finishing of S-type materials** Double-sided chipbreaker with E-level tolerance can prevent wear and hardening to achieve high machining precision and good surface quality.
	NGF	E			**Recommended chipbreaker for finishing of S- materials** E-class double side chip breaker with excellent sharp edge.High positioning accuracy, light cutting force.-NGF is recommended chip breaker for S series material general finishing.
	WGF	M			**Recommended chipbreaker for finishing of S- materials** E-class double side chip breaker with excellent sharp edge.High positioning accuracy, light cutting force.-NGF is recommended chip breaker for S series material general finishing.
For semi-finishing	DM	M			**Recommended chipbreaker for semi-finishing of P-type materials** Double-sided chipbreaker with M-level tolerance produces small cutting forces and has large chip breaking range, which ensures good performance for machining highly adhesive alloy steel.
	PM	M			**Recommended chipbreaer for semi-finishing of P-type materials** Double-sided chipbreaker with M-level tolerance has higher strength of cutting edge than chipbreaker DM. It is suitable for semi-finishing under unstable working conditions as well as machining cast iron with small cutting forces.

Negative inserts with hole

Appli-cation	Chipbreaker	Preci-sion	Recommended cutting parameters	Chipbreaker profile	Feature/Shape of insert
For semi-finishing	NM	M			**Recommended chipbreaker for semi-finishing of S-type materials** Double-sided chipbreaker with M-class tolerance keeps high precision after inserts are turned, with good capability to prevent wear and hardening to achieve higher machining efficiency than chipbreaker NF.
	EM	M			**Recommended chipbreaker for semi-finishing of M-type materials** Double-sided chipbreaker with M-level tolerance can solve the processing problems such as chip breaking and adhering of stainless steel, achieving higher machining efficiency than chipbreaker EF.
	WGM	M			**Wiper chipbreaker for semi-finishing** Double-sided chipbreaker with M-level tolerance, semi-finishing chipbreaker with wiper designed, perfect combination of good wiper result and sturdy cutting edge structure, which perfectly meet the requirement of high efficiently and good surface quality.
	All round	M			**From semi-finishing to roughing of P-type, M-type, K-type materials** Double-sided chipbreaker with M-level tolerance has good cutting edge strength and wide application.
Light-load roughing	DR Double-side	M			**Recommended chipbreaker for light roughing of P-type and K-type materials** Double-sided chipbreaker with M-level tolerance is the first choice for light roughing, can achieve high evacuation rate and efficiency of cutting edge.
	LR Single-side	M			**Recommended chipbreaker for light-load roughing of P-type materials** Single-sided general chipbreaker with M-level tolerance, has wide chip breaking range and sharp cutting edge is designed with inclined angle, which enables it to cut lightly and easily and control the chipping flow direction. Chip-leaded-stages can reduces the contact area with chips, so that heat can easily be dissipated.
For roughing	ER Single/Double side	M		Double sided 	**Recommended chipbreaker for roughing of M-type materials** Single / double-sided chipbreaker with M-level tolerance has good capacity of impact-resistance. It is designed to achieve balance between security and sharpness of the cutting edge, and it can achieve high efficiency by preventing the problems of adhering and high cutting heat when roughing stainless steel.
				Single sided 	

Negative inserts with hole

Appli-cation	Chipbreaker	Preci-sion	Recommended cutting parameters	Chipbreaker profile	Feature/Shape of insert
For roughing	DR Single-side	M			**Recommended chipbreaker for roughing of P-type materials** Single-sided chipbreaker with M-level tolerance has high security of cutting edge, which can achieve high feed rate and low cutting forces at great cutting depth and high feed rate.
	SNR	M			**Recommended chipbreaker for S-material high efficiency roughing** M-level double-sided chipbreaker perfectly combines sharpness and strength of the cutting edge, with small cutting resistance and high edge strength can effectively reduce groove wear. SNR is recommended chipbreaker for high depth roughing of S- materials.
Heavy-load machining	HDR Single-side	M			**Recommended chipbreaker for heavy lad machining of P materials** M level single-sided chip breaker with strengthen cutting edges, high safety and excellent plastic deformation resistance under high metal removal rate.
	HPR Single-side	M			**Recommended chipbreaker for heavy-load machining of P-type materials** Single-sided chipbreaker with M-level tolerance, strong cutting edge. Multi-stages chipbreaker ensures the flowing of chip and heat dissipation of insert. It is suitable for machining under unstable and relatively bad working condition, especially for external roughing of work piece with a rough oxidized surfaces.
Cast iron machining	Without chipbreaker	M			**For cast iron machining** Double-sided chipbreaker with M-level tolerance has high cutting edge strength. It can overcome inferior factors such as intettruption and vibration, etc. when machining cast iron.
Super hard inserts	Without chipbreaker	G			**For machining of non-ferrous metal and high-hardness metal** G-level tolerance is the best choice for machining non-ferrous metals and high-hardness material by welding PCBN and PCD material to cemented carbide substrate.
Ceramic inserts	Without chipbreaker	G			**For roughing of K-, H- high-temperature alloy roughing** Sialon Ceramics, V-positioning, solution for high-speed machining of cast iron, hardened steel and superalloy.

Positive inserts with hole

Appli-cation	Chipbreaker	Preci-sion	Recommended cutting parameters	Chipbreaker profile	Feature/Shape of insert
For extra finishing	USF	G			**Precision turning chipbreaker** With G-level tolerance, large rake angle, sharp cutting edge, for soft cutting action, this is the first choice for precision turning of small shaft parts.
	R/L	G			**Recommended chipbreaker for precise boring inserts** With G-level tolerance, sharp cutting edge and small nose radius, it can effectively reduce the vibration in machining and is suitable for boring and external turning.
	SF	G			**First choice for finishing with high requirements on chipbreaker** With G-level tolerance, it is the first choice for precise finishing due to its excellent performance on chip breaking.
For finishing	HF	M			**Chipbreaker for finishing with wide application** With M-level tolerance, it is suitable for internal and external finishing of various materials such as steel and cast iron.
	EF	M			**Recommended chipbreaker for finishing of M-type materials** With M-level tolerance, it has sharp cutting edges and is suitable for cutting adhesive materials such as stainless steel, soft steel, etc.
	NF	E G			**Recommended chipbreaker for finishing S-type materials** With E and G-level tolerance and sharp cutting edges, it is suitable for internal and external finishing of high-temperature alloy materials.
	NGF	E G			**Recommended chipobreaker for S-material general finishing** E, G grade accuracy, for inner hole finishing of S materials.
For semi-finishing	HM	M			**Chipbreaker for semi-finishing with wide application** With M-level tolerance, it is suitable for internal and external semi-finishing of materials like steel, cast iron, etc.
	EM	M			**Recommended chipbreaker for semi-finishing of M-Type materials** With M-level tolerance, it has higher hardness of cutting edge than EF and can achieve higher efficiency.

Positive inserts with hole

Application	Chipbreaker	Precision	Recommended cutting parameters	Chipbreaker profile	Feature/Shape of insert
For semi-finishing	All round	M			**Recommended chipbreaker for semi-finishing of M-type materials** With M-level tolerance, it is suitable for profile machining materials like steel, cast iron, etc.
Cast iron machining	Without chipbreaker	M G			**Chipbreaker for machining of cast iron** With M- and G- level tolerance, it has high cutting edge strength and is suitable for internal and external machining of cast iron.
For roughing	HR	M			**General chipbreaker for roughing** With M-level tolerance, it is suitable for both internal and external roughing of materials such as steel, stainless steel, cast iron, etc.
	Special chipbreaker	M			**Recommended chipbreaker for heavy machining of P-type materials** Single-sided with M-level tolerance, it has good cutting edge strength with high security. It is the first choice for profile roughing.
	SNR	M			**Recommended chipobreaker for S-material high-efficiency roughing** M-level accuracy, for inner hole roughing of S materials.
For Al machining	LC	G			**Chipbreaker for machining of Al alloy** With G-level tolerance, large rake angle and clearance angle make the cutting edge sharper, ensuring easy and fast cutting while remaining effective chip breaking.
	LH	G			**Special chipbreaker for machining of Al alloy** With G-level tolerance, large rake angle and polishing treatment on surface, it can effectively prevent built-up edge and achieve high workpiece surface quality while maintaining long life.
Super hard inserts	Without chipbreaker	G			**Special chipbreaker for non-ferrous metals and materials with high hardness** With G-level tolerance, it is the best choice for machining of non-ferrous metals and materials with high-hardness by welding PCBN and PCD material to cemented carbide substrate.

Chip breaking range reference for general turning inserts

Negative inserts



▶ Workpiece material: 45# steel



▶ Workpiece material: stainless steel (1Cr18Ni9Ti)

Positive inserts



▶ Workpiece material: 45# steel



▶ Workpiece material: stainless steel (1Cr18Ni9Ti)

Cutting test for chip breaking range of general turning inserts

Case

Insert: CNMG120408-DF
Toolholder: PCLNL2525M12
Workpiece material: 45# steel
Cutting speed: 200m/min





-USF

Precision turning chipbreaker

- Effective chip control due to the proper chipbreaker.
- Large rake angle makes cutting easier and faster.



- Nose radius precision controlled within 0.02mm for excellent machining precision.
- Special surface after-treatment for better surface quality.
- High strength screw clamping ensures good repeatability and accuracy .





Application range of USF chipbreaker



Workpiece material: 42CrMo



Workpiece material: 1Cr18Ni9Ti

-LC chipbreaker for aluminum

- -LC inserts are designed with a special chipbreaker. Large rake angle and clearance angle make the cutting edge sharper, ensuring easier cutting while remaining effective chip breaking.
- Achieved the mirror rake face after special treatment. Reduced the friction resistence, and stick free. Accordingly, make the chip removal fluently and improve the surface quality and tool life.
- The G-class tolerance of insert, higher Repeated Position Accuracy, at the same time, it can effectively avoid the vibration during the machining process.

Optimized inclined angel makes controlling the chipping flow direction valid.



Smooth connection of insert nose and cutting edge makes rake face smoother.



–LC and –LH chipbreaker characteristics and machining range

-LC chipbreaker can be used in machining of pure Al, while -LH chipbreaker can not.
-LC chipbreaker expand the chip breaking range of Al alloy machining.





Workpiece material: Pure aluminum

Cutting parameters	V=350m/min Ap=0.2mm F=0.2mm/r	
Chips		
Surface quality		
	-LC chipbreaker	similar products from overseas manufacturers

- **-LH chipbreaker is more suitable for machining aluminum alloy in condition of large cutting depth and high feed rate.**
- **-LC chipbreaker is more suitable for machining aluminum alloy in condition of small cutting depth and low feed rate.**
- **-LC chipbreaker can be used in machining pure aluminum.**

-WGF/WGM

chipbreaker series
Turning inserts with wiper



High efficiency

Roughness remains the same when feed rate is doubled.

Wiper is assembled by three curves to form a circular arc edge. The nose of wiper provides less profile height on the surface that is formed by the cutting edge, resulting in a smooth turning surface.

Inserts with wiper has high efficiency when used for finish and semi-finish turning. The surface quality remains the same even at double feed rate.

Wiper technique = high machining efficiency + high surface quality

High quality

Roughness value is reduced to half when feed rate remains the same.





When used for finishing, it can improve roughness of workpiece surface and achieve turning instead of grinding.
When used for semi-finishing, efficiency could be improved by doubling the feed rate, the roughness of workpiece surface remaining the same.

Guide to use

●Select reasonable approach angle of the tools

Minor angle being close to 0 degree is the reason that inserts with wiper can reduce roughness of the surface, which is determined by the shape of insert and approach angle of the tool holder. Therefore, acceptable roughness of surface is the result of reasonable approach (minor) angle. The finishing function of wiper would be reduced or invalid if unreasonable approach (minor) angle is chosen. For example, the approach angle should be 95°for CNMG / WNMG inserts, while 93°is the best for DNMX.TNMX inserts.

●Be careful with DNMX / TNMX inserts

DNMX / TNMX inserts with wiper don't have wide application. It cannot achieve a wiper result when minor angle is not 0 degree, like chamfer and profile surface, and will even cause over-cutting or no-cutting on workpiece, affecting the shape and size precision of workpiece. Please contact technical service regarding these problems.

S- Ni-based Superalloy Machining

Difficulties Overcame

Features of Ni-based superalloy machining

- High cutting resistance (containing a large amount of alloying elements, severe hardening, great plastic deformation ;
- High cutting temperature;
- Severe wear of inserts.

Chipbreaker for machining of Ni-based superalloy should have tough and sharp insert nose, smooth rake face and proper inclination angle.



-NM for semi-finishing ***-SNR*** for high efficiency roughing

-NF for finishing ***-NGF*** for general finishing



-SNR Chipbreaker for roughing with large depth of cut

- Positive rake angle design, sharp cutting edge, low cutting resistance, effectively reducing groove wear;
- Cutting edge with variable rake angles increase cutting edge strength at large depths of cut. Edge strength increases as the depth of cut increases;
- Large slot width combined with unique edge rib design not only provides excellent chip breaking performance but also can effectively improve edge strength.

-NGF Chipbreaker for General Finishing

- Proper inclination angle design, sharp cutting edge, small cutting resistance;
- E-level tolerance of insert, high clamping accuracy, proper chipbreaker width, good chip breaking performance,excellent surface quality;
- Special edge treatment, high wear resistance.

-NF/NM Chipbreaker for General Finishing

- -NF chipbreaker has sharp cutting edge, while -NM chipbreaker high cutting edge strength.
- Smooth surface of chipbreaker ensures unobstructed chip flow.
- High wear resistance of cutting edge after special treatment.



-EF -EM -ER

Specially designed for machining intensively adhesive and high-plasticity materials such as stainless steel, etc



-EF

Rake angle and inclined angle are specially designed for intensively adhesive stainless steel and high-plasticity materials which are hard to be machined. Sharp cutting edge enables it to cut lightly and easily and achieve good surface quality by well controlling chip breaking. It is especially suitable for finishing these kinds of materials.



-EM

Inserts meet the requirements of machining intensively adhesive materials. Impact resistance of cutting edge is improved in addition to sharpness, which makes it suitable for semi-finishing and intermittent machining of adhesive materials such as austenitic stainless steel, etc.



-ER

Specially designed double rake angle with wide land achieves balance between edge security and sharpness, and effectively reduces cutting resistance and wear on groove.



Number of machined parts / Cutting edge



Machining external of valve

Machining end surface of valve
(intermittent machining)
Workpiece diameter:135mm
Rotating speed:350rpm
Feed rate:0.25mm/r
Cutting depth:1.5mm

Number of machined parts / Cutting edge



Machining external of valve
Workpiece diameter:89mm
Rotating speed:635rpm
Feed rate:0.15mm/r
Cutting depth:1.0mm





-SF Chipbreaker for finishing

- Unique nose design and sharp cutting edge lead to small cutting resistance and effectively reduce vibration of the tool holder.
- With high re-positioning precision, the insert is compatible with specially developed cemented carbide tool holders, which can increase the capability of vibration resistance and improve machining quality.
- Special treatment on insert's surface can reduce the possibility of chips adhering to the rake face of insert. Good performance of chip breaking and chip flowing ensures improved surface quality of workpiece.
- By adopting excellent grade, it is suitable for extra finishing of various materials.





YBC151

The combination of substrate with excellent wear resistance and coating composed of MT-TiCN, thick layer of Al_2O_3 and TiN makes it suitable for finishing steel.

YBC251

The substrate with good toughness and high security of cutting edge, in optimal combination with coating composed of MT-TiCN, thick layer of Al_2O_3 and TiN makes it suitable for steel semi-finishing.

YBC351

The best combination of substrate with high wear resistance and coating composed of MT-Ti (CN), thick Al_2O_3 layer and TiN makes it suitable for finishing and semi-finishing of cast iron materials.

YBM151

Substrate with special structure, in combination with coating composed of TiCN, thin Al_2O_3 layer and TiN, with excellent resistance against diffusive wear and plastic deformation makes it suitable for finishing, semi-finishing and roughing of stainless steel.

YBM251

Combination of substrate with good toughness and strength and coating composed of TiCN, thin Al_2O_3 layer and TiN makes it suitable for semi-finishing and roughing of stainless steel.

Coated Cemented Carbide CVD



BLACK DIAMOND INSERTS

Innovation of machining techniques for stainless steel turning

YBM

YBM153



Best choice for roughing of stainless steel with high-speed under good working condition

Coating

- CVD coating with advanced ultra-fine grain coating technology, greatly improves wear resistance of inserts.
- Thanks to special treatment on transition layer, multi-layer coating are combined firmly.
- The exceptionally smooth coating surface and good low friction ability can reduce the occurrence of built-up edges.

Substrate

- Added with resist high temperature rare element, inserts shows a good capability against plastic deformation and good capability of Red Hardness.
- Unique manufacturing technology improves high temperature toughness and wear resistance of substrate.





Application fields YBM153 is suitable for finishing and semi-finishing of stainless steel with high cutting efficiency under stable working condition. Such as medium-size fluid valve components in petrochemical industry, flange and other parts in auto pipeline, valve and valve body in auto engine systems, ship mechanical parts, aviation hydraulic parts, adapting pieces in IT and semiconductor industry, medium and long-axis in food processing machinery, construction machinery and general machinery.

YBM253



Ideal grade for turning of stainless steel with high cutting depth and high feed rate under bad working condition

Coating

- Ultra-fine grain coating technology provides better wear resistance and toughness;
- Improved remain internal stress design ensures good toughness and anti-cracking performance;
- Polishing treatment on coating surface makes it suitable for cutting adhesive materials.

Substrate

- With gradient carbide substrate insert has better impact resistance and cutting edge strength.



Application fields YBM253 grade is suitable for roughing of heavy stainless steel parts with high cutting depth and high feed rate under the condition with great impact.



BLACK DIAMOND INSERTS

Achieving both higher cutting speed and longer tool life

Second generation of YBC

Coated Cemented Carbide CVD

YBC152

Thick TiCN and thick Al_2O_3 coatings improve the impact toughness and abrasion resistance, which makes it suitable for finishing and semi-finishing of steel at high speed. Cutting speed can increase by more than 25%, while the tool life can increase by more than 30% at the same cutting speed.

YBC252

Comprising of thick TiCN and thick Al_2O_3 coatings, the grade has high capability against plastic deformation and good hardness of cutting edge. It is preferred grade for machining of steel from finishing to roughing. Under the same cutting conditions, the cutting speed can be increased by more than 25%, while the tool life can be 30% longer under the same cutting speed.

YBC352

Thickness TiCN and Al_2O_3 coating, with strongest toughness and plastic deformation resistance, the ideal grade for high efficient steel rough machining under the bad condition.

Perfect unification of toughness and anti-plastic deformation.
Specially designed cutting edge with “skeleton” realizes perfect unification of toughness and anti-plastic deformation.



Roughness of insert surface is improved after special treatment on surface, which effectively reduces cutting forces, prevents workpiece adhering to surface of inserts and improves operation stability of inserts.



The perfect combination of fibrous TiCN and fine grain Al_2O_3 obviously improves abrasion resistance and anti-breakage of inserts.



Test comparison of inserts abrasion

Workpiece material：45#steel
Inserts：CNMG120408-DM
Cutting parameters：Vc=400m/min a_p=1mm fn=0.2mm/r

Grade from other company



YBC152



YBD052

CVD coated grade, which is characterized by super fine grain and smooth surface, is the combination of hard substrate and coating (extra thick Al_2O_3 + thick TiCN). The grade is optimized for best wear resistance when machining gray cast iron at high speed under dry condition.

YBD102

CVD coated grade, which is the combination of hard substrate and coating (thick Al_2O_3 + thick TiCN), shows excellent wear resistance and impact resistance when machining nodular cast iron at high speed.

YBD152

CVD coated grade, which is the combination of hard substrate and coating (medium thick Al_2O_3 + thick TiCN), has good flaking resistance. It is suitable for turning of cast iron at high speed, and light intermittent cutting can be supported even at moderate speed. It is also suitable for milling of cast iron.

YBD252

CVD coated grade, which is the combination of hard substrate and coating (medium thick Al_2O_3 + thick TiCN), achieves the balance between wear resistance and toughness. It is suitable for wet milling of cast iron, which requires toughness (such as nodular cast iron) at moderate or low speed. It is also suitable for intermittent turning.

BLACK DIAMOND INSERTS YBD

First choice for high-efficiency and high-speed machining of cast iron

- The combination of thick coating and substrate with good hardness and impact resistance gives the inserts excellent impact resistance and stability under high temperature, and improves wear resistance of inserts. Inserts also satisfy the requirements of high speed and high feed rate when machining cast iron.
- The appearance of shining full black is easily identified.



Layer of fine grain with compact surface

Significant results

- Working efficiency has been improved. Both the coating and the substrate are suitable for machining cast iron at high speed and high feed rate. Cutting speed can be increased by **30% to 40%**.
- Cost is reduced as tool life is increased by **40%-50%**.
- High machining stability.

Recommended combination of grade and chipbreaker



Recommended cutting parameters

Workpiece material	Range of machining	Grade	Recommended cutting speed(m/min)
P Steel	For finishing	YBC151	180-460
		YBC152	220-500
	For semi-finishing	YBC251	160-440
		YBC252	180-480
	For roughing	YBC351	130-380
		YBC352	
M Stainless steel	For finishing For semi-finishing For roughing	YBM151 YBM153 YBM251 YBM253	110-280
K Cast iron	For finishing	YBD052	200-500
		YBD102	200-480
	For semi-finishing	YBD151	180-450
		YBD152	190-450
	For roughing	YBD252	150-380

Case



Coated Cemented Carbide PVD

makes it easy to machine materials which are hard to be machined

New nano coating grade

- Special coating techniques make inserts smooth, which leads to low friction and unobstructed chip flow.
- Unique coating with nano structure closely integrates with substrate, ensuring higher hardness and toughness.
- Excellent thermal stability and chemical stability can effectively protect cutting edge.





nc-TiAlN coating(YBG202)



TiAlN base multi-elements coating (YBG105)

High-performance nanostructure coating guarantees good toughness and hardness of inserts. Special coating technology guarantees smooth surface and excellent wear resistance. Outstanding thermal stability and chemical stability effectively protect cutting edge.

YBG102

The combination of nc-TiAlN coating and fine grain substrate makes it suitable for turning of various materials and finishing and semi-finishing of high-temperature alloys.

YBG202

nc-TiAlN coating and ultra-fine grain substrate makes it suitable for finishing and semi-finishing of various materials and turning of super alloy.

YBG302

The combination of nc-TiAlN coating and tough cemented carbide substrate, which integrates security and wear resistance, makes it suitable for parting and grooving of various materials.

YBG105

Finishing and semi-finishing for materials difficult to cut PVD coated grade

PVD coated grade, new TiAlN based multilayer coating, has higher wear resistance and Anti-thermal-oxidation ability. It is suitable for finishing and semi-finishing turning of various materials difficult to cut, such as high temperature alloy, heat resistant alloy, etc.

YBG205

PVD coating grade for finishing of stainless steel

Suitable for relatively small workpieces which require high surface smoothness.

Superfine TiAlN nano coating added with wear-resistant and heat-resistant rare elements has high hardness and excellent heat-resistance, providing effective protection for the cutting edge. Special coating technology ensures stronger combination of coating and substrate. It is suitable for extra finishing of stainless steel.

YBG212

Nc-TiAlN coating combined with super tough substrate which made of super fine grain.It's suitable for finishing and roughing materials which are hard to be machined.

YBS103 New

Turning grade for Ni-based S material

Fine wear resistance, and good capability against built-up edge and heat resistance. Suitable for turning of Ni-based materials.

YBM215 New

PVD coating of multiple layer nanometer

Improved capability of grade's wear resistance and anti-high temperature increases the strength between grade and substrate and the tool stability. This grade is very suitable for turning for stainless steel.

Recommended combination of grade and chipbreaker



Recommended cutting parameters

Workpiece material	Range of machining	Grade	Recommended cutting speed(m/min)
P Steel	For finishing	YBG102	180-460
	For semi-finishing	YBG202 YBG205	150-380
M Stainless steel	For finishing～for semi-finishing	YBG202 YBG205 YBM215	170-300
S Heat resistant Alloy Ti alloy	For finishing～for semi-finishing	YBG102	30-60
		YBG105	40-70
		YBG212	30-50
		YBS103	40-90
	For roughing	YBG102	20-40
		YBG105	30-40
		YBG212	20-40
		YBS103	20-50

Case

Insert : YBG202/TNMG120404-EF
Hardness and material of workpiece : 0Cr18Ni9 HB240
Cutting conditions : Vc=200m/min, a_p=1mm, f=0.15mm/r
Cutting fluid : Dry cutting



Number of machined parts/Cutting edge

Insert : YBG102/DNEG150404-NF
Hardness and material of workpiece :
High temperature alloy Inconel 718 HRC≥39
Cutting conditions : Vc=80m/min, a_p=0.3mm, f=0.15mm/r
Cutting fluid : Dry cutting





Tool life (min)

Cermet & Coated Cermet

The chemical stability between Ti(CN) base cermet inserts and workpieces is relatively high, which reduces the friction and temperature of the cutting edge during cutting, preventing mutual diffusion of atoms of the workpiece material and the inserts, and improving resistance to bonding abrasion. Therefore, Ti(CN) base cermet shows good capability of Red Hardness and resistance to crater wear. It is an optimal material for high-speed finishing and semi-finishing of steel. High temperature strength of cermet is higher than that of WC-Co, and toughness better than that of Al_2O_3 and Si_3N_4 ceramic. This fulfils the application blank of WC-base cemented carbide and Al_2O_3 and Si_3N_4 ceramic from finishing to semi-finishing at high speed.

Product features

Scientifically designed structure ensures good material performance and long tool life. Refined production management assures the stability of product quality.

- Symmetrical fine grain organization, together with the control of symmetrical organization and toric phase structure, improves the strength and hardness of cermet.
- Intensified bonding phase and well-designed grain boundary improve the high temperature capacity, heat conductibility and thermal vibration resistance.
- Coating of Physical Vapor Deposition (PVD) is applied to cermet substrate with high toughness, so that the grade has high hardness and toughness with wide-range application.



Substrate of cermet grade of YNG151 (homogenized ultra-fine structure)

PVD coating organization structure of cermet

Recommended cutting parameters

Workpiece material	Range of machining	Grade	Recommended cutting speed(m/min)
P Steel	For finishing	YNG151	260-550
		YNG151C	260-580
M Stainless steel		YNG151	170-330
		YNG151C	160-350
K Cast iron		YNG151	250-400
		YNG151C	270-420

Case

Insert: YNG151/CNMG120404-SF

Hardness and material of workpiece:

20CrMnTi HB180-223

Cutting parameters: V_C=220m/min

a_p=0.5~1.0mm

f=0.14mm/r



Outstanding chip breaking Good surface quality



Substrate of YD101: the combination of cemented carbide phrase WC of fine grain and bonding phase Co

Cemented Carbide Grade

Uncoated cemented carbide grade is widely used for machining of non-ferrous metal, high temperature alloy, etc. It is economical and can be universally applied.

Substrate of YD201: the combination of cemented carbide phase WC of middle grain and bonding phase Co

Recommended cutting parameters

Workpiece material	Range of machining	Grade	Recommended cutting speed(m/min)
K Cast iron	For semi-finishing For roughing	YD201	60-130
N Non-ferrous metal	For finishing For semi-finishing	YD101	110-1750
S Heat resistant Alloy Ti alloy	For finishing	YD101	20-50

Case

Insert：YD101/CCGX09T304-LH

Workpiece material：ZL105 HB70

Cutting parameters：Vc=400m/min

a_p=1mm

f=0.3mm/r





Workpiece has high surface quality and high dimensional precision.

PCBN



PCBN tool material has high hardness, high thermal stability and high chemical inertness,There will be no chemical reaction with iron materials under the high temperature, the cutting temperature can reach 1200-1300℃ ,Suitable for cutting hardened steel, cast iron, powder metallurgy and high temperature alloys.





High-performance special ceramic coating

Incorporate a solid interface

High wear resistance and good toughness

- High hardness and high heat resistance to achieve tool long life and high-speed processing;
- Effectively inhibit crater wear and realize stable processing;
- Improve the stress of the matrix and reduce the micro chipping and spalling of the cutting edge.

Chamfer width and angle



The shape of chamfering



Cutting edge specifications of PCBN inserts

(The form below is just for typical example, the actual application shall be adjusted according to the corresponding situation.)

High hardness material processing	Low cutting force	Universal type	Highly damage resistance
			
Cast iron processing	Low cutting force	Universal type	High intensity of cutting edge
			

Case

Machining differential gears

Workpiece material: carburizing steel 20CrMnTi, HRC58-62
Insert model: VNGA160404AS01225-2
Grade: BH0121
Cutting parameters: Vc=130m/min; f=0.1mm/r; ap=0.15mm
Processing method: turning the side of the inner groove
Cooling method: dry cutting
Processing requirements: surface finish Ra ＜ 0.8μm



- 21% increase in processing life
- 42% savings in insert cost

Machining cylinder liner

Workpiece material: gray cast iron HT250, HB220
Insert model: CNGA120416AS01015-2
Insert grade: BK1011
Cutting parameters: Vc=600m/min; f=0.2mm/r; ap=0.15mm
Processing method: turning outer circle
Cooling method: wet cutting
Processing requirements: surface finish Ra ＜ 1.6μm and no dimension deviation.



- Machining life increased by 5 times
- Processing efficiency increased by 1 times

Machining of high-temperature alloy bars

Workpiece material: nickel-based alloy Inconel 718, 43-48HRC
Insert model: VBGW160404AT01225-2
Insert grade: BS3011
Cutting parameters: Vc=150m/min; f=0.15mm/r; ap=0.25mm
Processing method: turning outer circle
Cooling method: dry cutting
Processing requirements: flank wear ≤ 0.2mm



- Machining life increased by 6 times
- Processing efficiency increased by 5 times

Coated PCBN insert

By using a combination of strong PCBN substrate and heat-resistant ceramic coating,developed a new super-hard series product——Coated PCBN inserts, dedicated used for cutting all kinds of hardened steel. The tool life of coated PCBN inserts have been greatly improved, being compared with previous uncoated PCBN inserts.

K Cast iron processing category:



Finishing

BK1011 Extremely high wear resistance and edge retention;
Suitable for continuous to intermittent high-speed finishing, and capable of achieving consistent surface quality.

BK1021 Excellent wear resistance and good impact resistance;
Suitable for continuous to intermittent heavy-duty roughing, good versatility.

Typical applications: brake discs, brake drums, cylinder liners, compressor parts.

Semi-finishing / Roughing

BK2511 Great wear resistance and outstanding chemical stability;
Suitable for continuous to interrupted high speed roughing.

BK2541 Very high wear resistance and excellent fracture toughness;
Suitable for continuous to interrupted finishing, good versatility.

Typical application industries: brake discs, brake drums, cylinder liners, compressor parts, rolls, slurry pumps.

S Powder metallurgy and high temperature alloy processing category:

Finishing

BS1011
Excellent wear resistance and chemical stability;
Suitable for machining powder metallurgical parts in continuous to lightly interrupted operation;
Suitable for machining powder metallurgical parts with more than 10% alloying elements.

BS2011
Excellent heat resistance and chemical stability;
Suitable for continuous to lightly interrupted machining of powder metallurgical parts;
Suitable for processing powder metallurgical parts with an alloying element content of up to 10%.

BS3011
Very high hardness and wear resistance.
Suitable for continuous to interrupted machining of powder metallurgy and high temperature alloy parts.
Typical application industries: automotive parts, high temperature resistant parts.



H Hardened steel processing:

Finishing

BH0121
Excellent heat and wear resistance;
Suitable for continuous to lightly interrupted high-speed finishing;
Suitable for machining carburized hardened steel such as 20CrMnTi, 20CrMn, 18Cr2Ni4WA, etc.



BH2511
Excellent heat resistance and impact strength;
Suitable for continuous to moderate intermittent finishing;
Suitable for machining carburized hardened steels such as 20CrMnTi, 20CrMn, 18Cr2Ni4WA, etc.
Typical application industries: Gears, bearings.

BH1020
Effective balance of wear resistance and chemical resistance;
Suitable for continuous to lightly intermittent finishing of all types of hardened steels, with good versatility.

BH2011
Excellent wear resistance and impact strength;
Suitable for continuous to moderate intermittent finishing;
Suitable for machining hardened bearing and die steels such as GCr15, 100Cr6, 18Cr2Ni4WA, etc.

BH3511
Excellent chipping resistance and very high fracture toughness;
Suitable for roughing and finishing all types of hardened steels in moderate to heavy interrupted work conditions.
Typical application industries: gears, bearings, molds.



Recommended cutting data

Grade	Workpiece material	Cutting speed(m/min)	Feed amount(mm/r)	Depth of cut(mm)
BK1011	Gray cast iron	400-1500	0.02-0.5	0.1-0.3
	Hard cast iron	80-160	0.05-0.5	0.05-0.1
BK1021	Gray cast iron	400-1500	0.02-0.5	0.1-0.3
	Hard cast iron	80-160	0.05-0.5	0.05-0.1
BK2511	Gray cast iron	300-600	0.1-0.5	1-3
BK2541	Hard cast iron	50-150	0.1-0.5	1-3
BH0121	Hardened steel	150-250	0.05-0.5	0.05-0.1
BH1020		140-220	0.05-0.5	0.05-0.1
BH2011		100-170	0.05-0.5	0.05-0.1
BH2511		120-180	0.05-0.5	0.05-0.1
BH3511		80-150	0.05-0.4	0.05-0.2
BS1011	Powder metallurgy and high temperature alloys	70-180	0.05-0.25	0.03-0.2
BS2011		100-200	0.05-0.25	0.03-0.2
BS3011		50-160	0.05-0.25	0.03-0.25

PCD tools

PCD tool material has high hardness, excellent wear resistance, low friction coefficient,Excellent thermal conductivity, suitable for non-ferrous metals and its alloys(e.g. Cu, Al, Mg, etc.)Nonmetallic materials and composite materials(such as: MMC, ceramics, reinforced plastics, etc.) machining



N

DN0121
Super-fine grain particle size
great sharpness and edges durability

Application range: suitable for mirror effect occasion

DN0511
Fine grain particle size
Excellent toughness and relatively good wear-resistance

Application range:
strong universality, particular suitable for low-medium silumin materials in milling.

DN1021
medium grain particle size
Excellent toughness and wear-resistance

Application range:
strong universality, particular suitable for low-medium silumin materials in turning.

DN3021
mixed combined with fine particle and coarse particle
Excellent wear-resistance

Application range:
suitable for MMC, high silumin, high-strength silumin and bimetallic materials



Recommended cutting data

Grade	Workpiece materials	Machining method	Cutting speed (m/min)
DN0121	Silumin (Si≤12%)	Turning	500~1000
		Milling	300~1500
	fibre reinforced composite materials	Turning /Milling	200~1000
DN0511	Silumin (Si≤12%)	Turning	900~3500
		Milling	600~2400
	Metal base compound	Turning /Milling	1500~1800
	Coppeer and magnesium alloyssilumin	Turning /Milling	400~1260
	Cemented carbide	Turning	20~40
DN1021	Silumin (Si≤12%)	Turning	400~1200
		Milling	250~1400
	Coppeer and magnesium alloyssilumin	Turning /Milling	400~1260
DN3021	Silumin (Si≤12%)	Turning	300~700
		Milling	500~1000
	Metal base compound	Milling	500~1000
	Unsintered ceramic materials	Turning	100~200
	Sintered Ceramic	Turning	20~50
	Bimetallic materials	Milling	200~300

Ceramic Grade



CN3100

A -siaon/ β -siaon matrix, the latest developmed Siloxane sialon.

Applications: With excellent wear resistance, fracture toughness and thermal shock resistance, for use in general machining to finishing in high temperature alloy parts. It has better resistance of breakage at the depth of cut,compared with SiC/Al2O3 whisker ceramic material.

Physical properties

Grade	Density(g/cm^3)	HardnessHv(GPa)	Flexural strength(MPa)	Fracture toughness (MPa m$^{1/2}$)
CN3100	3.34	1720	⩾900	7.5

Recommended cutting data

Grade	Workpiece material	Operation	Cutting speed (m/min)	Feed rate(mm/r)	Depth of cut (mm)
CN3100	Nickel high temperature alloy	For roughing	150-260	0.1-0.3	<5

Case

Workpiece material：GH4169
Insert specification：RPGN090700T01020-V
Cutting data：Vc=200 m/min，ap=1 mm，
f=0.1（mm/r）

Workpiece shape and process：Figure 1，four working procedures, two blades and four cutting edges in the figure finish the milling of turbine disk section, and the wear resistance is excellent.



Figure 1

Application instruction for general turning toolsırning inserts overview

Table of correctional coefficient between material hardness and cutting speed

Workpiece material		Theoretical Hardness	Correctional coefficient between hardness of materials and cutting speed								
			Hardness decrease ← Hardness difference(Measured value – Theoretical value) → Hardness increase								
			-60	-40	-20	0	+20	+40	+60	+80	+100
P		HB180	1.42	1.24	1.11	1.0	0.91	0.84	0.77	0.72	0.67
M		HB180	1.44	1.25	1.11	1.0	0.91	0.84	0.78	0.73	0.68
K	Grey cast iron	HB220	1.21	1.13	1.06	1.0	0.95	0.90	0.86	0.82	0.79
	Nodular cast iron	HB250	1.33	1.21	1.09	1.0	0.91	0.84	0.75	0.70	0.65
N		HB75			1.05	1.0	0.95				
S		HB350			1.12	1.0	0.89				
Rockwell hardness HRC				-6	-3	0	+3	+6	+9		
H		HRC60		1.10	1.02	1.0	0.96	0.93	0.90		
Actual Cutting Speed = Recommended Cutting Speed×Correctional Coefficient of Cutting Speed											

●Please find recommended cutting parameters on insert packing box.
Example: If the material you are going to machine is normal alloy steel, whose theoretical hardness is HB180, and the selected insert is CNMG120404-DF/YBC151, then the recommended cutting speed is V=150m/min. If the hardness measured value of the material is HB220, then the hardness difference value is 220-180= +40. Correctional coefficient found in the table is 0.84. Therefore, the actual applicable cutting speed is Vc=250×0.84=210m/min.

Correctional coefficient table between tool life and cutting speed

Tool life / Insert materials	Correctional coefficient between tool life and cutting speed					
	10 minutes	15 minutes (Standard life)	30 minutes	45 minutes	60 minutes	90 minutes
YBC151	1.12	1.00	0.82	0.73	0.67	0.60
YBC251	1.11	1.00	0.84	0.76	0.71	0.64
YBC351	1.11	1.00	0.84	0.76	0.70	0.63
YBC152	1.25	1.00	0.68	0.54	0.46	0.37
YBC252	1.55	1.00	0.47	0.30	0.22	0.14
YBM151	1.28	1.00	0.66	0.52	0.43	0.34
YBM153	1.32	1.00	0.64	0.48	0.37	0.31
YBM215	1.22	1.00	0.85	0.77	0.72	0.67
YBM251	1.19	1.00	0.75	0.63	0.56	0.47
YBM253	1.22	1.00	0.73	0.61	0.54	0.45
YBG202	1.10	1.00	0.85	0.77	0.72	0.66
YBG205	1.15	1.00	0.82	0.74	0.69	0.64
YBD052	1.22	1.00	0.80	0.65	0.60	0.55
YBD102	1.20	1.00	0.75	0.62	0.58	0.50
YBD152	1.11	1.00	0.70	0.60	0.50	0.40
YBG105	1.28	1.00	0.79	0.72	0.63	0.58
YBG212	1.25	1.00	0.75	0.70	0.60	0.50
YBS103	1.35	1.00	0.85	0.78	0.68	0.62
Actual cutting speed = Recommended cutting speed × Correctional coefficient of cutting speed						

Example: If the material you are going to machine is normal alloy steel, and the selected insert is CNMG120404-DF/YBC151, then the recommended cutting speed is V=250m/min (standard life is 15 minutes). If you expect the tool life to reach 60 minutes, the correctional coefficient found in the table is 0.67, then the applicable cutting speed is Vc=250×0.67=167.5m/min.

General turning inserts code key

Insert shape

Insert shape/Code		
A	B	C
D	E	H
 K	L	M
O	P	R
S	T	T
V	W	Others Z

Chipbreaker and clamping system

Code	With/Without hole	With/Without chipbreaker	Section plane of insert	Code	With/Without hole	With/Without chipbreaker	Section plane of insert
B	With	Without		N	Without	Without	
H	With	Single-side		R	Without	Single-side	
C	With	Without		F	Without	Double-side	
J	With	Double-side		A	With	Without	
W	With	Without		M	With	Single-side	
T	With	Single-side		G	With	Double-side	
Q	With	Without		X	---	---	Special
U	With	Double-side					

T N M G

Clearance angle of main cutting edge

Code	Clearance angle	Code	Clearance angle
A		B	
C		D	
E		F	
G		N	
P		O	Other clearance angles

Tolerance





Code	Nose height m Tolerance(mm)	Inscribed circle ØI.C Tolerance(mm)	Thickness S Tolerance(mm)
A	±0.005	±0.025	±0.025
F	±0.005	±0.013	±0.025
C	±0.013	±0.025	±0.025
H	±0.013	±0.013	±0.025
E	±0.025	±0.025	±0.025
G	±0.025	±0.025	±0.13
J	±0.005	±0.05-±0.13	±0.025
K	±0.013	±0.05-±0.13	±0.025
L	±0.025	±0.05-±0.13	±0.025
M	±0.08-±0.18	±0.05-±0.13	±0.13
N	±0.08-±0.18	±0.05-±0.13	±0.025
U	±0.13-±0.38	±0.08-±0.25	±0.13

(Reference) Details of M-level tolerance (Identified by shape)

● Nose height tolerance(mm)

Inscribed circle	Regular triangle	Square	Diamond with 80°	Diamond with 55°	Diamond with 35°	Round
6.35	±0.08	±0.08	±0.08	±0.11	±0.16	---
9.525	±0.08	±0.08	±0.08	±0.11	±0.16	---
12.7	±0.13	±0.13	±0.13	±0.15	---	---
15.875	±0.15	±0.15	±0.15	±0.18	---	---
19.05	±0.15	±0.15	±0.15	±0.18	---	---
25.4	---	±0.18	---	---	---	---

● Tolerance of inscribed circle ØI.C(mm)

Inscribed circle	Regular triangle	Square	Diamond with 80°	Diamond with 55°	Diamond with 35°	Round
6.35	±0.05	±0.05	±0.05	±0.05	±0.05	---
9.525	±0.05	±0.05	±0.05	±0.05	±0.05	±0.05
12.7	±0.08	±0.08	±0.08	±0.08	---	±0.08
15.875	±0.10	±0.10	±0.10	±0.10	---	±0.10
19.05	±0.10	±0.10	±0.10	±0.10	---	±0.10
25.4	---	±0.13	---	---	---	±0.13

General turning inserts code key

Diameter of IC	Insert shape							
	C	D	R	S	T	V	W	K
3.97					06			
5.0			05					
5.56					09			
6.0			06					
6.35	06	07			11	11		
8.0			08					
9.525	09	11	09	09	16	16	06	16
10.0			10					
12.0			12					
12.7	12	15	12	12	22	22	08	
15.875	16		15	15	27			
16.0		19	16					
19.05	19		19	19	33			
20.0			20					
25.0	25	25	25					
25.4			25	25				
31.75			31					
32			32					

Length of cutting edge



Thickness is defined as the height from the bottom of insert to the highest part of cutting edge

Code	Insert thickness(mm)
00	0.79
T0	0.99
01	1.59
T1	1.98
02	2.38
T2	2.58
03	3.18
T3	3.97
04	4.76
T4	4.96
05	5.96
T5	5.95
06	6.35
T6	6.75
07	7.94
09	9.52
T9	9.72
11	11.11
12	12.70

Insert thickness

22 04 08 - DM (ISO)

4 3 2 (inch)

Inscribed circle

Code	Diameter of IC(mm)
2	6.35
3	9.525
4	12.7
5	15.875
6	19.05
8	25.4

Thickness

Code	Thickness (mm)
2	3.18
3	4.76
4	6.35
5	7.94
6	9.52

Nose radius

Code	Nose radius (mm)
0	0.2
1	0.4
2	0.8
3	1.2
4	1.6
5	2.0
6	2.4

Nose radius code

Code	Nose radius (mm)
00	No radius
02	0.2
04	0.4
08	0.8
12	1.2
16	1.6
20	2.0
24	2.4
32	3.2
X	Others
Diameter of insert (Metric)	Round insert

Chipbreaker code

DF	DM	DR
HF	HM	HR
EF	EM	ER
NF	NM	SF
PM	WGF	SNR

Metric and inch comparison table of negative inserts

C-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	090304	321	-DF -WGF -SF -EF -NF -WGM -PM -DM -EM -NM -DR -ER -LR -HDR -HPR -SNR
	090308	322	
	120404	431	
	120408	432	
	120412	433	
	120416	434	
	160608	542	
	160612	543	
	160616	544	
	190608	642	
	190612	643	
	190616	644	
	190624	646	
	250724	856	
	250732	858	
	250924	866	
	250932	868	

D-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	110404	331	-EF -DF -WGF -SF -NF -WGM -PM -DM -EM -NM -DR -ER -LR -HDR -SNR -NGF
	110408	332	
	110412	333	
	150404	431	
	150408	432	
	150412	433	
	150604	441	
	150608	442	
	150612	443	
	150616	444	
	190608	542	
	190612	543	

V-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	160404	331	-DF -EF -SF -NF -PM -DM -EM -NM -SNR -NGF
	160408	332	
	160412	333	

R-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	120400	43	

W-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape	06T304	3(2.5)1	-DF -WGF -SF -EF -NF -WGM -PM -DM -EM -NM -DR -SNR
	06T308	3(2.5)2	
	06T312	3(2.5)3	
	060404	331	
	060408	332	
	060412	333	
	080404	431	
	080408	432	
	080412	433	

T-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	110304	221	-DF -WGF -SF -EF -WGM -PM -DM -EM -DR -ER -LR -HDR -SNR
	110308	222	
	160404	331	
	160408	332	
	160412	333	
	220404	431	
	220408	432	
	220412	433	
	220416	434	
	270608	542	
	270612	543	
	270616	544	

S-type negative angle	(ISO)	(Inch)	Chipbreaker
Insert shape	090304	321	-DF -SF -EF -PM -DM -EM -NM -DR -ER -LR -HDR -HPR -SNR
	090308	322	
	090312	323	
	120404	431	
	120408	432	
	120412	433	
	120416	434	
	150608	542	
	150612	543	
	150616	544	
	190412	633	
	190424	636	
	190612	643	
	190616	644	
	250724	856	
	250732	858	
	250924	866	
	250932	868	

Metric and inch comparison table of positive insert

C-type positive angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	060202	2(1.5)0	-USF
	060204	2(1.5)1	-SF
	060208	2(1.5)2	-HF
	09T302	3(2.5)0	-EF
	09T304	3(2.5)1	-HM
	09T308	3(2.5)2	-EM
	120404	431	-HR
	120408	432	-LH
	120412	433	-LC

D-type positive angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	070202	2(1.5)0	-USF
	070204	2(1.5)1	-SF
	070208	2(1.5)2	-HF
	11T302	3(2.5)0	-EF
	11T304	3(2.5)1	-HM
	11T308	3(2.5)2	-EM
	11T312	3(2.5)3	-HR
			-LH
			-LC

T-type positive angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	06T102	1.2(1.2)0	
	06T104	1.2(1.2)1	
	06T108	1.2(1.2)2	
	090202	1.8(1.5)0	
	090204	1.8(1.5)1	
	090208	1.8(1.5)2	
	110202	2(1.5)0	
	110204	2(1.5)1	
	110208	2(1.5)2	-USF
	110302	220	-SF
	110304	221	-HF
	110308	222	-EF
	16T302	3(2.5)0	-HM
	16T304	3(2.5)1	-EM
	16T308	3(2.5)2	-HR
	16T312	3(2.5)3	-LH
	160400	330	-LC
	220408	432	
	220412	433	
	220416	434	
	270408	532	
	270412	533	
	330612	643	
	330616	644	

S-type positive angle	(ISO)	(Inch)	Chipbreaker
Insert shape	060204	2(1.5)1	
	09T302	3(2.5)0	
	09T304	3(2.5)1	
	09T308	3(2.5) 2	-HF
	120404	431	-EF
	120408	432	-HM
	120412	433	-EM
	150404	531	-HR
	150408	532	-LH
	150412	533	-LC
	190408	632	
	190412	633	
	190416	634	

V-type positive angle	(ISO)	(Inch)	Chipbreaker
Insert shape 	110202	2(1.5)0	
	110204	2(1.5)1	
	110208	2(1.5)2	-USF
	110302	220	-SF
	110304	221	-HF
	110308	222	-NF
	160402	330	-LH
	160404	331	-LC
	160408	332	-NGF
	160412	333	

CN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF	CNMG090304-DF	9.7	9.525	3.18	3.81	0.4		○		○					○														○			
	CNMG090308-DF	9.7	9.525	3.18	3.81	0.8		○	○	○																						
	CNMG120404-DF	12.9	12.7	4.76	5.16	0.4		★	●	★					○							○							○			
	CNMG120408-DF	12.9	12.7	4.76	5.16	0.8		★	●	★	○				○							○							●			
For finishing	CNMG120412-DF	12.9	12.7	4.76	5.16	1.2		★	○	○												○										
WGF	CNMG120404-WGF	12.9	12.7	4.76	5.16	0.4		★												★					★							
	CNMG120408-WGF	12.9	12.7	4.76	5.16	0.8		★												★					★							
For finishing Wiper																																
SF	CNMG090304-SF	9.7	9.525	3.18	3.81	0.4							○																○			
	CNMG090308-SF	9.7	9.525	3.18	3.81	0.8							○																○	★		
	CNMG120404-SF	12.9	12.7	4.76	5.16	0.4							○																	★		
	CNMG120408-SF	12.9	12.7	4.76	5.16	0.8							○																	★		
For finishing	CNMG120412-SF	12.9	12.7	4.76	5.16	1.2							○																○			
EF	CNMG090304-EF	9.7	9.525	3.18	3.81	0.4									●	★				★	○											
	CNMG090308-EF	9.7	9.525	3.18	3.81	0.8									○	★				★	○											
	CNMG120404-EF	12.9	12.7	4.76	5.16	0.4									●	★				★	★											
	CNMG120408-EF	12.9	12.7	4.76	5.16	0.8							●		●	★				★	★											
For finishing	CNMG120412-EF	12.9	12.7	4.76	5.16	1.2									○	★				★	★											

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DCLNR/L
Kr:95°
Page A166

PCBNR/L
Kr:75°
A172

PCLNR/L
Kr:95°
A173

PCLNR/L
Kr:95°
A212

CN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
NF	CNEG120404-NF	12.9	12.7	4.76	5.16	0.4							●	★																	○	
	CNEG120408-NF	12.9	12.7	4.76	5.16	0.8							○	★																	○	
	CNEG120412-NF	12.9	12.7	4.76	5.16	1.2							○	★																	○	
For finishing																																
WGM	CNMG120408-WGM	12.9	12.7	4.76	5.16	0.8				★						★											★					
	CNMG120412-WGM	12.9	12.7	4.76	5.16	1.2				★						★											★					
For finishing Wiper																																
PM	CNMG090304-PM	9.7	9.525	3.18	3.81	0.4		★	●	○																						
	CNMG090308-PM	9.7	9.525	3.18	3.81	0.8		○	●	○																	★					
	CNMG120404-PM	12.9	12.7	4.76	5.16	0.4		★	●	★	○															★	★	○				
	CNMG120408-PM	12.9	12.7	4.76	5.16	0.8	●	★	●	★	●															★	★	★				
	CNMG120412-PM	12.9	12.7	4.76	5.16	1.2		○	●	★	●															★	★	★				
	CNMG120416-PM	12.9	12.7	4.76	5.16	1.6		★	●	○	●															★	○					
	CNMG160608-PM	16.1	15.875	6.35	6.35	0.8	●	○	●	○	○															○	○					
	CNMG160612-PM	16.1	15.875	6.35	6.35	1.2	●	○	●	○	●															★	○					
	CNMG160616-PM	16.1	15.875	6.35	6.35	1.6			●	○																○	○					
	CNMG190608-PM	19.3	19.05	6.35	7.94	0.8		★	●	○	○																★					
	CNMG190612-PM	19.3	19.05	6.35	7.94	1.2		★	●	★	●															○	★					
For semi-finishing	CNMG190616-PM	19.3	19.05	6.35	7.94	1.6	●	★	●	○	●															○						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DCLNR/L Kr:95°	PCBNR/L Kr:75°	PCLNR/L Kr:95°	PCLNR/L Kr:95°
Page A166	A172	A173	A212

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DM	CNMG090304-DM	9.7	9.525	3.18	3.81	0.4		○	●	○												●									
	CNMG090308-DM	9.7	9.525	3.18	3.81	0.8			○	○												●									
	CNMG120404-DM	12.9	12.7	4.76	5.16	0.4		★	●	★	○				●			○				●							●			
	CNMG120408-DM	12.9	12.7	4.76	5.16	0.8	●	★	●	★	●				●			●	○			●							●			
	CNMG120412-DM	12.9	12.7	4.76	5.16	1.2		★	●	★	●				○							●										
	CNMG120416-DM	12.9	12.7	4.76	5.16	1.6			●	○	●											○										
	CNMG160608-DM	16.1	15.875	6.35	6.35	0.8		★	●	★	○											●										
	CNMG160612-DM	16.1	15.875	6.35	6.35	1.2		○	●	★	○											○										
	CNMG160616-DM	16.1	15.875	6.35	6.35	1.6		★	●	○	●											○										
	CNMG190608-DM	19.3	19.05	6.35	7.94	0.8		○	●	○												○										
	CNMG190612-DM	19.3	19.05	6.35	7.94	1.2		★	●	★	○											○										
	CNMG190616-DM	19.3	19.05	6.35	7.94	1.6			●	★	○											○										
EM	CNMG120404-EM	12.9	12.7	4.76	5.16	0.4									●	★					★		★									
	CNMG120408-EM	12.9	12.7	4.76	5.16	0.8									●	★					★		★									
	CNMG120412-EM	12.9	12.7	4.76	5.16	1.2									●	★					★		★									
	CNMG160608-EM	16.1	15.875	6.35	6.35	0.8							○		○	★					○		★									
	CNMG160612-EM	16.1	15.875	6.35	6.35	1.2									○	★					○		★									
	CNMG160616-EM	16.1	15.875	6.35	6.35	1.6									○	★					○		★									

DM: For semi-finishing

EM: For semi-finishing

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DCLNR/L Kr:95° — Page A166

PCBNR/L Kr:75° — A172

PCLNR/L Kr:95° — A173

PCLNR/L Kr:95° — A212

CN□□ (Negative inserts)

Good working condition 😊 Normal working condition 😐 Bad working condition



Workpiece material	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
P Steel	😊	😊	😐	😐	☹	☹	😊		😐	😐		☹											😊	😊		
M Stainless steel							😊		😐	😐			😐	😊	😊	😐	😐						😊	😊		
K Cast iron																			😊	😐	☹	☹				☹
N Non-ferrous metal																									😐	☹
S Heat resistant alloy, Ti alloy							😊	😊			😊							😊							😊	

Inserts shape	Type	Dimensions(mm) L	ØI.C	S	ød	r	Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
							YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
NM	CNMG120404-NM	12.9	12.7	4.76	5.16	0.4							○	★										●							○	
	CNMG120408-NM	12.9	12.7	4.76	5.16	0.8							●	★										○							○	
For semi-finishing	CNMG120412-NM	12.9	12.7	4.76	5.16	1.2							○	★										○							○	
LR	CNMM120408-LR	12.9	12.7	4.76	5.16	0.8				★																						
	CNMM120412-LR	12.9	12.7	4.76	5.16	1.2				★																						
Light-load roughing	CNMM120416-LR	12.9	12.7	4.76	5.16	1.6				★																						
	CNMM160608-LR	16.1	15.875	6.35	6.35	0.8				★																						
	CNMM160612-LR	16.1	15.875	6.35	6.35	1.2				★																						
	CNMM160616-LR	16.1	15.875	6.35	6.35	1.6				★																						
	CNMM160624-LR	16.1	15.875	6.35	6.35	2.4				★																						
	CNMM190612-LR	19.3	19.05	6.35	7.94	1.2				★																						
	CNMM190616-LR	19.3	19.05	6.35	7.94	1.6				★																						
	CNMM190624-LR	19.3	19.05	6.35	7.94	2.4				★																						
	CNMM250924-LR	25.79	25.4	9.525	9.12	2.4				★																						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DCLNR/L Kr:95°
Page A166

PCBNR/L Kr:75°
A172

PCLNR/L Kr:95°
A173

PCLNR/L Kr:95°
A212

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																				Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DR For light roughing	CNMG120408-DR	12.9	12.7	4.76	5.16	0.8		★	●	★	●												●			●						
	CNMG120412-DR	12.9	12.7	4.76	5.16	1.2		○	●	★	○												●			●						
	CNMG120416-DR	12.9	12.7	4.76	5.16	1.6		○		○													●			●						
	CNMG160608-DR	16.1	15.875	6.35	6.35	0.8			○	○													○									
	CNMG160612-DR	16.1	15.875	6.35	6.35	1.2			●	★	○												●			○						
	CNMG160616-DR	16.1	15.875	6.35	6.35	1.6			○	★	●																					
	CNMG190608-DR	19.3	15.875	6.35	7.94	0.8			○	○													●			○						
	CNMG190612-DR	19.3	19.05	6.35	7.94	1.2		○	●	★	●												○			○						
	CNMG190616-DR	19.3	19.05	6.35	7.94	1.6		○	●	★	●															○						
	CNMG190624-DR	19.3	19.05	6.35	7.94	2.4		○	●	○	●																					
DR For roughing	CNMM120412-DR	12.9	12.7	4.76	5.16	1.2			●		○																					
	CNMM160612-DR	16.1	15.875	6.35	6.35	1.2			●		○																					
	CNMM160616-DR	16.1	15.875	6.35	6.35	1.6					○																					
	CNMM190612-DR	19.3	19.05	6.35	7.94	1.2			●	○	●																					
	CNMM190616-DR	19.3	19.05	6.35	7.94	1.6			●	★	●																					
	CNMM190624-DR	19.3	19.05	6.35	7.94	2.4		○	○		○																					
	CNMM250924-DR	25.79	25.4	9.525	9.12	2.4			○	★	○																					
ER For roughing	CNMG120408-ER	12.9	12.7	4.76	5.16	0.8													●				★									
	CNMG120412-ER	12.9	12.7	4.76	5.16	1.2													●				★									
	CNMG160612-ER	16.1	15.875	6.35	6.35	1.2													●				★									
	CNMG160616-ER	16.1	15.875	6.35	6.35	1.6																	★									
	CNMG190612-ER	19.3	19.05	6.35	7.94	1.2																	★									
	CNMG190616-ER	19.3	19.05	6.35	7.94	1.6																	★									
ER For roughing	CNMM250724-ER	25.79	25.4	7.94	9.12	2.4				★													★									
	CNMM250732-ER	25.79	25.4	7.94	9.12	3.2				★													★									
	CNMM250924-ER	25.79	25.4	9.525	9.12	2.4				★													★									
	CNMM250932-ER	25.79	25.4	9.525	9.12	3.2				★													★									
SNR For roughing	CNMG120408-SNR	12.9	12.7	4.76	5.16	0.8							○	●			○							●								
	CNMG120412-SNR	12.9	12.7	4.76	5.16	1.2							○	●			○							●								
	CNMG160608-SNR	16.1	15.875	6.35	6.35	0.8							○	●			○							●								
	CNMG190616-SNR	19.3	19.05	6.35	7.94	1.6							○	●			○							●								

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DCLNR/L Kr:95°

Page A166

PCBNR/L Kr:75°

A172

PCLNR/L Kr:95°

A173

PCLNR/L Kr:95°

A212

CN□□ (Negative inserts)

Good working condition 😊 Normal working condition 😐 Bad working condition 😞



Workpiece material		YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
P	Steel	😊	😊	😐	😐	😞	😞	😊		😐	😐		😞											😊	😊		
M	Stainless steel						😊			😐	😐			😐	😊	😊	😐	😐						😊	😊		
K	Cast iron																		😊	😐	😞	😞					😞
N	Non-ferrous metal																									😐	😞
S	Heat resistant alloy, Ti alloy						😊	😊			😊								😊							😊	

Inserts shape	Type	Dimensions(mm) L	ØI.C	S	ød	r	Coated cemented carbide																				Cermet	Coated cermet	Cemented carbide	
							YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HDR For heavy machining	CNMM120408-HDR	12.9	12.7	4.76	5.16	0.8		○	●	○	○	○																			
	CNMM120412-HDR	12.9	12.7	4.76	5.16	1.2			○	○	○	○																			
	CNMM120416-HDR	12.9	12.7	4.76	5.16	1.6			○		○	○																			
	CNMM160612-HDR	16.1	15.875	6.35	6.35	1.2			○		○	○																			
	CNMM160616-HDR	16.1	15.875	6.35	6.35	1.6				○	○	○																			
	CNMM190616-HDR	19.3	19.05	6.35	7.94	1.6			○	○	○	○																			
	CNMM190624-HDR	19.3	19.05	6.35	7.94	2.4		○	○	○	○	○																			
HPR For heavy machining	CNMM190616-HPR	19.5	19.05	6.35	7.94	1.6				★		○																			
	CNMM250924-HPR	25.19	25.4	9.525	9.12	2.4				★		○																			
Without chipbreaker	CNMA120404	12.9	12.7	4.76	5.16	0.4																			★	○	○				
	CNMA120408	12.9	12.7	4.76	5.16	0.8																			★	★	★				
	CNMA120412	12.9	12.7	4.76	5.16	1.2																			★	★	★				
	CNMA120416	12.9	12.7	4.76	5.16	1.6																			★	★	○				
	CNMA160608	16.1	15.875	6.35	6.35	0.8																				○					
	CNMA160612	16.1	15.875	6.35	6.35	1.2																				★					
	CNMA160616	16.1	15.875	6.35	6.35	1.6																			○	★	○				
	CNMA160620	16.1	15.875	6.35	6.35	2.0																					○				
	CNMA160630	16.1	15.875	6.35	6.35	3.0																					○				
	CNMA190612	19.3	19.05	6.35	7.94	1.2																			★	○	★				
	CNMA190616	19.3	19.05	6.35	7.94	1.6																			○	★	★				

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A166

A172

A173

A212

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CN□□ (Negative inserts)



Good working condition　Normal working condition　Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
All round	CNMG120404	12.9	12.7	4.76	5.16	0.4	●		●													●				○						
	CNMG120408	12.9	12.7	4.76	5.16	0.8	●	★	●	★	○											●				★	★	★				
	CNMG120412	12.9	12.7	4.76	5.16	1.2	●	★	●	★															○	○	○					
	CNMG160608	16.1	15.875	6.35	6.35	0.8	●		●													○										
	CNMG160612	16.1	15.875	6.35	6.35	1.2			●		○																					
	CNMG160616	16.1	15.875	6.35	6.35	1.6			○																							
	CNMG190608	19.3	19.05	6.35	7.94	0.8	○		○		○																					
	CNMG190612	19.3	19.05	6.35	7.94	1.2	○		●		○																					
	CNMG190616	19.3	19.05	6.35	7.94	1.6	○		○		○																					
All round	CNMM120404	12.9	12.7	4.76	5.16	0.4	○																									
	CNMM120408	12.9	12.7	4.76	5.16	0.8	○		○																							
	CNMM120412	12.9	12.7	4.76	5.16	1.2	○																									
	CNMM190608	19.3	19.05	6.35	7.94	0.8					○																					
	CNMM190612	19.3	19.05	6.35	7.94	1.2			○		○																					
	CNMM190616	19.3	19.05	6.35	7.94	1.6			○																							
	CNMM190624	19.3	19.05	6.35	7.94	2.4					○																					

★Recommended grade (always stock available)　●Available grade (always stock available)　○Make-to-order

Applicable tool

DCLNR/L Kr:95°

Page A166

PCBNR/L Kr:75°

A172

PCLNR/L Kr:95°

A173

PCLNR/L Kr:95°

A212

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF For finishing	DNMG110404-DF	11.6	9.525	4.76	3.81	0.4		○	●	○																		●			
	DNMG110408-DF	11.6	9.525	4.76	3.81	0.8		○	○	○																					
	DNMG110412-DF	11.6	9.525	4.76	3.81	1.2		○	○																						
	DNMG150404-DF	15.5	12.7	4.76	5.16	0.4		★	●	★																					
	DNMG150408-DF	15.5	12.7	4.76	5.16	0.8		★	●	★																					
	DNMG150412-DF	15.5	12.7	4.76	5.16	1.2		○		○																					
	DNMG150604-DF	15.5	12.7	6.35	5.16	0.4	●	★	●	★												○									
	DNMG150608-DF	15.5	12.7	6.35	5.16	0.8		★	●	○																					
	DNMG150612-DF	15.5	12.7	6.35	5.16	1.2			○																						
WGF For finishing Wiper	DNMX110404-WGF	11.6	9.525	4.76	3.81	0.4		★												★					★						
	DNMX110408-WGF	11.6	9.525	4.76	3.81	0.8		★												★					★						
	DNMX150404-WGF	15.5	12.7	4.76	5.16	0.4		★												★					★						
	DNMX150408-WGF	15.5	12.7	4.761	5.16	0.8		★												★					★						
	DNMX150604-WGF	15.5	12.7	6.35	5.16	0.4		★												★					★						
	DNMX150608-WGF	15.5	12.7	6.35	5.16	0.8		★												★					★						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L Kr:93°	PDJNR/L Kr:93°	PDPNN Kr:62°30'	PDPNR/L Kr:62°30'	PDUNR/L Kr:93°
Page A167	A174	A175	A213	A214

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
SF	DNMG110404-SF	11.6	9.525	4.76	3.81	0.4							○																○	★		
	DNMG150404-SF	15.5	12.7	4.76	5.16	0.4							○																○	★		
	DNMG150408-SF	15.5	12.7	4.76	5.16	0.8							○																○	★		
	DNMG150604-SF	15.5	12.7	6.35	5.16	0.4							○																○	★		
For finishing	DNMG150608-SF	15.5	12.7	6.35	5.16	0.8							○																○	★		
EF	DNMG110404-EF	11.6	9.525	4.76	3.81	0.4									●	★				★	★											
	DNMG110408-EF	11.6	9.525	4.76	3.81	0.8									○	★				★	○											
	DNMG110412-EF	11.6	9.525	4.76	3.81	1.2									○	★				★	○											
	DNMG150404-EF	15.5	12.7	4.76	5.16	0.4									●	★				★	○											
	DNMG150408-EF	15.5	12.7	4.76	5.16	0.8									●	★				★	○											
For finishing	DNMG150412-EF	15.5	12.7	4.76	5.16	1.2									○	★				★	○											
	DNMG150604-EF	15.5	12.7	6.35	5.16	0.4									●	★				★	★											
	DNMG150608-EF	15.5	12.7	6.35	5.16	0.8									●	★				★	★											
	DNMG150612-EF	15.5	12.7	6.35	5.16	1.2									○	★				★	★											
NF	DNEG150404-NF	15.5	12.7	4.76	5.16	0.4							○	★																	○	
	DNEG150408-NF	15.5	12.7	4.76	5.16	0.8							○	★																	○	
	DNEG150604-NF	15.5	12.7	6.35	5.16	0.4							●	★																	○	
For finishing	DNEG150608-NF	15.5	12.7	6.35	5.16	0.8							●	★																	○	
NGF	DNEG150408-NGF	15.5	12.7	4.76	5.16	0.8							○	●			○															
	DNEG150412-NGF	15.5	12.7	4.76	5.16	1.2							○	●			○															
	DNEG150608-NGF	15.5	12.7	6.35	5.16	0.8							○	●			○															
For finishing	DNEG150612-NGF	15.5	12.7	6.35	5.16	1.2							○	●			○															

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L
Kr:93°
Page A167

PDJNR/L
Kr:93°
A174

PDPNN
Kr:62°30'
A175

PDPNR/L
Kr:62°30'
A213

PDUNR/L
Kr:93°
A214

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
WGM	DNMX150408-WGM	15.5	12.7	4.76	5.16	0.8				★						★										★					
	DNMX150412-WGM	15.5	12.7	4.76	5.16	1.2				★						★										★					
	DNMX150608-WGM	15.5	12.7	6.35	5.16	0.8				★						★										★					
For semi-finishing Wiper	DNMX150612-WGM	15.5	12.7	6.35	5.16	1.2				★						★										★					
PM	DNMG110404-PM	11.6	9.525	4.76	3.81	0.4		●	●	○																●					
	DNMG110408-PM	11.6	9.525	4.76	3.81	0.8		●	●	○	○														★	○	○				
	DNMG110412-PM	11.6	9.525	4.76	3.81	1.2			○	○																					
	DNMG150404-PM	15.5	12.7	4.76	5.16	0.4		●	●	○																					
	DNMG150408-PM	15.5	12.7	4.76	5.16	0.8	●	●	●	○	○														★	★	○				
	DNMG150412-PM	15.5	12.7	4.76	5.16	1.2			●	○			○												○	★	○				
For semi-finishing	DNMG150416-PM	15.5	12.7	4.76	5.16	1.6			○	○																					
	DNMG150604-PM	15.5	12.7	6.35	5.16	0.4		●	●	○	○														★	★					
	DNMG150608-PM	15.5	12.7	6.35	5.16	0.8	●	○	●	★	●														★	★	○				
	DNMG150612-PM	15.5	12.7	6.35	5.16	1.2		★	●	★	○														★	○					
	DNMG150616-PM	15.5	12.7	6.35	5.16	1.6			○	○																					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L Kr:93°

Page A167

PDJNR/L Kr:93°

A174

PDPNN Kr:62°30'

A175

PDPNR/L Kr:62°30'

A213

PDUNR/L Kr:93°

A214

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DM For semi-finishing	DNMG110404-DM	11.6	9.525	4.76	3.81	0.4	●	●	○												○										
	DNMG110408-DM	11.6	9.525	4.76	3.81	0.8	★	●	★	○											●										
	DNMG110412-DM	11.6	9.525	4.76	3.81	1.2	○		○																						
	DNMG150404-DM	15.5	12.7	4.76	5.16	0.4	○	●	★																			○			
	DNMG150408-DM	15.5	12.7	4.76	5.16	0.8	★	●	★																			●			
	DNMG150412-DM	15.5	12.7	4.76	5.16	1.2	★	○	★																						
	DNMG150416-DM	15.5	12.7	4.76	5.16	1.6			○																						
	DNMG150604-DM	15.5	12.7	6.35	5.16	0.4	★	●	★	○												●						●			
	DNMG150608-DM	15.5	12.7	6.35	5.16	0.8	★	●	★	●												●									
	DNMG150612-DM	15.5	12.7	6.35	5.16	1.2	●	●	★	○																					
	DNMG150616-DM	15.5	12.7	6.35	5.16	1.6	○	○	○																						
EM For semi-finishing	DNMG110404-EM	11.6	9.525	4.76	3.81	0.4									○	★					○		★								
	DNMG110408-EM	11.6	9.525	4.76	3.81	0.8									○	★					○		★								
	DNMG110412-EM	11.6	9.525	4.76	3.81	1.2									○	★					○		★								
	DNMG150404-EM	15.5	12.7	4.76	5.16	0.4									●	★					★		★								
	DNMG150408-EM	15.5	12.7	4.76	5.16	0.8									●	★					★		★								
	DNMG150412-EM	15.5	12.7	4.76	5.16	1.2									○	★					★		★								
	DNMG150604-EM	15.5	12.7	6.35	5.16	0.4							○		●	★					○		★								
	DNMG150608-EM	15.5	12.7	6.35	5.16	0.8									●	★					○		★								
	DNMG150612-EM	15.5	12.7	6.35	5.16	1.2									○	★					○		★								
NM For semi-finishing	DNMG150412-NM	15.5	12.7	4.76	5.16	1.2							○	★										○						○	
	DNMG150612-NM	15.5	12.7	6.35	5.16	1.2							●	★										○						○	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L
Kr:93°
Page A167

PDJNR/L
Kr:93°
A174

PDPNN
Kr:62°30'
A175

PDPNR/L
Kr:62°30'
A213

PDUNR/L
Kr:93°
A214

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LR	DNMM150608-LR	15.5	12.7	6.35	5.16	0.8				★																					
	DNMM150612-LR	15.5	12.7	6.35	5.16	1.2				★																					
Light-load roughing	DNMM150616-LR	15.5	12.7	6.35	5.16	1.6				★																					
DR	DNMG150408-DR	15.5	12.7	4.76	5.16	0.8				○																					
	DNMG150412-DR	15.5	12.7	4.76	5.16	1.2				○																					
	DNMG150416-DR	15.5	12.7	4.76	5.16	1.6				○	○																				
	DNMG150608-DR	15.5	12.7	6.35	5.16	0.8		★	○	○	○														●	●					
For light roughing	DNMG150612-DR	15.5	12.7	6.35	5.16	1.2		○	●	★	○														○	●					
	DNMG150616-DR	15.5	12.7	6.35	5.16	1.6					○															○					
DR	DNMM150608-DR	15.5	12.7	6.35	5.16	0.8		○	○																						
	DNMM150612-DR	15.5	12.7	6.35	5.16	1.2		○	●																						
For roughing	DNMM150616-DR	15.5	12.7	6.35	5.16	1.6					○																				
ER	DNMG150608-ER	15.5	12.7	6.35	5.16	0.8																	★								
	DNMG150612-ER	15.5	12.7	6.35	5.16	1.2																	★								
For roughing																															
ER	DNMM150608-ER	15.5	12.7	6.35	5.16	0.8																	★								
	DNMM150612-ER	15.5	12.7	6.35	5.16	1.2																	★								
For roughing																															
SNR	DNMG150608-SNR	15.5	12.7	6.35	5.16	0.8							○	●		○								●							
	DNMG150612-SNR	15.5	12.7	6.35	5.16	1.2							○	●		○								●							
For roughing																															

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L Kr:93°

Page A167

PDJNR/L Kr:93°

A174

PDPNN Kr:62°30'

A175

PDPNR/L Kr:62°30'

A213

PDUNR/L Kr:93°

A214

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

DN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HDR For heavy machining	DNMM150608-HDR	15.5	12.7	6.35	5.16	0.8			○		○	○																				
	DNMM150612-HDR	15.5	12.7	6.35	5.16	1.2					○	○																				
	DNMM150616-HDR	15.5	12.7	6.35	5.16	1.6					○	○																				
All round	DNMG150604	15.5	12.7	6.35	5.16	0.4			○																							
	DNMG150608	15.5	12.7	6.35	5.16	0.8			○																							
	DNMG150612	15.5	12.7	6.35	5.16	1.2			○																							
	DNMG150616	15.5	12.7	6.35	5.16	1.6			○																							
	DNMG190608	19.3	15.875	6.35	7.94	0.8			○																							
	DNMG190612	19.3	15.875	6.35	7.94	1.2			○		○																					
Without chipbreaker	DNMA110416	11.6	9.525	4.76	3.81	1.6																					○					
	DNMA110424	11.6	9.525	4.76	3.81	2.4																					○					
	DNMA150404	15.5	12.7	4.76	5.16	0.4																					○					
	DNMA150408	15.5	12.7	4.76	5.16	0.8																			★	★	○					
	DNMA150604	15.5	12.7	6.35	5.16	0.4																			○	○	○					
	DNMA150608	15.5	12.7	6.35	5.16	0.8																			○	★	★					
	DNMA150612	15.5	12.7	6.35	5.16	1.2																			○	○	○					
	DNMA150616	15.5	12.7	6.35	5.16	1.6																				○	○					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DDJNR/L
Kr:93°
Page A167

PDJNR/L
Kr:93°
A174

PDPNN
Kr:62°30'
A175

PDPNR/L
Kr:62°30'
A213

PDUNR/L
Kr:93°
A214

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF	SNMG090304-DF	9.525	9.525	3.18	3.81	0.4		○																							
	SNMG090308-DF	9.525	9.525	3.18	3.81	0.8		○																							
	SNMG120404-DF	12.7	12.7	4.76	5.16	0.4		○																							
	SNMG120408-DF	12.7	12.7	4.76	5.16	0.8		○	●	○																		○			
For finishing	SNMG120412-DF	12.7	12.7	4.76	5.16	1.2		○		○																					
EF	SNMG090304-EF	9.525	9.525	3.18	3.81	0.4									○	★				★	○										
	SNMG090308-EF	9.525	9.525	3.18	3.81	0.8									○	★				★	○										
	SNMG090312-EF	9.525	9.525	3.18	3.81	1.2									○	★				★	○										
	SNMG120404-EF	12.7	12.7	4.76	5.16	0.4									●	★				★	★										
	SNMG120408-EF	12.7	12.7	4.76	5.16	0.8									●	★				★	★										
For finishing	SNMG120412-EF	12.7	12.7	4.76	5.16	1.2									○	★				★	★										
	SNMG150608-EF	15.875	15.875	6.35	6.35	0.8									○	★				★	○										
	SNMG150612-EF	15.875	15.875	6.35	6.35	1.2									○	★				★	○										
SF	SNMG090304-SF	9.525	9.525	3.18	3.81	0.4							○															○	★		
	SNMG090308-SF	9.525	9.525	3.18	3.81	0.8							○															○	★		
	SNMG120404-SF	12.7	12.7	4.76	5.16	0.4							○															○	★		
	SNMG120408-SF	12.7	12.7	4.76	5.16	0.8							○															○	★		
For finishing	SNMG120412-SF	12.7	12.7	4.76	5.16	1.2							○															○			
	SNMG150608-SF	15.875	15.875	6.35	6.35	0.8							○															○			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75°
Page A168

PSBNR/L Kr:75°
A176

PSDNN Kr:45°
A177

PSKNR/L Kr:75°
A178

PSSNR/L Kr:45°
A179

PSKNR/L Kr:75°
A215

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																				Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
PM	SNMG090304-PM	9.525	9.525	3.18	3.81	0.4		○	●	○																					
	SNMG090308-PM	9.525	9.525	3.18	3.81	0.8		○	●	○	○														○						
	SNMG090312-PM	9.525	9.525	3.18	3.81	1.2		○		○																					
	SNMG120404-PM	12.7	12.7	4.76	5.16	0.4		○	●	○	○														○						
	SNMG120408-PM	12.7	12.7	4.76	5.16	0.8		●	●	○	●														★	★	★				
	SNMG120412-PM	12.7	12.7	4.76	5.16	1.2		●	●	○	○														★	★	★				
	SNMG120416-PM	12.7	12.7	4.76	5.16	1.6			●	○	○															○					
	SNMG150608-PM	15.875	15.875	6.35	6.35	0.8				○																					
	SNMG150612-PM	15.875	15.875	6.35	6.35	1.2		●	●	○															○	●					
	SNMG190616-PM	19.05	19.05	6.35	7.94	1.6			●	○																					
DM	SNMG090304-DM	9.525	9.525	3.18	3.81	0.4		○		○																					
	SNMG090308-DM	9.525	9.525	3.18	3.81	0.8		○	●	○	○																				
	SNMG120404-DM	12.7	12.7	4.76	5.16	0.4		★	●	○																					
	SNMG120408-DM	12.7	12.7	4.76	5.16	0.8				○												○							○		
	SNMG120412-DM	12.7	12.7	4.76	5.16	1.2		★	●	★																					
	SNMG120416-DM	12.7	12.7	4.76	5.16	1.6			●	○	○																					
	SNMG150608-DM	15.875	15.875	6.35	6.35	0.8		○	●	○												●									
	SNMG150612-DM	15.875	15.875	6.35	6.35	1.2		●	●	★	●																				
	SNMG150616-DM	15.875	15.875	6.35	6.35	1.6				○																					
	SNMG190612-DM	19.05	19.05	6.35	7.94	1.2		○	●	○	○											○									
	SNMG190616-DM	19.05	19.05	6.35	7.94	1.6				○																					

For semi-finishing

For semi-finishing

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75°	PSBNR/L Kr:75°	PSDNN Kr:45°	PSKNR/L Kr:75°	PSSNR/L Kr:45°	PSKNR/L Kr:75°
Page A168	A176	A177	A178	A179	A215

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EM	SNMG120404-EM	12.7	12.7	4.76	5.16	0.4									●	★					★		★									
	SNMG120408-EM	12.7	12.7	4.76	5.16	0.8									●	★					★		★									
	SNMG120412-EM	12.7	12.7	4.76	5.16	1.2									●	★					★		★									
	SNMG120416-EM	12.7	12.7	4.76	5.16	1.6									○	★					○		★									
For semi-finishing	SNMG150612-EM	15.875	15.875	6.35	6.35	1.2									●	★					○		★									
	SNMG150616-EM	15.875	15.875	6.35	6.35	1.6									○	★					○		★									
NM	SNMG120408-NM	12.7	12.7	4.76	5.16	0.8							●	★										○							○	
	SNMG120412-NM	12.7	12.7	4.76	5.16	1.2							○	★										○							○	
For semi-finishing																																
LR	SNMM120408-LR	12.9	12.7	4.76	5.16	0.8				★																						
	SNMM120412-LR	12.9	12.7	4.76	5.16	1.2				★																						
	SNMM120416-LR	12.9	12.7	4.76	5.16	1.6				★																						
	SNMM150612-LR	15.875	15.875	6.35	6.35	1.2				★																						
	SNMM150616-LR	15.875	15.875	6.35	6.35	1.6				★																						
	SNMM190612-LR	19.3	19.05	6.35	7.94	1.2				★																						
Light-load roughing	SNMM190616-LR	19.3	19.05	6.35	7.94	1.6				★																						
	SNMM190624-LR	19.3	19.05	6.35	7.94	2.4				★																						
	SNMM250924-LR	25.79	25.4	9.525	9.12	2.4				★																						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75° — Page A168

PSBNR/L Kr:75° — A176

PSDNN Kr:45° — A177

PSKNR/L Kr:75° — A178

PSSNR/L Kr:45° — A179

PSKNR/L Kr:75° — A215

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

SN□□ (Negative inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DR For light roughing	SNMG120408-DR	12.7	12.7	4.76	5.16	0.8		○	●	★	○															○	○					
	SNMG120412-DR	12.7	12.7	4.76	5.16	1.2			●	○	●															○						
	SNMG120416-DR	12.7	12.7	4.76	5.16	1.6		○	○	○																						
	SNMG150608-DR	15.875	15.875	6.35	6.35	0.8				○																						
	SNMG150612-DR	15.875	15.875	6.35	6.35	1.2			●	★	●															○	○					
	SNMG150616-DR	15.875	15.875	6.35	6.35	1.6			●	★																○	○					
	SNMG150624-DR	15.875	15.875	6.35	6.35	2.4				○																						
	SNMG190612-DR	19.05	19.05	6.35	7.94	1.2			●	○	○																					
	SNMG190616-DR	19.05	19.05	6.35	7.94	1.6			●	★	●															○	○					
	SNMG190624-DR	19.05	19.05	6.35	7.94	2.4			●	○	○																					
DR For roughing	SNMM120408-DR	12.7	12.7	4.76	5.16	0.8					○																					
	SNMM120412-DR	12.7	12.7	4.76	5.16	1.2					○																					
	SNMM120416-DR	12.7	12.7	4.76	5.16	1.6					○																					
	SNMM150608-DR	15.875	15.875	6.35	6.35	0.8					○																					
	SNMM150612-DR	15.875	15.875	6.35	6.35	1.2					○																					
	SNMM150616-DR	15.875	15.875	6.35	6.35	1.6			●		○																					
	SNMM190608-DR	19.05	19.05	6.35	7.94	0.8					○																					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75° Page A168

PSBNR/L Kr:75° A176

PSDNN Kr:45° A177

PSKNR/L Kr:75° A178

PSSNR/L Kr:45° A179

PSKNR/L Kr:75° A215

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DR	SNMM190612-DR	19.05	19.05	6.35	7.94	1.2			●	○	○																				
	SNMM190616-DR	19.05	19.05	6.35	7.94	1.6		○	●	★	●																				
	SNMM190624-DR	19.05	19.05	6.35	7.94	2.4		★	●	○	●																				
	SNMM250724-DR	25.4	25.4	7.94	9.12	2.4			●		○																				
For roughing	SNMM250924-DR	25.4	25.4	9.525	9.12	2.4			●	★	●																				
ER	SNMG120408-ER	12.7	12.7	4.76	5.16	0.8																	★								
	SNMG120412-ER	12.7	12.7	4.76	5.16	1.2																	★								
	SNMG150608-ER	15.875	15.875	6.35	6.35	0.8																	★								
	SNMG150612-ER	15.875	15.875	6.35	6.35	1.2																	★								
For roughing	SNMG190612-ER	19.05	19.05	6.35	7.94	1.2																	★								
	SNMG190616-ER	19.05	19.05	6.35	7.94	1.6																	★								
ER	SNMM250724-ER	25.4	25.4	7.94	9.12	2.4				●													★								
	SNMM250732-ER	25.4	25.4	7.94	9.12	3.2				●													★								
	SNMM250924-ER	25.4	25.4	9.525	9.12	2.4				●													★								
For roughing	SNMM250932-ER	25.4	25.4	9.525	9.12	3.2				●													★								
SNR	SNMG120408-SNR	12.7	12.7	4.76	5.16	0.8							○	●			○							●							
For roughing																															

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75°

Page A168

PSBNR/L Kr:75°

A176

PSDNN Kr:45°

A177

PSKNR/L Kr:75°

A178

PSSNR/L Kr:45°

A179

PSKNR/L Kr:75°

A215

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HDR For heavy machining	SNMM120408-HDR	12.7	12.7	4.76	5.16	0.8			○		○	○																				
	SNMM120412-HDR	12.7	12.7	4.76	5.16	1.2			○		○	○																				
	SNMM120416-HDR	12.7	12.7	4.76	5.16	1.6					○	○																				
	SNMM150608-HDR	15.875	15.875	6.35	6.35	0.8			○		○	○																				
	SNMM150612-HDR	15.875	15.875	6.35	6.35	1.2			●		○	○																				
	SNMM150616-HDR	15.875	15.875	6.35	6.35	1.6			○		○	○																				
	SNMM150624-HDR	15.875	15.875	6.35	6.35	2.4					○	○																				
	SNMM190608-HDR	19.05	19.05	6.35	7.94	0.8					○	○																				
	SNMM190612-HDR	19.05	19.05	6.35	7.94	1.2			○		○	○																				
	SNMM190616-HDR	19.05	19.05	6.35	7.94	1.6			○	○	○	○																				
	SNMM190624-HDR	19.05	19.05	6.35	7.94	2.4					○	○																				
	SNMM250724-HDR	25.4	25.4	7.94	9.12	2.4				★	●	○																				
	SNMM250924-HDR	25.4	25.4	9.525	9.12	2.4					○	○																				
HPR For heavy machining	SNMM190616-HPR	19.5	19.05	6.35	7.94	1.6				★		○																				
	SNMM250924-HPR	25.4	25.4	9.525	9.12	2.4				★		○																				

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75°
Page A168

PSBNR/L Kr:75°
A176

PSDNN Kr:45°
A177

PSKNR/L Kr:75°
A178

PSSNR/L Kr:45°
A179

PSKNR/L Kr:75°
A215

SN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
All round	SNMG090304	9.525	9.525	3.18	3.81	0.4			○																						
	SNMG090308	9.525	9.525	3.18	3.81	0.8			○		○																				
	SNMG120404	12.7	12.7	4.76	5.16	0.4			●																						
	SNMG120408	12.7	12.7	4.76	5.16	0.8	○		●		○											●					○				
	SNMG120412	12.7	12.7	4.76	5.16	1.2			○	○	●																				
	SNMG120416	12.7	12.7	4.76	5.16	1.6	○		○																						
	SNMG150608	15.875	15.875	6.35	6.35	0.8			○																						
	SNMG150612	15.875	15.875	6.35	6.35	1.2	○		●																						
	SNMG190612	19.05	19.05	6.35	7.94	1.2	○		●		○																				
	SNMG190616	19.05	19.05	6.35	7.94	1.6	○		●																						
	SNMG250724	25.4	25.4	7.94	9.12	2.4	○		○		●																				
	SNMG250924	25.4	25.4	9.525	9.12	2.4			○		●																				
All round	SNMM090304	9.525	9.525	3.18	3.81	0.4																									○
	SNMM090308	9.525	9.525	3.18	3.81	0.8			○																						
	SNMM120408	12.7	12.7	4.76	5.16	0.8	○																								
	SNMM120412	12.7	12.7	4.76	5.16	1.2			○																						
	SNMM120416	12.7	12.7	4.76	5.16	1.6			○																						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DSBNR/L Kr:75°

Page A168

PSBNR/L Kr:75°

A176

PSDNN Kr:45°

A177

PSKNR/L Kr:75°

A178

PSSNR/L Kr:45°

A179

PSKNR/L Kr:75°

A215

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

SN□□ (Negative inserts)



Good working condition　Normal working condition　Bad working condition

Workpiece material																											
P	Steel	😊	😊	😐	😐	☹	☹	😊		😐	😐		☹												😊	😊	
M	Stainless steel							😊		😐	😐			😐	😊	😊	😐	😐							😊	😊	
K	Cast iron																		😊	😐	☹	☹					☹
N	Non-ferrous metal																									😐	☹
S	Heat resistant alloy, Ti alloy							😊	😊			😊						😊								😊	

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
All round	SNMM190608	19.05	19.05	6.35	7.94	0.8			○																						
	SNMM190612	19.05	19.05	6.35	7.94	1.2			○																						
	SNMM190616	19.05	19.05	6.35	7.94	1.6			○																						
	SNMM250724	25.4	25.4	7.94	9.12	2.4			●		●																				
	SNMM250924	25.4	25.4	9.525	9.12	2.4					○																				
Without chipbreaker	SNMA090304	9.525	9.525	3.18	3.81	0.4																					○				
	SNMA090308	9.525	9.525	3.18	3.81	0.8																			○	○					
	SNMA120404	12.7	12.7	4.76	5.16	0.4																			○						
	SNMA120408	12.7	12.7	4.76	5.16	0.8																			○	★	★				●
	SNMA120416	12.7	12.7	4.76	5.16	1.6																			○	○	★				
	SNMA150608	15.875	15.875	6.35	6.35	0.8																					○				
	SNMA150612	15.875	15.875	6.35	6.35	1.2																					★				
	SNMA190612	19.05	19.05	6.35	7.94	1.2																			○	○	★				
	SNMA190616	19.05	19.05	6.35	7.94	1.6																				★	★				

★Recommended grade (always stock available)　●Available grade (always stock available)　○Make-to-order

Applicable tool

DSBNR/L Kr:75°

Page A168

PSBNR/L Kr:75°

A176

PSDNN Kr:45°

A177

PSKNR/L Kr:75°

A178

PSSNR/L Kr:45°

A179

PSKNR/L Kr:75°

A215

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF	TNMG160404-DF	16.5	9.525	4.76	3.81	0.4		★	●	★												○						●			
	TNMG160408-DF	16.5	9.525	4.76	3.81	0.8		★	○	★																		●			
	TNMG160412-DF	16.5	9.525	4.76	3.81	1.2		○	○	○																					
	TNMG220408-DF	22	12.7	4.76	5.16	0.8		★	○	○																					
For finishing	TNMG220412-DF	22	12.7	4.76	5.16	1.2		○																							
WGF	TNMX160404-WGF	16.5	9.525	4.76	3.81	0.4		★												★					★						
	TNMX160408-WGF	16.5	9.525	4.76	3.81	0.8		★												★					★						
For finishing Wiper																															
SF	TNMG110304-SF	11	6.35	3.18	2.26	0.4							○																○	★		
	TNMG160404-SF	16.5	9.525	4.76	3.81	0.4							○																○	★		
	TNMG160408-SF	16.5	9.525	4.76	3.81	0.8							○																○	★		
	TNMG220408-SF	22	12.7	4.76	5.16	0.8							○																○	★		
For finishing	TNMG220412-SF	22	12.7	4.76	5.16	1.2							○																○	★		

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DTGNR/L Kr:91°
Page A169

PTFNR/L Kr:90°
A180

PTTNR/L Kr:60°
A181

PTGNR/L Kr:90°
A182

PTFNR/L Kr:90°
A216

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EF	TNMG110304-EF	11	6.35	3.18	2.26	0.4									○	★				★	○											
	TNMG110308-EF	11	6.35	3.18	2.26	0.8									○	★				★	○											
	TNMG160404-EF	16.5	9.525	4.76	3.81	0.4									●	★				★	★											
	TNMG160408-EF	16.5	9.525	4.76	3.81	0.8									●	★				★	★											
	TNMG160412-EF	16.5	9.525	4.76	3.81	1.2									○	★				★	★											
For finishing	TNMG220404-EF	22	12.7	4.76	5.16	0.4									○	★				★	○											
	TNMG220408-EF	22	12.7	4.76	5.16	0.8									○	★				★	○											
	TNMG220412-EF	22	12.7	4.76	5.16	1.2									○	★				★	○											
WGM	TNMX160408-WGM	16.5	9.525	4.76	3.81	0.8				★						★											★					
	TNMX160412-WGM	16.5	9.525	4.76	3.81	1.2				★						★											★					
For semi-finishing Wiper																																
PM	TNMG110304-PM	11	6.35	3.18	2.26	0.4		★	●	○																						
	TNMG110308-PM	11	6.35	3.18	2.26	0.8		★	○	○																						
	TNMG160404-PM	16.5	9.525	4.76	3.81	0.4		★	●	★																★	★					
	TNMG160408-PM	16.5	9.525	4.76	3.81	0.8		★	●	★	●		○													★	★	★				
	TNMG160412-PM	16.5	9.525	4.76	3.81	1.2		★	●	○	○															★	★	○				
For semi-finishing	TNMG220408-PM	22	12.7	4.76	5.16	0.8		★	●	○	●															★	○	○				
	TNMG220412-PM	22	12.7	4.76	5.16	1.2	●	★	●	○	○															○	○					
	TNMG220416-PM	22	12.7	4.76	5.16	1.6			○	○																	○					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DTGNR/L
Kr:91°
Page A169

PTFNR/L
Kr:90°
A180

PTTNR/L
Kr:60°
A181

PTGNR/L
Kr:90°
A182

PTFNR/L
Kr:90°
A216

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DM	TNMG110308-DM	11	6.35	3.18	2.26	0.8		○		○																						
	TNMG160404-DM	16.5	9.525	4.76	3.81	0.4		★	●	★	○				○														●			
	TNMG160408-DM	16.5	9.525	4.76	3.81	0.8		★	●	★	●				●							●							○			
	TNMG160412-DM	16.5	9.525	4.76	3.81	1.2		○	○	★	○																					
	TNMG220404-DM	22	12.7	4.76	5.16	0.4		★	●	★	○											○										
	TNMG220408-DM	22	12.7	4.76	5.16	0.8		★	●	★	●											○							○			
	TNMG220412-DM	22	12.7	4.76	5.16	1.2		○	○	○	○																					
	TNMG220416-DM	22	12.7	4.76	5.16	1.6		○	○	○																						
EM	TNMG160404-EM	16.5	9.525	4.76	3.81	0.4									●	★					★		★									
	TNMG160408-EM	16.5	9.525	4.76	3.81	0.8									●	★					★		★									
	TNMG160412-EM	16.5	9.525	4.76	3.81	1.2									○	★					★		★									
	TNMG220408-EM	22	12.7	4.76	5.16	0.8									●	★					○		★									
	TNMG220412-EM	22	12.7	4.76	5.16	1.2									○	★					○		★									
	TNMG220416-EM	22	12.7	4.76	5.16	1.6									○	★					○		★									
LR	TNMM160408-LR	16.5	9.525	4.76	3.81	0.8				★																						
	TNMM160412-LR	16.5	9.525	4.76	3.81	1.2				★																						
	TNMM220408-LR	22	12.7	4.76	5.16	0.8				★																						
	TNMM220412-LR	22	12.7	4.76	5.16	1.2				★																						
	TNMM220416-LR	22	12.7	4.76	5.16	1.6				★																						

For semi-finishing

For semi-finishing

Light-load roughing

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DTGNR/L Kr:91°

Page A169

PTFNR/L Kr:90°

A180

PTTNR/L Kr:60°

A181

PTGNR/L Kr:90°

A182

PTFNR/L Kr:90°

A216

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DR	TNMG160408-DR	16.5	9.525	4.76	3.81	0.8		○		○	○															○	○					
	TNMG160412-DR	16.5	9.525	4.76	3.81	1.2		○	○	○	○															●	●					
	TNMG220408-DR	22	12.7	4.76	5.16	0.8				○	●															○						
	TNMG220412-DR	22	12.7	4.76	5.16	1.2			○	○	○																○					
	TNMG220416-DR	22	12.7	4.76	5.16	1.6					○															○						
	TNMG270608-DR	27.5	15.875	6.35	6.35	0.8					○																					
	TNMG270612-DR	27.5	15.875	6.35	6.35	1.2					○																					
	TNMG270616-DR	27.5	15.875	6.35	6.35	1.6					○																					
DR	TNMM160408-DR	16.5	9.525	4.76	3.81	0.8			○		○																					
	TNMM160412-DR	16.5	9.525	4.76	3.81	1.2			○		○																					
	TNMM220408-DR	22	12.7	4.76	5.16	0.8			●		●																					
	TNMM220412-DR	22	12.7	4.76	5.16	1.2			●		○																					
	TNMM220416-DR	22	12.7	4.76	5.16	1.6			○		○																					
	TNMM270612-DR	27.5	15.875	6.35	5.16	1.2					○																					
	TNMM270616-DR	27.5	15.875	6.35	5.16	1.6					○																					
ER	TNMG160408-ER	16.5	9.525	4.76	3.81	0.8																	★									
	TNMG160412-ER	16.5	9.525	4.76	3.81	1.2																	★									
	TNMG220408-ER	22	12.7	4.76	5.16	0.8																	★									
	TNMG220412-ER	22	12.7	4.76	5.16	1.2																	★									
SNR	TNMG160408-SNR	16.5	9.525	4.76	3.81	0.8							○	●			○							●								

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

For light roughing

For roughing

For roughing

For roughing

Applicable tool

DTGNR/L Kr:91°	PTFNR/L Kr:90°	PTTNR/L Kr:60°	PTGNR/L Kr:90°	PTFNR/L Kr:90°
Page A169	A180	A181	A182	A216

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material		
P	Steel	😊😊😐😐☹☹😊😐😐☹😊😊
M	Stainless steel	😊😐😐😐😊😊😐😐😊😊
K	Cast iron	😊😐☹☹☹
N	Non-ferrous metal	😐☹
S	Heat resistant alloy, Ti alloy	😊😊😊😊

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HDR For heavy machining	TNMM160408-HDR	16.5	9.525	4.76	3.81	0.8					○	○																			
	TNMM160412-HDR	16.5	9.525	4.76	3.81	1.2					○	○																			
	TNMM220408-HDR	22	12.7	4.76	5.16	0.8					○	○																			
	TNMM220412-HDR	22	12.7	4.76	5.16	1.2					○	○																			
	TNMM220416-HDR	22	12.7	4.76	5.16	1.6					○	○																			
	TNMM270612-HDR	27.5	15.875	6.35	6.35	1.2					○	○																			
	TNMM270616-HDR	27.5	15.875	6.35	6.35	1.6					○	○																			
	TNMM270624-HDR	27.5	15.875	6.35	6.35	2.4					○	○																			
All round	TNMG110308	11	6.35	3.18	2.26	0.8			○																						
	TNMG160404	16.5	9.525	4.76	3.81	0.4	○		●																						
	TNMG160408	16.5	9.525	4.76	3.81	0.8	●	○	●																						
	TNMG160412	16.5	9.525	4.76	3.81	1.2	●		●	○												○									
	TNMG220404	22	12.7	4.76	5.16	0.4	○		●		○																				
	TNMG220408	22	12.7	4.76	5.16	0.8	○		●		○											○									
	TNMG220412	22	12.7	4.76	5.16	1.2	●		●		○																				
	TNMG220416	22	12.7	4.76	5.16	1.6			○																						
	TNMG270612	27.5	15.875	6.35	6.35	1.2			●		●																				
	TNMG270616	27.5	15.875	6.35	6.35	1.6			○		○																				
	TNMG330916	33	19.05	9.525	7.94	1.6					●																				
	TNMG330924	33	19.05	9.525	7.94	2.4	○		○		●																				

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DTGNR/L Kr:91°
Page A169

PTFNR/L Kr:90°
A180

PTTNR/L Kr:60°
A181

PTGNR/L Kr:90°
A182

PTFNR/L Kr:90°
A216

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
All round	**TNMM160404**	16.5	9.525	4.76	3.81	0.4			○																						
	TNMM160408	16.5	9.525	4.76	3.81	0.8					○																					
	TNMM160412	16.5	9.525	4.76	3.81	1.2	○		○																							
	TNMM220408	22	12.7	4.76	5.16	0.8			○																							
	TNMM220412	22	12.7	4.76	5.16	1.2			●		○											○										
	TNMM220416	22	12.7	4.76	5.16	1.6					○																					
	TNMM270616	27.5	15.875	6.35	6.35	1.6			●		○																					
Without chipbreaker	**TNMA160404**	16.5	9.525	4.76	3.81	0.4																			○	★	★					
	TNMA160408	16.5	9.525	4.76	3.81	0.8	○																		★	★	★					○
	TNMA160412	16.5	9.525	4.76	3.81	1.2																			★	○	○					
	TNMA160416	16.5	9.525	4.76	3.81	1.6																			○	○	○					
	TNMA220404	22	12.7	4.76	5.16	0.4																			○	○	○					
	TNMA220408	22	12.7	4.76	5.16	0.8																			○	○	○					
	TNMA270616	27.5	15.875	6.35	6.35	1.6																					○					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DTGNR/L Kr:91°

Page A169

PTFNR/L Kr:90°

A180

PTTNR/L Kr:60°

A181

PTGNR/L Kr:90°

A182

PTFNR/L Kr:90°

A216

VN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF	VNMG160404-DF	16.6	9.525	4.76	3.81	0.4		★	●	★												●									
	VNMG160408-DF	16.6	9.525	4.76	3.81	0.8		★	○	○																					
For finishing																															
EF	VNMG160404-EF	16.6	9.525	4.76	3.81	0.4									○	★				★	★										
	VNMG160408-EF	16.6	9.525	4.76	3.81	0.8									○	★				★	★										
	VNMG160412-EF	16.6	9.525	4.76	3.81	1.2									○	★				★	○										
For finishing																															
NF	VNEG160404-NF	16.6	9.525	4.76	3.81	0.4							○	★																○	
	VNEG160408-NF	16.6	9.525	4.76	3.81	0.8							○	★																○	
For finishing																															
NGF	VNEG160408-NGF	16.6	9.525	4.76	3.81	0.8							○	●			○														
	VNEG160412-NGF	16.6	9.525	4.76	3.81	1.2							○	●			○														
For finishing																															
SF	VNMG160404-SF	16.6	9.525	4.76	3.81	0.4							○																○	★	
	VNMG160408-SF	16.6	9.525	4.76	3.81	0.8							○																○		
For finishing																															

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DVVNN
Kr:72°30'

Page A170

DVJNR/L
Kr:93°

A170

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

VN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																				Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
PM	VNMG160404-PM	16.6	9.525	4.76	3.81	0.4		★	●	○	○																○	○				
	VNMG160408-PM	16.6	9.525	4.76	3.81	0.8		★	●	○																★	★	○				
For semi-finishing	VNMG160412-PM	16.6	9.525	4.76	3.81	1.2			○	○																○	○					
DM	VNMG160408-DM	16.6	9.525	4.76	3.81	0.8		★	●	★	○											○										
	VNMG160412-DM	16.6	9.525	4.76	3.81	1.2		○	○	○												○										
For semi-finishing																																
EM	VNMG160404-EM	16.6	9.525	4.76	3.81	0.4									●	★					★		★									
	VNMG160408-EM	16.6	9.525	4.76	3.81	0.8									●	★					★		★									
For semi-finishing																																
NM	VNMG160412-NM	16.6	9.525	4.76	3.81	1.2							○	★										○							○	
For semi-finishing																																
SNR	VNMG160408-SNR	16.6	9.525	4.76	3.81	0.8							○	●			○							●								
	VNMG160412-SNR	16.6	9.525	4.76	3.81	1.2							○	●			○							●								
For roughing																																
All round	VNMG160404	16.6	9.525	4.76	3.81	0.4	○		○																							
	VNMG160408	16.6	9.525	4.76	3.81	0.8	●		●																							

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DVVNN
Kr:72°30'

Page A170

DVJNR/L
Kr:93°

A170

WN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
DF For finishing	WNMG06T304-DF	6.5	9.525	3.97	3.81	0.4		★																							
	WNMG06T308-DF	6.5	9.525	3.97	3.81	0.8		★		★																					
	WNMG06T312-DF	6.5	9.525	3.97	3.81	1.2		★		★																					
	WNMG060404-DF	6.5	9.525	4.76	3.81	0.4		★	●	★												○									
	WNMG060408-DF	6.5	9.525	4.76	3.81	0.8		★	●	★												●									
	WNMG060412-DF	6.5	9.525	4.76	3.81	1.2		★	●	○												○									
	WNMG080404-DF	8.7	12.7	4.76	5.16	0.4		★	●	○												○									
	WNMG080408-DF	8.7	12.7	4.76	5.16	0.8		★	●	★												●									
	WNMG080412-DF	8.7	12.7	4.76	5.16	1.2		○	○	○																					
WGF For finishing Wiper	WNMG060404-WGF	6.5	9.525	4.76	3.81	0.4		★												★				★							
	WNMG060408-WGF	6.5	9.525	4.76	3.81	0.8		★												★				★							
	WNMG080404-WGF	8.7	12.7	4.76	5.16	0.4		★												★				★							
	WNMG080408-WGF	8.7	12.7	4.76	5.16	0.8		★												★				★							
SF For finishing	WNMG06T304-SF	6.5	9.525	3.97	3.81	0.4							○															○	★		
	WNMG06T308-SF	6.5	9.525	3.97	3.81	0.8							○															○			
	WNMG06T312-SF	6.5	9.525	3.97	3.81	1.2							○															○			
	WNMG060404-SF	6.5	9.525	4.76	3.81	0.4							○															○	★		
	WNMG060408-SF	6.5	9.525	4.76	3.81	0.8							○															○	★		
	WNMG080404-SF	8.7	12.7	4.76	5.16	0.4							○															○	★		
	WNMG080408-SF	8.7	12.7	4.76	5.16	0.8							○															○	★		
	WNMG080412-SF	8.7	12.7	4.76	5.16	1.2							○															○			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DWLNR/L Kr:95°

Page A171

PWLNR/L Kr:95°

A183

PWLNR/L Kr:95°

A217

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

WN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EF	WNMG06T304-EF	6.5	9.525	3.97	3.81	0.4									○	★				★	○											
	WNMG06T308-EF	6.5	9.525	3.97	3.81	0.8									○	★				★	○											
	WNMG06T312-EF	6.5	9.525	3.97	3.81	1.2									○	★				★	○											
	WNMG060404-EF	6.5	9.525	4.76	3.81	0.4									●	★				★	○											
For finishing	WNMG060408-EF	6.5	9.525	4.76	3.81	0.8									●	★				★	○											
	WNMG080404-EF	8.7	12.7	4.76	5.16	0.4							○		●	★				★	★											
	WNMG080408-EF	8.7	12.7	4.76	5.16	0.8							○		●	★				★	★											
NF	WNEG080404-NF	8.7	12.7	4.76	5.16	0.4							○	★																○		
	WNEG080408-NF	8.7	12.7	4.76	5.16	0.8							○	★																○		
For finishing																																
WGM	WNMG060408-WGM	6.5	9.525	4.76	3.81	0.8				★						★										★						
	WNMG060412-WGM	6.5	9.525	4.76	3.81	1.2				★						★										★						
For semi-finishing Wiper	WNMG080408-WGM	8.7	12.7	4.76	5.16	0.8				★						★										★						
	WNMG080412-WGM	8.7	12.7	4.76	5.16	1.2				★						★										★						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DWLNR/L Kr:95°

Page A171

PWLNR/L Kr:95°

A183

PWLNR/L Kr:95°

A217

WN□□ (Negative inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
PM	WNMG060408-PM	6.5	9.525	4.76	3.81	0.8		★	●	○	○															★	★					
	WNMG060412-PM	6.5	9.525	4.76	3.81	1.2		○		○																★	★					
	WNMG080404-PM	8.7	12.7	4.76	5.16	0.4		○	●	○	○																					
	WNMG080408-PM	8.7	12.7	4.76	5.16	0.8		★	●	★	●															★	★	★				
	WNMG080412-PM	8.7	12.7	4.76	5.16	1.2		★	●	★	●															★	★	★				
	WNMG080416-PM	8.7	12.7	4.76	5.16	1.6				○																○	○					
	WNMG080608-PM	8.7	12.7	6.35	5.16	0.8				○																						
DM	WNMG06T304-DM	6.5	9.525	3.97	3.81	0.4				○																						
	WNMG06T308-DM	6.5	9.525	3.97	3.81	0.8			○	○																						
	WNMG06T312-DM	6.5	9.525	3.97	3.81	1.2				○																						
	WNMG060408-DM	6.5	9.525	4.76	3.81	0.8		★	●	★	●											●										
	WNMG060412-DM	6.5	9.525	4.76	3.81	1.2			○	○																						
	WNMG080404-DM	8.7	12.7	4.76	5.16	0.4		★	●	★	○				○							○										
	WNMG080408-DM	8.7	12.7	4.76	5.16	0.8		★	●	★	●											○										
	WNMG080412-DM	8.7	12.7	4.76	5.16	1.2		★	●	★												○										
	WNMG080416-DM	8.7	12.7	4.76	5.16	1.6				○																						
EM	WNMG06T304-EM	6.5	9.525	3.97	3.81	0.4									○	★					○		★									
	WNMG06T308-EM	6.5	9.525	3.97	3.81	0.8									○	★					○		★									
	WNMG06T312-EM	6.5	9.525	3.97	3.81	1.2									○	★					○		★									
	WNMG060404-EM	6.5	9.525	4.76	3.81	0.4									○	★					○		★									
	WNMG060408-EM	6.5	9.525	4.76	3.81	0.8									●	★					○		★									
	WNMG080404-EM	8.7	12.7	4.76	5.16	0.4									●	★					★		★									
	WNMG080408-EM	8.7	12.7	4.76	5.16	0.8									●	★					★		★									
	WNMG080412-EM	8.7	12.7	4.76	5.16	1.2									●	★					★		★									

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

DWLNR/L Kr:95°

Page A171

PWLNR/L Kr:95°

A183

PWLNR/L Kr:95°

A217

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

WN□□ (Negative inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
NM	WNMG080408-NM	8.7	12.7	4.76	5.16	0.8							○	★										○							○	
	WNMG080412-NM	8.7	12.7	4.76	5.16	1.2							○	★										○							○	
For semi-finishing																																
DR	WNMG060408-DR	6.5	9.525	4.76	3.81	0.8		○	○	○															○							
	WNMG060412-DR	6.5	9.525	4.76	3.81	1.2			○	○	○														○	○						
For roughing	WNMG080408-DR	8.7	12.7	4.76	5.16	0.8		○	○	★	○														●	●						
	WNMG080412-DR	8.7	12.7	4.76	5.16	1.2		○	○	★	○														●	●						
	WNMG080416-DR	8.7	12.7	4.76	5.16	1.6				○															○	○						
SNR	WNMG080408-SNR	8.7	12.7	4.76	5.16	0.8							○	●			○							●								
	WNMG080412-SNR	8.7	12.7	4.76	5.16	1.2							○	●			○							●								
For roughing																																
Without chipbreaker	WNMA06T308	6.5	9.525	3.97	3.81	0.8																		○								
	WNMA060404	6.5	9.525	4.76	3.81	0.4																					○					
	WNMA060408	6.5	9.525	4.76	3.81	0.8																		★	○		○					
	WNMA060412	6.5	9.525	4.76	3.81	1.2																					○					
	WNMA080404	8.7	12.7	4.76	5.16	0.4																				○						
	WNMA080408	8.7	12.7	4.76	5.16	0.8																		★	★		★					
	WNMA080412	8.7	12.7	4.76	5.16	1.2																		★	★		★					
	WNMA080416	8.7	12.7	4.76	5.16	1.6																					★					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A171

A183

A217

KN□□ (Negative inserts)

Good working condition Normal working condition Bad working condition



R-type shown

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)						Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		La	L	l.W	S	brn	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
Profile turning	KNUX160405L11	16	16.15	9.525	4.76	2.2	0.5	○		●	★	○											●										
	KNUX160410L11	16	16.15	9.525	4.76	2.2	1.0			●													○										
	KNUX160405L12	16	16.15	9.525	4.76	2.2	0.5	○		●													○										
	KNUX160410L12	16	16.15	9.525	4.76	2.2	1.0	○	○	●													○										
	KNUX160415L12	16	16.15	9.525	4.76	2.2	1.5			○																							
	KNUX160405R11	16	16.15	9.525	4.76	2.2	0.5	●		●	○	●											●										
	KNUX160410R11	16	16.15	9.525	4.76	2.2	1.0	○		●													○										
	KNUX160405R12	16	16.15	9.525	4.76	2.2	0.5	●		●													○										
	KNUX160410R12	16	16.15	9.525	4.76	2.2	1.0	○	○	●		○											○										
	KNUX160415R12	16	16.15	9.525	4.76	2.2	1.5			○																							

Note: KNUX160405L11
Chipbreaker code: 11→Declining chipbreaker 12→Straight chipbreaker

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order



Applicable tool

CKJNR/L Kr:93°

Page A204

CKNNR/L Kr:63°

A204

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

Heavy turning(Negative inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	l.W	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
Inserts for train wheel hub	**175.32-191940-22**	19.05	10	19.05	6.35	4.0	●		●																						
	175.32-191940-27	19.05	10	19.05	7.2	4.0			●																						
Inserts for train wheel hub	**175.32-191940-24**	19.05	10	19.05	6.35	4.0	○		●																						
	175.32-301940-24	30	10	19.05	6.35	4.0	○		●																						
Inserts for train wheel hub	**175.32-191940-25**	19.05	10	19.05	6.35	4.0			●																						
Inserts for train wheel hub	**175.32-191940-28**	19.05	10	19.05	6.35	4.0	●	★	●	○																					

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

CC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF For extra finishing	CCGT09T301R-USF	9.7	9.525	3.97	4.4	0.1									○	○																
	CCGT09T302R-USF	9.7	9.525	3.97	4.4	0.2									●	○																
	CCGT09T304R-USF	9.7	9.525	3.97	4.4	0.4									○	○																
USF For extra finishing	CCGT09T301L-USF	9.7	9.525	3.97	4.4	0.1									○	○																
	CCGT09T302L-USF	9.7	9.525	3.97	4.4	0.2									●	○																
	CCGT09T304L-USF	9.7	9.525	3.97	4.4	0.4									○	○																
SF For extra finishing	CCGT060202-SF	6.4	6.35	2.38	2.8	0.2							○																○	○		
	CCGT060204-SF	6.4	6.35	2.38	2.8	0.4							○																○	○		
	CCGT09T304-SF	9.7	9.525	3.97	4.4	0.4							○																○	★		
HF For finishing	CCMT060202-HF	6.4	6.35	2.38	2.8	0.2		★	●	★					●														○			○
	CCMT060204-HF	6.4	6.35	2.38	2.8	0.4		★	●	○	○				●													●	●		●	
	CCMT060208-HF	6.4	6.35	2.38	2.8	0.8		★	●		○				●							○						●				
	CCMT09T302-HF	9.7	9.525	3.97	4.4	0.2			●	○					●													●				○
	CCMT09T304-HF	9.7	9.525	3.97	4.4	0.4		★	●	★	○				●											●	●	●	○			○
	CCMT09T308-HF	9.7	9.525	3.97	4.4	0.8		★	●	○	○				●							○			○	○	○	●		○	○
	CCMT120404-HF	12.9	12.7	4.76	5.56	0.4	●	○	●	○																	●	○				
	CCMT120408-HF	12.9	12.7	4.76	5.56	0.8		○																								

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SCACR/L Kr:90°	SCLCR/L Kr:95°	SCLCR/L Kr:95°	SCFCR/L Kr:90°	SCLCR/L Kr:95°
Page A184	A185	A218	A232	A233

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EF	CCMT060202-EF	6.4	6.35	2.38	2.8	0.2							○		●	★				★	○											
	CCMT060204-EF	6.4	6.35	2.38	2.8	0.4							○		●	★				★	○											
	CCMT09T302-EF	9.7	9.525	3.97	4.4	0.2							○		●	★				★	○											
	CCMT09T304-EF	9.7	9.525	3.97	4.4	0.4							○		●	★				★	★											
	CCMT09T308-EF	9.7	9.525	3.97	4.4	0.8							○		●	★				○	★											
	CCMT120404-EF	12.9	12.7	4.76	5.56	0.4							○		●	★				★	○											
	CCMT120408-EF	12.9	12.7	4.76	5.56	0.8							○		●	★				○	○											
HM	CCMT060204-HM	6.4	6.35	2.38	2.8	0.4		★	●	★	○				●							●				●	●					●
	CCMT060208-HM	6.4	6.35	2.38	2.8	0.8		★	●	○	○				●							○				○	●					
	CCMT09T304-HM	9.7	9.525	3.97	4.4	0.4	●	★	●	★	●				●							●				●	●					
	CCMT09T308-HM	9.7	9.525	3.97	4.4	0.8		★	●	★	●				●							●				●	●					
	CCMT120404-HM	12.9	12.7	4.76	5.56	0.4		★	●	○	○											○				○	○					
	CCMT120408-HM	12.9	12.7	4.76	5.56	0.8		★	●	★	●				○							●				●	●					
	CCMT120412-HM	12.9	12.7	4.76	5.56	1.2		○	○																	○						
EM	CCMT060204-EM	6.4	6.35	2.38	2.8	0.4									●	★					○		★									
	CCMT060208-EM	6.4	6.35	2.38	2.8	0.8									●	★					○		★									
	CCMT09T304-EM	9.7	9.525	3.97	4.4	0.4									●	★					★		★									
	CCMT09T308-EM	9.7	9.525	3.97	4.4	0.8									●	★					★		★									
	CCMT120404-EM	12.9	12.7	4.76	5.56	0.4									●	★					○		★									
	CCMT120408-EM	12.9	12.7	4.76	5.56	0.8									●	★					○		★									
	CCMT120412-EM	12.9	12.7	4.76	5.56	1.2									●	★					○		★									

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A184 A185 A218 A232 A233

CC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																				Cermet		Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HR	CCMT060204-HR	6.4	6.35	2.38	2.8	0.4		○	●	○	○				○																	
	CCMT060208-HR	6.4	6.35	2.38	2.8	0.8		○	●		●											●					●					
	CCMT09T304-HR	9.7	9.525	3.97	4.4	0.4			●		○				○																	
	CCMT09T308-HR	9.7	9.525	3.97	4.4	0.8		★	●	★	●											●			●	●	●				●	
For roughing	CCMT120408-HR	12.9	12.7	4.76	5.56	0.8		★	●		●				○							●			●	●	●				●	●
	CCMT120412-HR	12.9	12.7	4.76	5.56	1.2		○	●		●											○				●	○					
LC	CCGX060202-LC	6.4	6.35	2.38	2.8	0.2																								★	
	CCGX060204-LC	6.4	6.35	2.38	2.8	0.4																								★	
	CCGX09T302-LC	9.7	9.525	3.97	4.4	0.2																								★	
	CCGX09T304-LC	9.7	9.525	3.97	4.4	0.4																								★	
	CCGX09T308-LC	9.7	9.525	3.97	4.4	0.8																								★	
For Al machining	CCGX120404-LC	12.9	12.7	4.76	5.5	0.4																								★	
	CCGX120408-LC	12.9	12.7	4.76	5.5	0.8																								★	
LH	CCGX060202-LH	6.4	6.35	2.38	2.8	0.2																								★	
	CCGX060204-LH	6.4	6.35	2.38	2.8	0.4																								★	●
	CCGX060208-LH	6.4	6.35	2.38	2.8	0.8																								★	
For Al machining	CCGX09T302-LH	9.7	9.525	3.97	4.4	0.2																								★	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SCACR/L Kr:90°	SCLCR/L Kr:95°	SCLCR/L Kr:95°	SCFCR/L Kr:90°	SCLCR/L Kr:95°
Page A184	A185	A218	A232	A233

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LH For Al machining	CCGX09T304-LH	9.7	9.525	3.97	4.4	0.4																								★	●
	CCGX09T308-LH	9.7	9.525	3.97	4.4	0.8																								★	
	CCGX120402-LH	12.9	12.7	4.76	5.56	0.2																								○	
	CCGX120404-LH	12.9	12.7	4.76	5.56	0.4																								★	
	CCGX120408-LH	12.9	12.7	4.76	5.56	0.8																								★	
	CCGX120412-LH	12.9	12.7	4.76	5.56	1.2																								○	
Without chipbreaker	CCMW060204	6.4	6.35	2.38	2.8	0.4																								●	
	CCMW09T304	9.7	9.525	3.97	4.4	0.4																								●	●
	CCMW09T308	9.7	9.525	3.97	4.4	0.8	○																							○	
	CCMW120404	12.9	12.7	4.76	5.56	0.4																									●
	CCMW120408	12.9	12.7	4.76	5.56	0.8																								●	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SCACR/L Kr:90°	SCLCR/L Kr:95°	SCLCR/L Kr:95°	SCFCR/L Kr:90°	SCLCR/L Kr:95°
Page A184	A185	A218	A232	A233

DC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF	DCGT0702005R-USF	7.8	6.35	2.38	2.8	0.05									●	○																
	DCGT070201R-USF	7.8	6.35	2.38	2.8	0.1									●	○																
	DCGT070202R-USF	7.8	6.35	2.38	2.8	0.2									●	○																
For extra finishing	DCGT11T301R-USF	11.6	9.525	3.97	4.4	0.1									○	○																
	DCGT11T302R-USF	11.6	9.525	3.97	4.4	0.2									●	○																
USF	DCGT0702005L-USF	7.8	6.35	2.38	2.8	0.05									○	○																
	DCGT070201L-USF	7.8	6.35	2.38	2.8	0.1									○	○																
	DCGT070202L-USF	7.8	6.35	2.38	2.8	0.2									●	○																
For extra finishing	DCGT11T301L-USF	11.6	9.525	3.97	4.4	0.1									○	○																
	DCGT11T302L-USF	11.6	9.525	3.97	4.4	0.2									●	○																
SF	DCGT070202-SF	7.8	6.35	2.38	2.8	0.2							○																○			
	DCGT070204-SF	7.8	6.35	2.38	2.8	0.4							○																	○		
	DCGT070208-SF	7.8	6.35	2.38	2.8	0.8							○																			
For extra finishing	DCGT11T302-SF	11.6	9.525	3.97	4.4	0.2							○																○	○		
	DCGT11T304-SF	11.6	9.525	3.97	4.4	0.4							○																	★		
	DCGT11T308-SF	11.6	9.525	3.97	4.4	0.8							○																○	○		
HF	DCMT070202-HF	7.8	6.35	2.38	2.8	0.2		★	●	○					○														○			
	DCMT070204-HF	7.8	6.35	2.38	2.8	0.4		★	●	★	○				●												○		○		●	
	DCMT070208-HF	7.8	6.35	2.38	2.8	0.8		○	○		○																					
For finishing	DCMT11T302-HF	11.6	9.525	3.97	4.4	0.2		★	●	○					●														○			○
	DCMT11T304-HF	11.6	9.525	3.97	4.4	0.4		★	●	★	○				●												○	○	●			○
	DCMT11T308-HF	11.6	9.525	3.97	4.4	0.8		★	●	○					○														○			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SDACR/L Kr:90°

Page A186

SDJCR/L Kr:93°

A187

SDNCN Kr:62°30'

A188

SDQCR/L Kr:107°30'

A219

SDUCR/L Kr:93°

A220

SDZCR/L Kr:95°

A221

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

DC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EF	DCMT070202-EF	7.8	6.35	2.38	2.8	0.2							○		●	★				★	○											
	DCMT070204-EF	7.8	6.35	2.38	2.8	0.4							○		●	★				★	○											
	DCMT11T302-EF	11.6	9.525	3.97	4.4	0.2							○		●	★				★	○											
	DCMT11T304-EF	11.6	9.525	3.97	4.4	0.4							○		●	★				★	○											
For finishing	DCMT11T308-EF	11.6	9.525	3.97	4.4	0.8							○		●	★				○	○											
HM	DCMT070204-HM	7.8	6.35	2.38	2.8	0.4		★	●	★	●				●							●					●					
	DCMT070208-HM	7.8	6.35	2.38	2.8	0.8		★	●	★					○							○					○					
	DCMT11T304-HM	11.6	9.525	3.97	4.4	0.4	●	★	●	★	○				●							●				●	●		●		●	○
	DCMT11T308-HM	11.6	9.525	3.97	4.4	0.8	●	★	●	★	●				●							●				●	○		○			○
For semi-finishing	DCMT11T312-HM	11.6	9.525	3.97	4.4	1.2			○																							
EM	DCMT070204-EM	7.8	6.35	2.38	2.8	0.4									●	★					○		★									
	DCMT070208-EM	7.8	6.35	2.38	2.8	0.8									●	★					○		★									
	DCMT11T304-EM	11.6	9.525	3.97	4.4	0.4									●	★					○		★									
	DCMT11T308-EM	11.6	9.525	3.97	4.4	0.8									●	★					○		★									
For semi-finishing																																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SDACR/L	SDJCR/L	SDNCN	SDQCR/L	SDUCR/L	SDZCR/L
Kr:90°	Kr:93°	Kr:62°30'	Kr:107°30'	Kr:93°	Kr:95°
Page A186	A187	A188	A219	A220	A221

DC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HR	DCMT11T304-HR	11.6	9.525	3.97	4.4	0.4		○	●	○	○											○				○	●				
	DCMT11T308-HR	11.6	9.525	3.97	4.4	0.8		●	●	★	○											○			○	●	●				
	DCMT11T312-HR	11.6	9.525	3.97	4.4	1.2		○	●																						
For roughing																															
LC	DCGX070201-LC	7.8	6.35	2.38	2.8	0.1																								★	
	DCGX070202-LC	7.8	6.35	2.38	2.8	0.2																								★	
	DCGX070204-LC	7.8	6.35	2.38	2.8	0.4																								★	
	DCGX11T304-LC	11.6	9.525	3.97	4.4	0.4																								★	
For Al machining	DCGX11T308-LC	11.6	9.525	3.97	4.4	0.8																								★	
LH	DCGX070202-LH	7.8	6.35	2.38	2.8	0.2																								★	
	DCGX070204-LH	7.8	6.35	2.38	2.8	0.4																								★	○
	DCGX11T302-LH	11.6	9.525	3.97	4.4	0.2																								★	○
	DCGX11T304-LH	11.6	9.525	3.97	4.4	0.4																								★	●
For Al machining	DCGX11T308-LH	11.6	9.525	3.97	4.4	0.8																								★	
Without chipbreaker	DCMW070204	7.8	6.35	2.38	2.8	0.4																				○					
	DCMW11T304	11.6	9.525	3.97	4.4	0.4																								●	
	DCMW11T308	11.6	9.525	3.97	4.4	0.8																								●	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SDACR/L Kr:90°

Page A186

SDJCR/L Kr:93°

A187

SDNCN Kr:62°30'

A188

SDQCR/L Kr:107°30'

A219

SDUCR/L Kr:93°

A220

SDZCR/L Kr:95°

A221

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

RC□□ (Positive inserts)

Good working condition / Normal working condition / Bad working condition



Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)				Coated cemented carbide																	Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
	RCGT1204MO	12	12	4.76	4.4			○																							
	RCMT0803MO	8.0	8.0	3.18	3.36				○																						
	RCMT10T3MO	10	10	3.97	4.4				○																						
	RCMT1204MO	12	12	4.76	4.4	○		●	★															★	★	○					
	RCMT1606MO	16	16	6.35	5.5	○		●		●														★							

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Good working condition / Normal working condition / Bad working condition



Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)				Coated cemented carbide																	Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LH For Al machining	**RCGX0803MO-LH**	8.0	8.0	3.18	3.36																									★	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SRDCN

Page A202

SRGCR/L

Page A203

RC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)				Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
	RCMX0803MO	8.0	8.0	3.18	3.36			●		○														○							
	RCMX1003MO	10	10	3.18	3.6	●		●		●																				○	
	RCMX1204MO	12	12	4.76	4.4	○		●																						○	●
	RCMX1606MO	16	16	6.35	5.5	●		●		○																				○	
	RCMX2006MO	20	20	6.35	6.5	○	★	●	○	○																★				○	●
	RCMX2507MO	25	25	7.94	7.2		★	●	○	○																○					
	RCMX3209MO	32	32	9.52	9.5	○	○	●	○	○															●						

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

SC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HF	SCMT09T302-HF	9.525	9.525	3.97	4.4	0.2		○	○						○												○					
	SCMT09T304-HF	9.525	9.525	3.97	4.4	0.4		●	●	○																					
	SCMT09T308-HF	9.525	9.525	3.97	4.4	0.8		●	○						○												○				○
For finishing																															
EF	SCMT09T302-EF	9.525	9.525	3.97	4.4	0.2							○		●	★				★	○											
	SCMT09T304-EF	9.525	9.525	3.97	4.4	0.4							○		●	★				★	○											
	SCMT09T308-EF	9.525	9.525	3.97	4.4	0.8							○		●	★				○	○											
For finishing																															
HM	SCMT09T304-HM	9.525	9.525	3.97	4.4	0.4		○	●													●				●	●				
	SCMT09T308-HM	9.525	9.525	3.97	4.4	0.8		●	●	○	●				○							●				●	○				
	SCMT120404-HM	12.7	12.7	4.76	5.56	0.4		○	●		○																●				
	SCMT120408-HM	12.7	12.7	4.76	5.56	0.8		●	●	○	○		●		○							●				●					
For semi-finishing	SCMT120412-HM	12.7	12.7	4.76	5.56	1.2		○	○													○									
EM	SCMT09T304-EM	9.525	9.525	3.97	4.4	0.4									●	★					○		★								
	SCMT09T308-EM	9.525	9.525	3.97	4.4	0.8									●	★					○		★								
	SCMT120404-EM	12.7	12.7	4.76	5.56	0.4									●	★					○		★								
	SCMT120408-EM	12.7	12.7	4.76	5.56	0.8									●	★					○		★								
For semi-finishing	SCMT120412-EM	12.7	12.7	4.76	5.56	1.2									●	★					○		★								

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A194

A195

A196

A197

A222

SC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material	
P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LC	SCGX09T304-LC	9.525	9.525	3.97	4.4	0.4																								★	
	SCGX09T308-LC	9.525	9.525	3.97	4.4	0.8																								★	
	SCGX120408-LC	12.7	12.7	4.76	5.5	0.8																								★	
For Al machining																															
LH	SCGX09T302-LH	9.525	9.525	3.97	4.4	0.2																								○	
	SCGX09T304-LH	9.525	9.525	3.97	4.4	0.4																								○	
	SCGX09T308-LH	9.525	9.525	3.97	4.4	0.8																								★	
	SCGX120404-LH	12.7	12.7	4.76	5.56	0.4																								○	
For Al machining	SCGX120408-LH	12.7	12.7	4.76	5.56	0.8																								★	
HR	SCMT09T304-HR	9.525	9.525	3.97	4.4	0.4		★	●		●				●											○					
	SCMT09T308-HR	9.525	9.525	3.97	4.4	0.8		★	○		●															●	●				
	SCMT09T312-HR	9.525	9.525	3.97	4.4	1.2		★																							
	SCMT120404-HR	12.7	12.7	4.76	5.56	0.4		○	●		○																				
For roughing	SCMT120408-HR	12.7	12.7	4.76	5.56	0.8		★	●	○	●				○										○	●	●				
	SCMT120412-HR	12.7	12.7	4.76	5.56	1.2		○	○		●														○	○					
All round	SCMT09T304	9.525	9.525	3.97	4.4	0.4	○		●																						
	SCMT120404	12.7	12.7	4.76	5.56	0.4			○		○																				
	SCMT120408	12.7	12.7	4.76	5.56	0.8	○		●																		○				
Without chipbreaker	SCMW060204	6.35	6.35	2.38	2.8	0.4																									○
	SCMW09T304	9.525	9.525	3.97	4.4	0.4																						○			
	SCMW09T308	9.525	9.525	3.97	4.4	0.8	○																								
	SCMW120408	12.7	12.7	4.76	5.56	0.8	●																								

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SSBCR/L
Kr:75°
Page A194

SSDCN
Kr:45°
A195

SSKCR/L
Kr:75°
A196

SSSCR/L
Kr:45°
A197

SSKCR/L
Kr:75°
A222

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF For extra finishing	TCGT110301R-USF	11	6.35	3.18	2.8	0.1									●	○																
	TCGT110302R-USF	11	6.35	3.18	2.8	0.2									●	○																
USF For extra finishing	TCGT110301L-USF	11	6.35	3.18	2.8	0.1									●	○																
	TCGT110302L-USF	11	6.35	3.18	2.8	0.2									●	○																
SF For extra finishing	TCGT090202-SF	9.6	5.56	2.38	2.5	0.2							○																			
	TCGT090204-SF	9.6	5.56	2.38	2.5	0.4							○																	○		
	TCGT090208-SF	9.6	5.56	2.38	2.5	0.8							○																			
	TCGT110302-SF	11	6.35	3.18	2.8	0.2							○																○			
	TCGT110304-SF	11	6.35	3.18	2.8	0.4							○																○	○		
	TCGT110308-SF	11	6.35	3.18	2.8	0.8							○																			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order



Applicable tool

STACR/L Kr:90°
Page A198

STFCR/L Kr:90°
A198

STGCR/L Kr:91°
A199

STECR/L Kr:60°
A200

STFCR/L Kr:90°
A223

TC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HF For finishing	TCMT090202-HF	9.6	5.56	2.38	2.5	0.2		★	●													○						○		○	
	TCMT090204-HF	9.6	5.56	2.38	2.5	0.4		★	●																			●			
	TCMT090208-HF	9.6	5.56	2.38	2.5	0.8			○																	○					
	TCMT110202-HF	11	6.35	2.38	2.8	0.2			●						●							○									
	TCMT110204-HF	11	6.35	2.38	2.8	0.4	●	★	●	★												●					●		○			
	TCMT110208-HF	11	6.35	2.38	2.8	0.8		○	●	○					●							○				○				○	
	TCMT16T302-HF	16.5	9.525	3.97	4.4	0.2		○																							
	TCMT16T304-HF	16.5	9.525	3.97	4.4	0.4		●	●						○												●	●			
	TCMT16T308-HF	16.5	9.525	3.97	4.4	0.8		○	●																			○		○	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A198 A198 A199 A200 A223

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EF For finishing	TCMT090202-EF	9.6	5.56	2.38	2.5	0.2							○		●	★				★	○											
	TCMT090204-EF	9.6	5.56	2.38	2.5	0.4							○		●	★				★	○											
	TCMT110202-EF	11	6.35	2.38	2.8	0.2							○		●	★				★	○											
	TCMT110204-EF	11	6.35	2.38	2.8	0.4							○		●	★				★	○											
	TCMT110208-EF	11	6.35	2.38	2.8	0.8							○		●	★				○	○											
	TCMT16T304-EF	16.5	9.525	3.97	4.4	0.4							○		●	★				★	○											
	TCMT16T308-EF	16.5	9.525	3.97	4.4	0.8							○		●	★				○	○											
EM For semi-finishing	TCMT090204-EM	9.6	5.56	2.38	2.8	0.4									●	★					○		★									
	TCMT090208-EM	9.6	5.56	2.38	2.8	0.8									●	★					○		★									
	TCMT110204-EM	11	6.35	2.38	2.8	0.4									●	★					○		★									
	TCMT110208-EM	11	6.35	2.38	2.8	0.8									●	★					○		★									
	TCMT110212-EM	11	6.35	2.38	2.8	1.2									●	★					○		★									
	TCMT16T304-EM	16.5	9.525	3.97	4.4	0.4									●	★					○		★									
	TCMT16T308-EM	16.5	9.525	3.97	4.4	0.8									●	★					○		★									
	TCMT16T312-EM	16.5	9.525	3.97	4.4	1.2									●	★					○		★									

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

STACR/L Kr:90°	STFCR/L Kr:90°	STGCR/L Kr:91°	STECR/L Kr:60°	STFCR/L Kr:90°
Page A198	A198	A199	A200	A223

TC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
HM	TCMT090204-HM	9.6	5.56	2.38	2.5	0.4		★	●		○											○					●				
	TCMT090208-HM	9.6	5.56	2.38	2.5	0.8		○	●		○																				
	TCMT110204-HM	11	6.35	2.38	2.8	0.4		★	●	○	○				●							●				●	●		○		
	TCMT110208-HM	11	6.35	2.38	2.8	0.8		★	●		○																●				
For semi-finishing	TCMT16T304-HM	16.5	9.525	3.97	4.4	0.4		★	●	★	●											●				○	●				
	TCMT16T308-HM	16.5	9.525	3.97	4.4	0.8		★	●	★	●											●				●	●			○	
	TCMT16T312-HM	16.5	9.525	3.97	4.4	1.2			●		●											○									
HR	TCMT090204-HR	9.6	5.56	2.38	2.5	0.4			○																						
	TCMT090208-HR	9.6	5.56	2.38	2.5	0.8																				○					●
	TCMT110204-HR	11	6.35	2.38	2.8	0.4			○																						
	TCMT110208-HR	11	6.35	2.38	2.8	0.8			○																						
For roughing	TCMT16T304-HR	16.5	9.525	3.97	4.4	0.4		○	●																						
	TCMT16T308-HR	16.5	9.525	3.97	4.4	0.8		●	●		●															●	●				
	TCMT16T312-HR	16.5	9.525	3.97	4.4	1.2		○	●																	●	●				○
	TCMT220408-HR	22	12.7	4.76	5.5	0.8		○	●		○											●									
LC	TCGX090202-LC	9.6	5.56	2.38	2.5	0.2																								★	
	TCGX090204-LC	9.6	5.56	2.38	2.5	0.4																								★	
	TCGX110202-LC	11	6.35	2.38	2.8	0.2																								★	
	TCGX110204-LC	11	6.35	2.38	2.8	0.4																								★	
For Al machining	TCGX110208-LC	11	6.35	2.38	2.8	0.8																								★	
	TCGX16T304-LC	16.5	9.525	3.97	4.4	0.4																								★	
	TCGX16T308-LC	16.5	9.525	3.97	4.4	0.8																								★	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A198 A198 A199 A200 A223

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

TC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																	Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LH	TCGX090202-LH	9.6	5.56	2.38	2.5	0.2																								★	
	TCGX090204-LH	9.6	5.56	2.38	2.5	0.4																								★	
	TCGX110202-LH	11	6.35	2.38	2.8	0.2																								★	
	TCGX110204-LH	11	6.35	2.38	2.8	0.4																								★	
	TCGX110208-LH	11	6.35	2.38	2.8	0.8																								★	
For Al machining	TCGX16T302-LH	16.5	9.525	3.97	4.4	0.2																								○	
	TCGX16T304-LH	16.5	9.525	3.97	4.4	0.4																								★	
	TCGX16T308-LH	16.5	9.525	3.97	4.4	0.8																								★	
All round	TCMT220408	22	12.7	4.76	5.5	0.8	○		●																	○						○
Without chipbreaker	TCMW110204	11	6.35	2.38	2.8	0.4																								●	○
	TCMW16T304	16.5	9.525	3.97	4.4	0.4	○																								○
	TCMW16T308	16.5	9.525	3.97	4.4	0.8										○										○	○				
	TCMW16T312	16.5	9.525	3.97	4.4	1.2	○									○															
	TCMW220408	22	12.7	4.76	5.5	0.8	○																				○				

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

STACR/L Kr:90°	STFCR/L Kr:90°	STGCR/L Kr:91°	STECR/L Kr:60°	STFCR/L Kr:90°
Page A198	A198	A199	A200	A223

VC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	Ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF	VCGT080201R-USF	8	4.76	2.38	2.3	0.1									○	○																
	VCGT080202R-USF	8	4.76	2.38	2.3	0.2									●	○																
For extra finishing	VCGT110301R-USF	11	6.35	3.18	2.8	0.1									●	○																
	VCGT110302R-USF	11	6.35	3.18	2.8	0.2									●	○																
USF	VCGT080201L-USF	8	4.76	2.38	2.3	0.1									○	○																
	VCGT080202L-USF	8	4.76	2.38	2.3	0.2									○	○																
For extra finishing	VCGT110301L-USF	11	6.35	3.18	2.8	0.1									○	○																
	VCGT110302L-USF	11	6.35	3.18	2.8	0.2									●	○																
SF	VCGT110302-SF	11	6.35	3.18	2.8	0.2							○																○	★		
	VCGT110304-SF	11	6.35	3.18	2.8	0.4							○																○	★		
For extra finishing																																
HF	VCGT110304-HF	11	6.35	3.18	2.8	0.4			●																							
For finishing																																
NF	VCGT160408-NF	16.5	9.525	4.76	4.4	0.8							●	★																		
For finishing																																
NGF	VCGT160408-NGF	16.5	9.525	4.76	4.4	0.8							○	●			○															
For finishing																																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A224

A225

A192

A193

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

VC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	Ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
LC For Al machining	VCGX110301-LC	11	6.35	3.18	2.8	0.1																								★	
	VCGX110302-LC	11	6.35	3.18	2.8	0.2																								★	
	VCGX110304-LC	11	6.35	3.18	2.8	0.4																								★	
	VCGX110308-LC	11	6.35	3.18	2.8	0.8																								★	
	VCGX160404-LC	16.6	9.525	4.76	4.4	0.4																								★	
	VCGX160408-LC	16.6	9.525	4.76	4.4	0.8																								★	
	VCGX160412-LC	16.6	9.525	4.76	4.4	1.2																								★	
	VCGX220530-LC	22	12.7	5.56	5.5	3.0																								★	
LH For Al machining	VCGX110202-LH	11	6.35	2.38	2.8	0.2																								○	
	VCGX110204-LH	11	6.35	2.38	2.8	0.4																								★	
	VCGX110301-LH	11	6.35	3.18	2.8	0.1																								★	●
	VCGX110302-LH	11	6.35	3.18	2.8	0.2																								★	●
	VCGX110304-LH	11	6.35	3.18	2.8	0.4																								★	●
	VCGX110308-LH	11	6.35	3.18	2.8	0.8																								○	
	VCGX160402-LH	16.6	9.525	4.76	4.4	0.2																								★	
	VCGX160404-LH	16.6	9.525	4.76	4.4	0.4																								★	○
	VCGX160408-LH	16.6	9.525	4.76	4.4	0.8																								★	○
	VCGX160412-LH	16.6	9.525	4.76	4.4	1.2																								★	●
	VCGX220530-LH	22	12.7	5.56	5.5	3.0																								★	●

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SVQCR/L
Kr:107°30'
Page A224

SVUCR/L
Kr:93°
A225

SVVCN
Kr:72°30'
A192

SVJCR/L
Kr:93°
A193

WC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material		
P	Steel	😊😊😐😐☹☹😊😐😐☹😊😊
M	Stainless steel	😊😐😐😐😊😊😐😐😊😊
K	Cast iron	😊😐☹☹☹
N	Non-ferrous metal	😐☹
S	Heat resistant alloy, Ti alloy	😊😊😊😊☹😊

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
53	WCMX040208R-53	4.3	6.35	2.38	3.1	0.8			●																						○
	WCMX06T308R-53	6.5	9.525	3.97	3.7	0.8	●		○																						○
	WCMX080412R-53	8.7	12.7	4.76	4.3	1.2									○	○	○										○				

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SWACR/L
Kr:90°

Page A201

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

VB□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	Ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
SF	**VBGT110302-SF**	11	6.35	3.18	2.8	0.2							○																○	○		
	VBGT110304-SF	11	6.35	3.18	2.8	0.4							○																○	○		
For extra finishing																																
EF	**VBMT110302-EF**	11	6.35	3.18	2.8	0.2							○		●	★				★	○											
	VBMT110304-EF	11	6.35	3.18	2.8	0.4							○		●	★				★	○											
	VBMT110308-EF	11	6.35	3.18	2.8	0.8							○		●	★				○	○											
	VBMT160404-EF	16.5	9.525	4.76	4.4	0.4							○		●	★				★	●											
For finishing	**VBMT160408-EF**	16.5	9.525	4.76	4.4	0.8							○		●	★				○	●											
HF	**VBMT110202-HF**	11	6.35	2.38	2.8	0.2			●		○				●																	
	VBMT110204-HF	11	6.35	2.38	2.8	0.4			●						○												○					
	VBMT110208-HF	11	6.35	2.38	2.8	0.8			●						○																	
For finishing																																
NF	**VBET160404-NF**	16.5	9.525	4.76	4.4	0.4							●	★																		
	VBET160408-NF	16.5	9.525	4.76	4.4	0.8							●	★																		
For finishing																																
NGF	**VBET160404-NGF**	16.5	9.525	4.76	4.4	0.4							○	●			○															
	VBET160408-NGF	16.5	9.525	4.76	4.4	0.8							○	●			○															
	VBET160412-NGF	16.5	9.525	4.76	4.4	1.2							○	●			○															
For finishing																																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A189

A190

A191

A226

A227

VB□□ (Positive inserts)



Good working condition Normal working condition Bad working condition



Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
EM	**VBMT110304-EM**	11	6.35	3.18	2.8	0.4									●	★					○		★									
	VBMT110308-EM	11	6.35	3.18	2.8	0.8									●	★					○		★									
For semi-finishing																																
HM	**VBMT160404-HM**	16.5	9.525	4.76	4.4	0.4		★	●	★	●				●							●				●						○
	VBMT160408-HM	16.5	9.525	4.76	4.4	0.8		★	●	★	●				●							●				●	●					
	VBMT160412-HM	16.5	9.525	4.76	4.4	1.2			●						○							○					○					○
For semi-finishing																																
HR	**VBMT160404-HR**	16.5	9.525	4.76	4.4	0.4		★	●	○	●																					
	VBMT160408-HR	16.5	9.525	4.76	4.4	0.8		○	●	○	●																○					
	VBMT160412-HR	16.5	9.525	4.76	4.4	1.2					○																					
For roughing	**VBGT160408-HR**	16.5	9.525	4.76	4.4	0.8			○																							
SNR	**VBMT160408-SNR**	16.5	9.525	4.76	4.4	0.8							○	●			○							●								
	VBMT160412-SNR	16.5	9.525	4.76	4.4	1.2							○	●			○							○								
For roughing																																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

Page A189 A190 A191 A226 A227

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

CP□□ (Positive inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
SF	**CPGT060202-SF**	6.4	6.35	2.38	2.8	0.2							○																○			
	CPGT060204-SF	6.4	6.35	2.38	2.8	0.4							○																○			
	CPGT09T304-SF	9.7	9.525	3.97	4.4	0.4							○																○	○		
For extra finishing																																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SCLPR/L
Kr:95°

Page A228

DP□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																		Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF	DPGT0702005R-USF	7.8	6.35	2.38	2.8	0.05									○	○																
	DPGT070201R-USF	7.8	6.35	2.38	2.8	0.1									○	○																
For extra finishing	DPGT11T301R-USF	11.6	9.525	3.97	4.4	0.1									●	○																
USF	DPGT0702005L-USF	7.8	6.35	2.38	2.8	0.05									○	○																
	DPGT070201L-USF	7.8	6.35	2.38	2.8	0.1									○	○																
For extra finis hing	DPGT11T301L-USF	11.6	9.525	3.97	4.4	0.1									○	○																
SF	DPGT070202-SF	7.8	6.35	2.38	2.8	0.2							○																○	○		
	DPGT070204-SF	7.8	6.35	2.38	2.8	0.4							○																○			
	DPGT070208-SF	7.8	6.35	2.38	2.8	0.8							○																			
For extra finishing	DPGT11T304-SF	11.6	9.525	3.97	4.4	0.4							○																○			
	DPGT11T308-SF	11.6	9.525	3.97	4.4	0.8							○																			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

SDQPR/L
Kr:107°30'

Page A229

SDUPR/L
Kr:93°

A230

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

SP□□ (Positive inserts)

Good working condition Normal working condition Bad working condition



Workpiece material

		YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
P	Steel	😊	😊	😐	😐	☹	☹	😊		😐	😐		☹											😊	😊		
M	Stainless steel							😊		😐	😐			😐	😊	😊	😐	😐						😊	😊		
K	Cast iron																			😊	😐	☹	☹				☹
N	Non-ferrous metal																									😐	☹
S	Heat resistant alloy, Ti alloy							😊	😊			😊							😊							😊	

Inserts shape	Type	Dimensions(mm) L	ØI.C	S	ød	r	Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
							YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
Without chipbreaker	**SPMW09T304**	9.525	9.525	3.97	4.4	0.4			○																				○	
	SPMW09T308	9.525	9.525	3.97	4.4	0.8	●																							
	SPMW120408	12.7	12.7	4.76	5.56	0.8																								○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

TB□□ (Positive inserts)

Good working condition Normal working condition Bad working condition



Workpiece material

		YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
P	Steel	😊	😊	😐	😐	☹	☹	😊		😐	😐		☹											😊	😊		
M	Stainless steel							😊		😐	😐			😐	😊	😊	😐	😐						😊	😊		
K	Cast iron																			😊	😐	☹	☹				☹
N	Non-ferrous metal																									😐	☹
S	Heat resistant alloy, Ti alloy							😊	😊			😊							😊							😊	

Inserts shape	Type	Dimensions(mm) L	ØI.C	S	ød	r	Coated cemented carbide																			Cermet	Coated cermet	Cemented carbide	
							YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
For extra finishing	**TBGH060102L**	6.4	3.97	1.59	2.2	0.2							★																★			
	TBGH060104L	6.4	3.97	1.59	2.2	0.4							★																			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

TP□□ (Positive inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																	Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
For extra finishing	TPGH090202L	9.6	5.56	2.38	2.8	0.2							●																○			
	TPGH090204L	9.6	5.56	2.38	2.8	0.4							●																●			
	TPGH110302L	11	6.35	3.18	3.18	0.2							○																●			
	TPGH110304L	11	6.35	3.18	3.18	0.4							●																●			

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

TP□□ (Positive inserts)

Good working condition Normal working condition Bad working condition





Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																	Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
SF For extra finishing	TPGT090202-SF	9.6	5.56	2.38	2.5	0.2							○																	○		
	TPGT090204-SF	9.6	5.56	2.38	2.5	0.4							○																○	★		
	TPGT090208-SF	9.6	5.56	2.38	2.5	0.8							○																○			
	TPGT110302-SF	11	6.35	3.18	2.8	0.2							○																○			
	TPGT110304-SF	11	6.35	3.18	2.8	0.4							○																○	○		
	TPGT110308-SF	11	6.35	3.18	2.8	0.8							○																	○		

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

STUPR/L
Kr:93°

Page A231

Insert code key A50–A51
Grade selection reference A19/A36–A48
Chipbreaker selection reference A22–A35
Recommended cutting parameters A241–A244

VP□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material

P	Steel
M	Stainless steel
K	Cast iron
N	Non-ferrous metal
S	Heat resistant alloy, Ti alloy

Inserts shape	Type	Dimensions(mm)					Coated cemented carbide																Cermet	Coated cermet	Cemented carbide	
		L	ØI.C	S	Ød	r	YBC151	YBC152	YBC251	YBC252	YBC351	YBC352	YBG102	YBG105	YBG202	YBG205	YBG212	YBG302	YBM151	YBM153	YBM215	YBM251	YBM253	YBS103	YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	YD101	YD201
USF	VPGT080201R-USF	8	4.76	2.38	2.3	0.1									○	○																
	VPGT080202R-USF	8	4.76	2.38	2.3	0.2									○	○																
For extra finishing	VPGT110301R-USF	11	6.35	3.18	2.8	0.1									●	○																
USF	VPGT080201L-USF	8	4.76	2.43	2.3	0.1									●	○																
	VPGT080202L-USF	8	4.76	2.43	2.3	0.2									●	○																
For extra finishing	VPGT110301L-USF	11	6.35	3.18	2.8	0.1									○	○																

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order



PCBN&PCD Insert

PCBN&PCD inserts code key

Insert shape

A	 B	C
D	E	H
K	L	M
P	S	T
V	W	Others Z

Tolerance class



Code	Nose height M Tolerance(mm)	Inscribed circle Tolerance(mm)	Thickness S Tolerance(mm)	Code	Nose height M Tolerance(mm)	Inscribed circle Tolerance(mm)	Thickness S Tolerance(mm)
A	±0.005	±0.025	±0.025	J	±0.005	±0.05-±0.13	±0.025
F	±0.005	±0.013	±0.025	K	±0.013	±0.05-±0.13	±0.025
C	±0.013	±0.025	±0.025	L	±0.025	±0.05-±0.13	±0.025
H	±0.013	±0.013	±0.025	M	±0.08-±0.18	±0.05-±0.13	±0.13
E	±0.025	±0.025	±0.025	N	±0.08-±0.18	±0.05-±0.13	±0.025
G	±0.025	±0.025	±0.13	U	±0.13-±0.38	±0.08-±0.25	±0.13

C N G A 12

Clearance angle of main cutting edge

Code	Clearance angle	Code	Clearance angle
A	 3°	B	 5°
C	 7°	D	 15°
E	 20°	F	 25°
G	 30°	N	 0°
P	11°	O	Other clearance angle

Chipbreaker and clamping system

Code	With/ Without hole	Section plane of insert
N	Without	
B	With	 > 65°
C	With	 > 65°
A	With	
W	With	 ≤65°
Q	With	 ≤65°
X	---	Special

Length of cutting edge

Diameter of IC (mm)	Insert shape						
	C	D	R	S	T	V	W
3.97					06		
5.0			05				
5.56					09		
6.0			06				
6.35	06	07			11	11	
8.0			08				
9.525	09	11	09	09	16	16	06
10.0			10				
12.0			12				
12.7	12	15	12	12	22	22	08
15.875	16		15	15	27		
16.0		19	16				
19.05	19		19	19	33		
20.0			20				
25.0	25	25	25				
25.4			25	25			
31.75			31				
32			32				

PCBN&PCD inserts code key

Insert thickness



Thickness is defined as height from bottom of insert to the highest part of cutting edge.

Code	Insert thickness(mm)	Code	Insert thickness(mm)
02	2.38	06	6.35
T2	2.58	T6	6.75
03	3.18	07	7.94
T3	3.97	09	9.52
04	4.76	T9	9.72
T4	4.96	11	11.11
05	5.56	12	12.70
T5	5.95		

Nose radius code

Code	Nose radius(mm)
00	No radius
02	0.2
04	0.4
08	0.8
12	1.2
16	1.6
20	2.0
24	2.4
32	3.2
X	Others
Diameter of insert (Metric)	Round insert

Type of cutting edge

Code	Type of cutting edge	Picture
E	Honing	
T	Chamfering	
S	Chamfering +honing	
F	Sharp edges	

04 04 A T 010 20 - 2 S

Insert Structure

Code	Type of cutting edge	Diagram
A	Single-sided insert	
B	Intact insert	
C	penetration insert	
D	Double-sided insert	

Chamfer width



Code	Dimensions (mm)
000	--
008	0.08
012	0.12
017	0.17
022	0.22

Chamfer angle

Code	Angle (°)
00	--
10	10
15	15
20	20
25	25

Cutting edge number

Code	number
/	number1
2	number2
3	number3
4	number4
6	number6

The length of cutting edge

	Standard	Elongate	Overlength
Code	Omission	S	SS
Length	Standard	+1mm	+2mm

CN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		CNGA120404AE-2	AE	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		CNGA120408AE-2		12.7	4.76	5.156	0.8	2.4	○	○								○	○	○
		CNGA120412AE-2		12.7	4.76	5.156	1.2	2.3	○	○								○	○	○
		CNGA120404AS01225-2	S01225	12.7	4.76	5.156	0.4	2.5	○	○			○	○	○	○	○	○	○	○
		CNGA120408AS01225-2		12.7	4.76	5.156	0.8	2.4	○	○			○	○	○	○	○	○	○	○
		CNGA120412AS01225-2		12.7	4.76	5.156	1.2	2.3	○	○			○	○	○	○	○	○	○	○
		CNGA120404AS00815-2	S00815	12.7	4.76	5.156	0.4	2.5					○	○	○					
		CNGA120408AS00815-2		12.7	4.76	5.156	0.8	2.4					○	○	○					
		CNGA120412AS00815-2		12.7	4.76	5.156	1.2	2.3					○	○	○					
		CNGA 120404AS01735-2	S01735	12.7	4.76	5.156	0.4	2.5							○	○	○			
		CNGA120408AS01735-2		12.7	4.76	5.156	0.8	2.4							○	○	○			
		CNGA120412AS01735-2		12.7	4.76	5.156	1.2	2.3							○	○	○			
		CNGA120404AT01215-2	T01215	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		CNGA120408AT01215-2		12.7	4.76	5.156	0.8	2.4	○	○								○	○	○
		CNGA120412AT01215-2		12.7	4.76	5.156	1.2	2.3	○	○								○	○	○
Double-sided insert		CNGA120404DE-4	DE	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		CNGA120408DE-4		12.7	4.76	5.156	0.8	2.4	○	○								○	○	○
		CNGA120412DE-4		12.7	4.76	5.156	1.2	2.3	○	○								○	○	○
		CNGA120404DT01215-4	T01215	12.7	4.76	5.156	0.4	2.5	★	★								★	★	★
		CNGA120408DT01215-4		12.7	4.76	5.156	0.8	2.4	★	★								★	★	★
		CNGA120412DT01215-4		12.7	4.76	5.156	1.2	2.3	★	★								★	★	★

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DCLNR/L
Kr:95°
Page A166

PCLNR/L
Kr:95°
A173

PCLNR/L
Kr:95°
A212

CN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		CNGA120404DS01225-4	S01225	12.7	4.76	5.156	0.4	2.5	○	○										
		CNGA120408DS01225-4		12.7	4.76	5.156	0.8	2.4	○	○										
		CNGA120412DS01225-4		12.7	4.76	5.156	1.2	2.3	○	○										
		CNGA120404DS00815-4	S00815	12.7	4.76	5.156	0.4	2.5					★	★	○					
		CNGA120408DS00815-4		12.7	4.76	5.156	0.8	2.4					★	★	○					
		CNGA120412DS00815-4		12.7	4.76	5.156	1.2	2.3					★	★	○					
		CNGA120404DS01225-4	S01225	12.7	4.76	5.156	0.4	2.5					★	★	★	★	★	○	○	○
		CNGA120408DS01225-4		12.7	4.76	5.156	0.8	2.4					★	★	★	★	★	○	○	○
		CNGA120412DS01225-4		12.7	4.76	5.156	1.2	2.3					★	★	★	★	★	○	○	○
		CNGA120404DS01735-4	S01735	12.7	4.76	5.156	0.4	2.5							○	★	○			
		CNGA120408DS01735-4		12.7	4.76	5.156	0.8	2.4							○	★	○			
		CNGA120412DS01735-4		12.7	4.76	5.156	1.2	2.3							○	★	○			
Penetration insert		CNGA120404CE-2	CE	12.7	4.76	5.156	0.4	2.5			○									
		CNGA120408CE-2		12.7	4.76	5.156	0.8	2.4			○									
		CNGA120412CE-2		12.7	4.76	5.156	1.2	2.3			○									
		CNGA120404CT01215-2	T01215	12.7	4.76	5.156	0.4	2.5			★									
		CNGA120408CT01215-2		12.7	4.76	5.156	0.8	2.4			★									
		CNGA120412CT01215-2		12.7	4.76	5.156	1.2	2.3			★									
		CNGA120404CS01225-2	S01225	12.7	4.76	5.156	0.4	2.5			○									
		CNGA120408CS01225-2		12.7	4.76	5.156	0.8	2.4			○									
		CNGA120412CS01225-2		12.7	4.76	5.156	1.2	2.3			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DCLNR/L Kr:95°
Page A166

PCLNR/L Kr:95°
A173

PCLNR/L Kr:95°
A212

CN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron	😊	😊	😐	☹												
S	Heat resistant alloy, Ti alloy														😊	😐	☹
H	Super hard material					😊	😊	😐	☹	☹							
N	Non ferrous metal																

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		**CNGN120404BE**	**BE**	12.7	4.76	0.4			○									
		CNGN120408BE		12.7	4.76	0.8			○									
		CNGN120412BE		12.7	4.76	1.2			○									
		CNGN120404BT01215	**T01215**	12.7	4.76	0.4			★									
		CNGN120408BT01215		12.7	4.76	0.8			★									
		CNGN120412BT01215		12.7	4.76	1.2			★									
		CNGN120404BS01225	**S01225**	12.7	4.76	0.4			○									
		CNGN120408BS01225		12.7	4.76	0.8			○									
		CNGN120412BS01225		12.7	4.76	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

DN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		DNGA150404AE-2	AE	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		DNGA150408AE-2		12.7	4.76	5.156	0.8	2.1	○	○								○	○	○
		DNGA150412AE-2		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		DNGA150604AE-2		12.7	6.35	5.156	0.4	2.5	○	○								○	○	○
		DNGA150608AE-2		12.7	6.35	5.156	0.8	2.1	○	○								○	○	○
		DNGA150612AE-2		12.7	6.35	5.156	1.2	2.0	○	○								○	○	○
		DNGA150404AT01215-2	T01215	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		DNGA150408AT01215-2		12.7	4.76	5.156	0.8	2.1	○	○								○	○	○
		DNGA150412AT01215-2		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		DNGA150604AT01215-2		12.7	6.35	5.156	0.4	2.5	○	○								○	○	○
		DNGA150608AT01215-2		12.7	6.35	5.156	0.8	2.1	○	○								○	○	○
		DNGA150612AT01215-2		12.7	6.35	5.156	1.2	2.0	○	○								○	○	○
		DNGA150404AS01225-2	S01225	12.7	4.76	5.156	0.4	2.5	○	○			○	○	○	○	○	○	○	○
		DNGA150408AS01225-2		12.7	4.76	5.156	0.8	2.1	○	○			○	○	○	○	○	○	○	○
		DNGA150412AS01225-2		12.7	4.76	5.156	1.2	2.0	○	○			○	○	○	○	○	○	○	○
		DNGA150604AS01225-2		12.7	6.35	5.156	0.4	2.5	○	○			○	○	○	○	○	○	○	○
		DNGA150608AS01225-2		12.7	6.35	5.156	0.8	2.1	○	○			○	○	○	○	○	○	○	○
		DNGA150612AS01225-2		12.7	6.35	5.156	1.2	2.0	○	○			○	○	○	○	○	○	○	○
		DNGA150404AS00815-2	S00815	12.7	4.76	5.156	0.4	2.5					○	○	○					
		DNGA150408AS00815-2		12.7	4.76	5.156	0.8	2.1					○	○	○					
		DNGA150412AS00815-2		12.7	4.76	5.156	1.2	2.0					○	○	○					
		DNGA150604AS00815-2		12.7	6.35	5.156	0.4	2.5					○	○	○					
		DNGA150608AS00815-2		12.7	6.35	5.156	0.8	2.1					○	○	○					
		DNGA150612AS00815-2		12.7	6.35	5.156	1.2	2.0					○	○	○					

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DDJNR/L Kr:93° — Page A167

PDJNR/L Kr:93° — A174

PDPNN Kr:62°30' — A175

PDPNR/L Kr:62°30' — A213

PDUNR/L Kr:93° — A214

DN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specification	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		DNGA150404AS01735-2	S01735	12.7	4.76	5.156	0.4	2.5							○	○	○			
		DNGA150408AS01735-2		12.7	4.76	5.156	0.8	2.1							○	○	○			
		DNGA150412AS01735-2		12.7	4.76	5.156	1.2	2.0							○	○	○			
		DNGA150604AS01735-2		12.7	6.35	5.156	0.4	2.5							○	○	○			
		DNGA150608AS01735-2		12.7	6.35	5.156	0.8	2.1							○	○	○			
		DNGA150612AS01735-2		12.7	6.35	5.156	1.2	2.0							○	○	○			
Double-sided insert		DNGA150404DE-4	DE	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		DNGA150408DE-4		12.7	4.76	5.156	0.8	2.1	○	○								○	○	○
		DNGA150412DE-4		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		DNGA150604DE-4		12.7	6.35	5.156	0.4	2.5	○	○								○	○	○
		DNGA150608DE-4		12.7	6.35	5.156	0.8	2.1	○	○								○	○	○
		DNGA150612DE-4		12.7	6.35	5.156	1.2	2.0	○	○								○	○	○
		DNGA150404DT01215-4	T01215	12.7	4.76	5.156	0.4	2.5	★	★								★	★	★
		DNGA150408DT01215-4		12.7	4.76	5.156	0.8	2.1	★	★								★	★	★
		DNGA150412DT01215-4		12.7	4.76	5.156	1.2	2.0	★	★								★	★	★
		DNGA150604DT01215-4		12.7	6.35	5.156	0.4	2.5	★	★								★	★	★
		DNGA150608DT01215-4		12.7	6.35	5.156	0.8	2.1	★	★								★	★	★
		DNGA150612DT01215-4		12.7	6.35	5.156	1.2	2.0	★	★								★	★	★

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DDJNR/L Kr:93° Page A167

PDJNR/L Kr:93° A174

PDPNN Kr:62°30' A175

PDPNR/L Kr:62°30' A213

PDUNR/L Kr:93° A214

DN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron
S	Heat resistant alloy, Ti alloy
H	Super hard material
N	Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		DNGA150404DS01225-4	S01225	12.7	4.76	5.156	0.4	2.5	○	○			★	★	★	★	★	○	○	○
		DNGA150408DS01225-4		12.7	4.76	5.156	0.8	2.1	○	○			★	★	★	★	★	○	○	○
		DNGA150412DS01225-4		12.7	4.76	5.156	1.2	2.0	○	○			★	★	★	★	★	○	○	○
		DNGA150602DS01225-4		12.7	6.35	5.156	0.2	2.7					★	★	★	★	★			
		DNGA150604DS01225-4		12.7	6.35	5.156	0.4	2.5	○	○			★	★	★	★	★	○	○	○
		DNGA150608DS01225-4		12.7	6.35	5.156	0.8	2.1	○	○			★	★	★	★	★	○	○	○
		DNGA150612DS01225-4		12.7	6.35	5.156	1.2	2.0	○	○			★	★	★	★	★	○	○	○
		DNGA150404DS00815-4	S00815	12.7	4.76	5.156	0.4	2.5					★	★	○					
		DNGA150408DS00815-4		12.7	4.76	5.156	0.8	2.1					★	★	○					
		DNGA150412DS00815-4		12.7	4.76	5.156	1.2	2.0					★	★	○					
		DNGA150602DS00815-4		12.7	6.35	5.156	0.2	2.7					★	★	○					
		DNGA150604DS00815-4		12.7	6.35	5.156	0.4	2.5					★	★	○					
		DNGA150608DS00815-4		12.7	6.35	5.156	0.8	2.1					★	★	○					
		DNGA150612DS00815-4		12.7	6.35	5.156	1.2	2.0					★	★	○					
		DNGA150404DS01735-4	S01735	12.7	4.76	5.156	0.4	2.5							○	★	○			
		DNGA150408DS01735-4		12.7	4.76	5.156	0.8	2.1							○	★	○			
		DNGA150412DS01735-4		12.7	4.76	5.156	1.2	2.0							○	★	○			
		DNGA150602DS01735-4		12.7	6.35	5.156	0.2	2.7							○	★	○			
		DNGA150604DS01735-4		12.7	6.35	5.156	0.4	2.5							○	★	○			
		DNGA150608DS01735-4		12.7	6.35	5.156	0.8	2.1							○	★	○			
		DNGA150612DS01735-4		12.7	6.35	5.156	1.2	2.0							○	★	○			

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DDJNR/L
Kr:93°
Page A167

PDJNR/L
Kr:93°
A174

PDPNN
Kr:62°30'
A175

PDPNR/L
Kr:62°30'
A213

PDUNR/L
Kr:93°
A214

DN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Penetration insert		DNGA150404CE-2	CE	12.7	4.76	5.156	0.4	2.5			○									
		DNGA150408CE-2		12.7	4.76	5.156	0.8	2.1			○									
		DNGA150412CE-2		12.7	4.76	5.156	1.2	2.0			○									
		DNGA150604CE-2		12.7	6.35	5.156	0.4	2.5			○									
		DNGA150608CE-2		12.7	6.35	5.156	0.8	2.1			○									
		DNGA150612CE-2		12.7	6.35	5.156	1.2	2.0			○									
		DNGA150404CT01215-2	T01215	12.7	4.76	5.156	0.4	2.5			★									
		DNGA150408CT01215-2		12.7	4.76	5.156	0.8	2.1			★									
		DNGA150412CT01215-2		12.7	4.76	5.156	1.2	2.0			★									
		DNGA150604CT01215-2		12.7	6.35	5.156	0.4	2.5			★									
		DNGA150608CT01215-2		12.7	6.35	5.156	0.8	2.1			★									
		DNGA150612CT01215-2		12.7	6.35	5.156	1.2	2.0			★									
		DNGA150404CS01225-2	S01225	12.7	4.76	5.156	0.4	2.5			○									
		DNGA150408CS01225-2		12.7	4.76	5.156	0.8	2.1			○									
		DNGA150412CS01225-2		12.7	4.76	5.156	1.2	2.0			○									
		DNGA150604CS01225-2		12.7	6.35	5.156	0.4	2.5			○									
		DNGA150608CS01225-2		12.7	6.35	5.156	0.8	2.1			○									
		DNGA150612CS01225-2		12.7	6.35	5.156	1.2	2.0			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DDJNR/L
Kr:93°
Page A167

PDJNR/L
Kr:93°
A174

PDPNN
Kr:62°30'
A175

PDPNR/L
Kr:62°30'
A213

PDUNR/L
Kr:93°
A214

DN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		DNGN150404BE	BE	12.7	4.76	0.4			○									
		DNGN150408BE		12.7	4.76	0.8			○									
		DNGN150412BE		12.7	4.76	1.2			○									
		DNGN150604BE		12.7	6.35	0.4			○									
		DNGN150608BE		12.7	6.35	0.8			○									
		DNGN150612BE		12.7	6.35	1.2			○									
		DNGN150404BT01215	T01215	12.7	4.76	0.4			★									
		DNGN150408BT01215		12.7	4.76	0.8			★									
		DNGN150412BT01215		12.7	4.76	1.2			★									
		DNGN150604BT01215		12.7	6.35	0.4			★									
		DNGN150608BT01215		12.7	6.35	0.8			★									
		DNGN150612BT01215		12.7	6.35	1.2			★									
		DNGN150404BS01225	S01225	12.7	4.76	0.4			○									
		DNGN150408BS01225		12.7	4.76	0.8			○									
		DNGN150412BS01225		12.7	4.76	1.2			○									
		DNGN150604BS01225		12.7	6.35	0.4			○									
		DNGN150608BS01225		12.7	6.35	0.8			○									
		DNGN150612BS01225		12.7	6.35	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

SN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron
S	Heat resistant alloy, Ti alloy
H	Super hard material
N	Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		SNGA120404AE-2	AE	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		SNGA120408AE-2		12.7	4.76	5.156	0.8	2.2	○	○								○	○	○
		SNGA120412AE-2		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		SNGA120404AE-4		12.7	4.76	5.156	0.4	2.5										○	○	○
		SNGA120408AE-4		12.7	4.76	5.156	0.8	2.2										○	○	○
		SNGA120412AE-4		12.7	4.76	5.156	1.2	2.0										○	○	○
		SNGA120404AT01215-2	T01215	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		SNGA120408AT01215-2		12.7	4.76	5.156	0.8	2.2	○	○								○	○	○
		SNGA120412AT01215-2		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		SNGA120404AT01215-4		12.7	4.76	5.156	0.4	2.5										○	○	○
		SNGA120408AT01215-4		12.7	4.76	5.156	0.8	2.2										○	○	○
		SNGA120412AT01215-4		12.7	4.76	5.156	1.2	2.0										○	○	○
		SNGA120404AS01225-2	S01225	12.7	4.76	5.156	0.4	2.5	○	○								○	○	○
		SNGA120408AS01225-2		12.7	4.76	5.156	0.8	2.2	○	○								○	○	○
		SNGA120412AS01225-2		12.7	4.76	5.156	1.2	2.0	○	○								○	○	○
		SNGA120404AS01225-4		12.7	4.76	5.156	0.4	2.5					○	○	○	○	○	○	○	○
		SNGA120408AS01225-4		12.7	4.76	5.156	0.8	2.2					○	○	○	○	○	○	○	○
		SNGA120412AS01225-4		12.7	4.76	5.156	1.2	2.0					○	○	○	○	○	○	○	○
		SNGA120404AS00815-4	S00815	12.7	4.76	5.156	0.4	2.5					○	○	○					
		SNGA120408AS00815-4		12.7	4.76	5.156	0.8	2.2					○	○	○					
		SNGA120412AS00815-4		12.7	4.76	5.156	1.2	2.0					○	○	○					
		SNGA120404AS01735-4	S01735	12.7	4.76	5.156	0.4	2.5							○	○	○			
		SNGA120408AS01735-4		12.7	4.76	5.156	0.8	2.2							○	○	○			
		SNGA120412AS01735-4		12.7	4.76	5.156	1.2	2.0							○	○	○			

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DSBNR/L
Kr:75°
Page A168

PSBNR/L
Kr:75°
A176

PSDNN
Kr:45°
A177

PSKNR/L
Kr:75°
A178

PSSNR/L
Kr:45°
A179

PSKNR/L
Kr:75°
A215

SN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		SNGA120404DE-4	DE	12.7	4.76	5.156	0.4	2.5	○	○										
		SNGA120408DE-4		12.7	4.76	5.156	0.8	2.2	○	○										
		SNGA120412DE-4		12.7	4.76	5.156	1.2	2.0	○	○										
		SNGA120404DT01215-4	T01215	12.7	4.76	5.156	0.4	2.5	★	★										
		SNGA120408DT01215-4		12.7	4.76	5.156	0.8	2.2	★	★										
		SNGA120412DT01215-4		12.7	4.76	5.156	1.2	2.0	★	★										
		SNGA120404DS01225-4	S01225	12.7	4.76	5.156	0.4	2.5	○	○										
		SNGA120408DS01225-4		12.7	4.76	5.156	0.8	2.2	○	○										
		SNGA120412DS01225-4		12.7	4.76	5.156	1.2	2.0	○	○										
		SNGA120404DS01225-8		12.7	4.76	5.156	0.4	2.5					○	○	○	○	○			
		SNGA120408DS01225-8		12.7	4.76	5.156	0.8	2.2					○	○	○	○	○			
		SNGA120412DS01225-8		12.7	4.76	5.156	1.2	2.0					○	○	○	○	○			
		SNGA120404DS00815-8	S00815	12.7	4.76	5.156	0.4	2.5					○	○	○					
		SNGA120408DS00815-8		12.7	4.76	5.156	0.8	2.2					○	○	○					
		SNGA120412DS00815-8		12.7	4.76	5.156	1.2	2.0					○	○	○					
		SNGA120404DS01735-8	S01735	12.7	4.76	5.156	0.4	2.5							○	○	○			
		SNGA120408DS01735-8		12.7	4.76	5.156	0.8	2.2							○	○	○			
		SNGA120412DS01735-8		12.7	4.76	5.156	1.2	2.0							○	○	○			

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DSBNR/L Kr:75°
Page A168

PSBNR/L Kr:75°
A176

PSDNN Kr:45°
A177

PSKNR/L Kr:75°
A178

PSSNR/L Kr:45°
A179

PSKNR/L Kr:75°
A215

SN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron	😊	😊	😐	☹															
S	Heat resistant alloy, Ti alloy																	😊	😐	☹
H	Super hard material					😊	😊	😐	☹	☹										
N	Non ferrous metal																			

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Penetration insert		SNGA120404CE-2	CE	12.7	4.76	5.156	0.4	2.5			○									
		SNGA120408CE-2		12.7	4.76	5.156	0.8	2.2			○									
		SNGA120412CE-2		12.7	4.76	5.156	1.2	2.0			○									
		SNGA120404CE-4		12.7	4.76	5.156	0.4	2.5			○									
		SNGA120408CE-4		12.7	4.76	5.156	0.8	2.2			○									
		SNGA120412CE-4		12.7	4.76	5.156	1.2	2.0			○									
		SNGA120404CT01215-4	T01215	12.7	4.76	5.156	0.4	2.5			★									
		SNGA120408CT01215-4		12.7	4.76	5.156	0.8	2.2			★									
		SNGA120412CT01215-4		12.7	4.76	5.156	1.2	2.0			★									
		SNGA120404CT01215-2		12.7	4.76	5.156	0.4	2.5			★									
		SNGA120408CT01215-2		12.7	4.76	5.156	0.8	2.2			★									
		SNGA120412CT01215-2		12.7	4.76	5.156	1.2	2.0			★									
		SNGA120404CS01225-4	S01225	12.7	4.76	5.156	0.4	2.5			○									
		SNGA120408CS01225-4		12.7	4.76	5.156	0.8	2.2			○									
		SNGA120412CS01225-4		12.7	4.76	5.156	1.2	2.0			○									
		SNGA120404CS01225-2		12.7	4.76	5.156	0.4	2.5			○									
		SNGA120408CS01225-2		12.7	4.76	5.156	0.8	2.2			○									
		SNGA120412CS01225-2		12.7	4.76	5.156	1.2	2.0			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DSBNR/L Kr:75°
Page A168

PSBNR/L Kr:75°
A176

PSDNN Kr:45°
A177

PSKNR/L Kr:75°
A178

PSSNR/L Kr:45°
A179

PSKNR/L Kr:75°
A215

SN□□ (Negative angle)



Good working condition 😊 Normal working condition 😐 Bad working condition 😞

Workpiece material		Cast iron	Heat resistant alloy, Ti alloy	Super hard material	Non ferrous metal
		K	S	H	N

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		**SNGN120404BE**	**BE**	12.7	4.76	0.4			○									
		SNGN120408BE		12.7	4.76	0.8			○									
		SNGN120412BE		12.7	4.76	1.2			○									
		SNGN120404BT01215	**T01215**	12.7	4.76	0.4			★									
		SNGN120408BT01215		12.7	4.76	0.8			★									
		SNGN120412BT01215		12.7	4.76	1.2			★									
		SNGN120404BS01225	**S01225**	12.7	4.76	0.4			○									
		SNGN120408BS01225		12.7	4.76	0.8			○									
		SNGN120412BS01225		12.7	4.76	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

TN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		TNGA160404AE-3	AE	9.525	4.76	3.81	0.4	2.5	○	○								○	○	○
		TNGA160408AE-3		9.525	4.76	3.81	0.8	2.2	○	○								○	○	○
		TNGA160412AE-3		9.525	4.76	3.81	1.2	2.0	○	○								○	○	○
		TNGA160404AT01215-3	T01215	9.525	4.76	3.81	0.4	2.5	○	○								○	○	○
		TNGA160408AT01215-3		9.525	4.76	3.81	0.8	2.2	○	○								○	○	○
		TNGA160412AT01215-3		9.525	4.76	3.81	1.2	2.0	○	○								○	○	○
		TNGA160404AS01225-3	S01225	9.525	4.76	3.81	0.4	2.5	○	○			○	○	○	○	○	○	○	○
		TNGA160408AS01225-3		9.525	4.76	3.81	0.8	2.2	○	○			○	○	○	○	○	○	○	○
		TNGA160412AS01225-3		9.525	4.76	3.81	1.2	2.0	○	○			○	○	○	○	○	○	○	○
		TNGA160404AS00815-3	S00815	9.525	4.76	3.81	0.4	2.5					○	○	○					
		TNGA160408AS00815-3		9.525	4.76	3.81	0.8	2.2					○	○	○					
		TNGA160412AS00815-3		9.525	4.76	3.81	1.2	2.0					○	○	○					
		TNGA160404AS01735-3	S01735	9.525	4.76	3.81	0.4	2.5							○	○	○			
		TNGA160408AS01735-3		9.525	4.76	3.81	0.8	2.2							○	○	○			
		TNGA160412AS01735-3		9.525	4.76	3.81	1.2	2.0							○	○	○			
Double-sided insert		TNGA160404DE-6	DE	9.525	4.76	3.81	0.4	2.5	○	○								○	○	○
		TNGA160408DE-6		9.525	4.76	3.81	0.8	2.2	○	○								○	○	○
		TNGA160412DE-6		9.525	4.76	3.81	1.2	2.0	○	○								○	○	○
		TNGA160404DT01215-6	T01215	9.525	4.76	3.81	0.4	2.5	★	★								★	★	★
		TNGA160408DT01215-6		9.525	4.76	3.81	0.8	2.2	★	★								★	★	★
		TNGA160412DT01215-6		9.525	4.76	3.81	1.2	2.0	★	★								★	★	★

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DTGNR/L Kr:90°
Page A169

PTFNR/L Kr:90°
A180

PTTNR/L Kr:60°
A181

PTGNR/L Kr:90°
A182

PTFNR/L Kr:90°
A216

TN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		TNGA160404DS01225-6	S01225	9.525	4.76	3.81	0.4	2.5	○	○			★	★	★	★	★	○	○	○
		TNGA160408DS01225-6		9.525	4.76	3.81	0.8	2.2	○	○			★	★	★	★	★	○	○	○
		TNGA160412DS01225-6		9.525	4.76	3.81	1.2	2.0	○	○			★	★	★	★	★	○	○	○
		TNGA160404DS00815-6	S00815	9.525	4.76	3.81	0.4	2.5					★	★	○					
		TNGA160408DS00815-6		9.525	4.76	3.81	0.8	2.2					★	★	○					
		TNGA160412DS00815-6		9.525	4.76	3.81	1.2	2.0					★	★	○					
		TNGA160404DS01735-6	S01735	9.525	4.76	3.81	0.4	2.5							○	★	○			
		TNGA160408DS01735-6		9.525	4.76	3.81	0.8	2.2							○	★	○			
		TNGA160412DS01735-6		9.525	4.76	3.81	1.2	2.0							○	★	○			
Penetration insert		TNGA160404CE-3	CE	9.525	4.76	3.81	0.4	2.5			○									
		TNGA160408CE-3		9.525	4.76	3.81	0.8	2.2			○									
		TNGA160412CE-3		9.525	4.76	3.81	1.2	2.0			○									
		TNGA160404CT01215-3	T01215	9.525	4.76	3.81	0.4	2.5			★									
		TNGA160408CT01215-3		9.525	4.76	3.81	0.8	2.2			★									
		TNGA160412CT01215-3		9.525	4.76	3.81	1.2	2.0			★									
		TNGA160404CS01225-3	S01225	9.525	4.76	3.81	0.4	2.5			○									
		TNGA160408CS01225-3		9.525	4.76	3.81	0.8	2.2			○									
		TNGA160412CS01225-3		9.525	4.76	3.81	1.2	2.0			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DTGNR/L Kr:90°
Page A169

PTFNR/L Kr:90°
A180

PTTNR/L Kr:60°
A181

PTGNR/L Kr:90°
A182

PTFNR/L Kr:90°
A216

TN□□ (Negative angle)



Good working condition 😊 Normal working condition 😐 Bad working condition 😞

Workpiece material		
K	Cast iron	😊 😊 😐 😞
S	Heat resistant alloy, Ti alloy	😊 😐 😞
H	Super hard material	😊 😊 😐 😞 😞
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		TNGN160404BE	BE	9.525	4.76	0.4			○									
		TNGN160408BE		9.525	4.76	0.8			○									
		TNGN160412BE		9.525	4.76	1.2			○									
		TNGN160404BT01215	T01215	9.525	4.76	0.4			★									
		TNGN160408BT01215		9.525	4.76	0.8			★									
		TNGN160412BT01215		9.525	4.76	1.2			★									
		TNGN160404BS01225	S01225	9.525	4.76	0.4			○									
		TNGN160408BS01225		9.525	4.76	0.8			○									
		TNGN160412BS01225		9.525	4.76	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

VN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		VNGA160404AE-2	AE	9.525	4.76	3.81	0.4	2.8										○	○	○
		VNGA160408AE-2		9.525	4.76	3.81	0.8	2.5										○	○	○
		VNGA160412AE-2		9.525	4.76	3.81	1.2	2.0										○	○	○
		VNGA160404AT01215-2	T01215	9.525	4.76	3.81	0.4	2.8										○	○	○
		VNGA160408AT01215-2		9.525	4.76	3.81	0.8	2.5										○	○	○
		VNGA160412AT01215-2		9.525	4.76	3.81	1.2	2.0										○	○	○
		VNGA160404AS01225-2	S01225	9.525	4.76	3.81	0.4	2.8					○	○	○	○	○	○	○	○
		VNGA160408AS01225-2		9.525	4.76	3.81	0.8	2.5					○	○	○	○	○	○	○	○
		VNGA160412AS01225-2		9.525	4.76	3.81	1.2	2.0					○	○	○	○	○	○	○	○
		VNGA160404AS00815-2	S00815	9.525	4.76	3.81	0.4	2.8					○	○	○					
		VNGA160408AS00815-2		9.525	4.76	3.81	0.8	2.5					○	○	○					
		VNGA160412AS00815-2		9.525	4.76	3.81	1.2	2.0					○	○	○					
		VNGA160404AS01735-2	S01735	9.525	4.76	3.81	0.4	2.8							○	○	○			
		VNGA160408AS01735-2		9.525	4.76	3.81	0.8	2.5							○	○	○			
		VNGA160412AS01735-2		9.525	4.76	3.81	1.2	2.0							○	○	○			
Double-sided insert		VNGA160404DE-4	DE	9.525	4.76	3.81	0.4	2.8										○	○	○
		VNGA160408DE-4		9.525	4.76	3.81	0.8	2.5										○	○	○
		VNGA160412DE-4		9.525	4.76	3.81	1.2	2.0										○	○	○
		VNGA160404DT01215-4	T01215	9.525	4.76	3.81	0.4	2.8										★	★	★
		VNGA160408DT01215-4		9.525	4.76	3.81	0.8	2.5										★	★	★
		VNGA160412DT01215-4		9.525	4.76	3.81	1.2	2.0										★	★	★

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DVVNN Kr:72°30'

Page A170

DVJNR/L Kr:93°

A170

VN□□ (Negative angle)



Good working condition | Normal working condition | Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		VNGA160404DS01225-4	S01225	9.525	4.76	3.81	0.4	2.8					★	★	★	★	★	○	○	○
		VNGA160408DS01225-4		9.525	4.76	3.81	0.8	2.5					★	★	★	★	★	○	○	○
		VNGA160412DS01225-4		9.525	4.76	3.81	1.2	2.0					★	★	★	★	★	○	○	○
		VNGA160404DS00815-4	S00815	9.525	4.76	3.81	0.4	2.8					★	★	○					
		VNGA160408DS00815-4		9.525	4.76	3.81	0.8	2.5					★	★	○					
		VNGA160412DS00815-4		9.525	4.76	3.81	1.2	2.0					★	★	○					
		VNGA160404DS01735-4	S01735	9.525	4.76	3.81	0.4	2.8							○	★	○			
		VNGA160408DS01735-4		9.525	4.76	3.81	0.8	2.5							○	★	○			
		VNGA160412DS01735-4		9.525	4.76	3.81	1.2	2.0							○	★	○			
Penetration insert		VNGA160402CE-2	CE	9.525	4.76	3.81	0.2	3.3			○									
		VNGN160404CE-2		9.525	4.76	3.81	0.4	2.8			○									
		VNGN160408CE-2		9.525	4.76	3.81	0.8	2.5												
		VNGN160412CE-2		9.525	4.76	3.81	1.2	2.0			○									
		VNGA160402CT01215-2	T01215	9.525	4.76	3.81	0.2	3.3			★									
		VNGN160404CT01215-2		9.525	4.76	3.81	0.4	2.8			★									
		VNGN160408CT01215-2		9.525	4.76	3.81	0.8	2.5			★									
		VNGN160412CT01215-2		9.525	4.76	3.81	1.2	2.0			★									
		VNGA160402CS01225-2	S01225	9.525	4.76	3.81	0.2	3.3			○									
		VNGN160404CS01225-2		9.525	4.76	3.81	0.4	2.8			○									
		VNGN160408CS01225-2		9.525	4.76	3.81	0.8	2.5												
		VNGN160412CS01225-2		9.525	4.76	3.81	1.2	2.0			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DVVNN
Kr:72°30'

Page A170

DVJNR/L
Kr:93°

A170

VN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		VNGN160402BE	BE	9.525	4.76	0.4			○									
		VNGN160404BE		9.525	4.76	0.4			○									
		VNGN160408BE		9.525	4.76	0.8												
		VNGN160412BE		9.525	4.76	1.2			○									
		VNGN160402BT01215	T01215	9.525	4.76	0.4			★									
		VNGN160404BT01215		9.525	4.76	0.4			★									
		VNGN160408BT01215		9.525	4.76	0.8			★									
		VNGN160412BT01215		9.525	4.76	1.2			★									
		VNGN160402BS01225	S01225	9.525	4.76	0.4			○									
		VNGN160404BS01225		9.525	4.76	0.4			○									
		VNGN160408BS01225		9.525	4.76	0.8												
		VNGN160412BS01225		9.525	4.76	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

WN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Single-sided insert		WNGA080404AE-3	AE	12.7	4.76	5.16	0.4	2.5										○	○	○
		WNGA080408AE-3		12.7	4.76	5.16	0.8	2.4										○	○	○
		WNGA080412AE-3		12.7	4.76	5.16	1.2	2.3										○	○	○
		WNGA080404AT01215-3	T01215	12.7	4.76	5.16	0.4	2.5										○	○	○
		WNGA080408AT01215-3		12.7	4.76	5.16	0.8	2.4										○	○	○
		WNGA080412AT01215-3		12.7	4.76	5.16	1.2	2.3										○	○	○
		WNGA080404AS01225-3	S01225	12.7	4.76	5.16	0.4	2.5					○	○	○	○	○	○	○	○
		WNGA080408AS01225-3		12.7	4.76	5.16	0.8	2.4					○	○	○	○	○	○	○	○
		WNGA080412AS01225-3		12.7	4.76	5.16	1.2	2.3					○	○	○	○	○	○	○	○
		WNGA080404AS00815-3	S00815	12.7	4.76	5.16	0.4	2.5					○	○	○					
		WNGA080408AS00815-3		12.7	4.76	5.16	0.8	2.4					○	○	○					
		WNGA080412AS00815-3		12.7	4.76	5.16	1.2	2.3					○	○	○					
		WNGA080404AS01735-3	S01735	12.7	4.76	5.16	0.4	2.5							○	○	○			
		WNGA080408AS01735-3		12.7	4.76	5.16	0.8	2.4							○	○	○			
		WNGA080412AS01735-3		12.7	4.76	5.16	1.2	2.3							○	○	○			
Double-sided insert		WNGA080404DE-6	DE	12.7	4.76	5.16	0.4	2.5	○	○										
		WNGA080408DE-6		12.7	4.76	5.16	0.8	2.4	○	○										
		WNGA080412DE-6		12.7	4.76	5.16	1.2	2.3	○	○										
		WNGA080404DT01215-6	T01215	12.7	4.76	5.16	0.4	2.5	★	★										
		WNGA080408DT01215-6		12.7	4.76	5.16	0.8	2.4	★	★										
		WNGA080412DT01215-6		12.7	4.76	5.16	1.2	2.3	★	★										

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DWLNR/L
Kr:95°
Page A171

PWLNR/L
Kr:95°
A183

PWLNR/L
Kr:95°
A217

WN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material:
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Double-sided insert		WNGA080404DS01225-6		12.7	4.76	5.16	0.4	2.5	○	○										
		WNGA080408DS01225-6	S01225	12.7	4.76	5.16	0.8	2.4	○	○										
		WNGA080412DS01225-6		12.7	4.76	5.16	1.2	2.3	○	○										
		WNGA080404DS00815-6		12.7	4.76	3.81	0.4	2.5					★	★	○					
		WNGA080408DS00815-6	S00815	12.7	4.76	3.81	0.8	2.2					★	★	○					
		WNGA080412DS00815-6		12.7	4.76	3.81	1.2	2.0					★	★	○					
		WNGA080404DS01225-6		12.7	4.76	3.81	0.4	2.5					★	★	★	★	★			
		WNGA080408DS01225-6	S01225	12.7	4.76	3.81	0.8	2.2					★	★	★	★	★			
		WNGA080412DS01225-6		12.7	4.76	3.81	1.2	2.0					★	★	★	★	★			
		WNGA080404DS01735-6		12.7	4.76	3.81	0.4	2.5							○	★	○			
		WNGA080408DS01735-6	S01735	12.7	4.76	3.81	0.8	2.2							○	★	○			
		WNGA080412DS01735-6		12.7	4.76	3.81	1.2	2.0							○	★	○			
Penetration insert		WNGA080404CE-3		12.7	4.76	5.16	0.4	2.5			○									
		WNGN080408CE-3	CE	12.7	4.76	5.16	0.8	2.4			○									
		WNGN080412CE-3		12.7	4.76	5.16	1.2	2.3			○									
		WNGA080404CT01215-3		12.7	4.76	5.16	0.4	2.5			★									
		WNGN080408CT01215-3	T01215	12.7	4.76	5.16	0.8	2.4			★									
		WNGN080412CT01215-3		12.7	4.76	5.16	1.2	2.3			★									
		WNGA080404CS01225-3		12.7	4.76	5.16	0.4	2.5			○									
		WNGN080408CS01225-3	S01225	12.7	4.76	5.16	0.8	2.4			○									
		WNGN080412CS01225-3		12.7	4.76	5.16	1.2	2.3			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

DWLNR/L Kr:95°
Page A171

PWLNR/L Kr:95°
A183

PWLNR/L Kr:95°
A217

WN□□ (Negative angle)



Good working condition Normal working condition Bad working condition

Workpiece material

		Cast iron	Heat resistant alloy, Ti alloy	Super hard material	Non ferrous metal
K	Cast iron	😊	😊	😐	☹
S	Heat resistant alloy, Ti alloy				😊 😐 ☹
H	Super hard material			😊 😊 😐 ☹ ☹	
N	Non ferrous metal				

Type	Shape of insert	Model	Specifi-cation	Dimension(mm)			Cast iron				Hardened steel					Powder alloy& Superalloy		
				ØI.C	S	r	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
Intact insert		**WNGN080404BE**	**BE**	12.7	4.76	0.4			○									
		WNGN080408BE		12.7	4.76	0.8			○									
		WNGN080412BE		12.7	4.76	1.2			○									
		WNGN080404BT01215	**T01215**	12.7	4.76	0.4			★									
		WNGN080408BT01215		12.7	4.76	0.8			★									
		WNGN080412BT01215		12.7	4.76	1.2			★									
		WNGN080404BS01225	**S01225**	12.7	4.76	0.4			○									
		WNGN080408BS01225		12.7	4.76	0.8			○									
		WNGN080412BS01225		12.7	4.76	1.2			○									

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

CC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material
- K Cast iron
- S Heat resistant alloy, Ti alloy
- H Super hard material
- N Non ferrous metal

Insert shape	Sepcification	Dimsension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
		ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
	CCGW060202AE-2	6.35	2.38	2.8	0.2	2.5	○	○								○	○	○
	CCGW060204AE-2	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	CCGW060208AE-2	6.35	2.38	2.8	0.8	2.4	○	○								○	○	○
	CCGW060202AS01225-2	6.35	2.38	2.8	0.2	2.5					○	○	○	○		○	○	○
	CCGW060204AS01225-2	6.35	2.38	2.8	0.4	2.5					○	○	○	○		○	○	○
	CCGW060208AS01225-2	6.35	2.38	2.8	0.8	2.4					○	○	○	○		○	○	○
	CCGW060202AT01225-2	6.35	2.38	2.8	0.2	2.5	○	○								○	○	○
	CCGW060204AT01225-2	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	CCGW060208AT01225-2	6.35	2.38	2.8	0.8	2.4	○	○								○	○	○
	CCGW09T302AE-2	9.525	3.97	4.4	0.2	2.5	○	○								○	○	○
	CCGW09T304AE-2	9.525	3.97	4.4	0.4	2.5	○	○								○	○	○
	CCGW09T308AE-2	9.525	3.97	4.4	0.8	2.4	○	○								○	○	○
	CCGW09T302AS01225-2	9.525	3.97	4.4	0.2	2.5					○	○	○	○		○	○	○
	CCGW09T304AS01225-2	9.525	3.97	4.4	0.4	2.5					○	○	○	○		○	○	○
	CCGW09T308AS01225-2	9.525	3.97	4.4	0.8	2.4					○	○	○	○		○	○	○
	CCGW09T302AT01225-2	9.525	3.97	4.4	0.2	2.5	○	○								○	○	○
	CCGW09T304AT01225-2	9.525	3.97	4.4	0.4	2.5	○	○								○	○	○
	CCGW09T308AT01225-2	9.525	3.97	4.4	0.8	2.4	○	○								○	○	○
	CCGW120402AE-2	12.7	4.76	5.5	0.2	2.5	○	○								○	○	○
	CCGW120404AE-2	12.7	4.76	5.5	0.4	2.5	○	○								○	○	○
	CCGW120408AE-2	12.7	4.76	5.5	0.8	2.4	○	○								○	○	○
	CCGW120402AS01225-2	12.7	4.76	5.5	0.2	2.5					○	○	○	○		○	○	○
	CCGW120404AS01225-2	12.7	4.76	5.5	0.4	2.5					○	○	○	○		○	○	○
	CCGW120408AS01225-2	12.7	4.76	5.5	0.8	2.4					○	○	○	○		○	○	○
	CCGW120402AT01225-2	12.7	4.76	5.5	0.2	2.5	○	○								○	○	○
	CCGW120404AT01225-2	12.7	4.76	5.5	0.4	2.5	○	○								○	○	○
	CCGW120408AT01225-2	12.7	4.76	5.5	0.8	2.4	○	○								○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SCACR/L Kr:90°
Page A184

SCLCR/L Kr:95°
A185

SCLCR/L Kr:95°
A218

SCFCR/L Kr:90°
A232

SCLCR/L Kr:95°
A233

DC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron
S	Heat resistant alloy, Ti alloy
H	Super hard material
N	Non ferrous metal

Insert shape	Sepcification	Dimsension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
		ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
	DCGW070202AE-2	6.35	2.38	2.8	0.2	2.7	○	○								○	○	○
	DCGW070204AE-2	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	DCGW070208AE-2	6.35	2.38	2.8	0.8	2.1	○	○								○	○	○
	DCGW070202AS01225-2	6.35	2.38	2.8	0.2	2.7					○	○	○	○		○	○	○
	DCGW070204AS01225-2	6.35	2.38	2.8	0.4	2.5					○	○	○	○		○	○	○
	DCGW070208AS01225-2	6.35	2.38	2.8	0.8	2.1					○	○	○	○		○	○	○
	DCGW070202AT01225-2	6.35	2.38	2.8	0.2	2.7	○	○								○	○	○
	DCGW070204AT01225-2	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	DCGW070208AT01225-2	6.35	2.38	2.8	0.8	2.1	○	○								○	○	○
	DCGW11T302AE-2	9.525	3.97	4.4	0.2	2.7	○	○								○	○	○
	DCGW11T304AE-2	9.525	3.97	4.4	0.4	2.5	○	○								○	○	○
	DCGW11T308AE-2	9.525	3.97	4.4	0.8	2.1	○	○								○	○	○
	DCGW11T302AS01225-2	9.525	3.97	4.4	0.2	2.7					○	○	○	○		○	○	○
	DCGW11T304AS01225-2	9.525	3.97	4.4	0.4	2.5					○	○	○	○		○	○	○
	DCGW11T308AS01225-2	9.525	3.97	4.4	0.8	2.1					○	○	○	○		○	○	○
	DCGW11T302AT01225-2	9.525	3.97	4.4	0.2	2.7	○	○								○	○	○
	DCGW11T304AT01225-2	9.525	3.97	4.4	0.4	2.5	○	○								○	○	○
	DCGW11T308AT01225-2	9.525	3.97	4.4	0.8	2.1	○	○								○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SDACR/L
Kr:90°
Page A186

SDJCR/L
Kr:93°
A187

SDNCN
Kr:62°30'
A188

SDQCR/L
Kr:107°30'
A219

SDUCR/L
Kr:93°
A220

SDZCR/L
Kr:95°
A221

TC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron
S	Heat resistant alloy, Ti alloy
H	Super hard material
N	Non ferrous metal

Insert shape	Sepcification	Dimsension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
		ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
	TCGW090202AE-3	5.56	2.38	2.5	0.2	2.5	○	○								○	○	○
	TCGW090204AE-3	5.56	2.38	2.5	0.4	2.5	○	○								○	○	○
	TCGW090208AE-3	5.56	2.38	2.5	0.8	2.2	○	○								○	○	○
	TCGW090202AS01225-3	5.56	2.38	2.5	0.2	2.5					○	○	○	○		○	○	○
	TCGW090204AS01225-3	5.56	2.38	2.5	0.4	2.5					○	○	○	○		○	○	○
	TCGW090208AS01225-3	5.56	2.38	2.5	0.8	2.2					○	○	○	○		○	○	○
	TCGW090202AT01225-3	5.56	2.38	2.5	0.2	2.5	○	○								○	○	○
	TCGW090204AT01225-3	5.56	2.38	2.5	0.4	2.5	○	○								○	○	○
	TCGW090208AT01225-3	5.56	2.38	2.5	0.8	2.2	○	○								○	○	○
	TCGW110202AE-3	6.35	2.38	2.8	0.2	2.5	○	○								○	○	○
	TCGW110204AE-3	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	TCGW110208AE-3	6.35	2.38	2.8	0.8	2.2	○	○								○	○	○
	TCGW110202AS01225-3	6.35	2.38	2.8	0.2	2.5					○	○	○	○		○	○	○
	TCGW110204AS01225-3	6.35	2.38	2.8	0.4	2.5					○	○	○	○		○	○	○
	TCGW110208AS01225-3	6.35	2.38	2.8	0.8	2.2					○	○	○	○		○	○	○
	TCGW110202AT01225-3	6.35	2.38	2.8	0.2	2.5	○	○								○	○	○
	TCGW110204AT01225-3	6.35	2.38	2.8	0.4	2.5	○	○								○	○	○
	TCGW110208AT01225-3	6.35	2.38	2.8	0.8	2.2	○	○								○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

STACR/L
Kr:90°
Page A198

STFCR/L
Kr:90°
A198

STGCR/L
Kr:91°
A199

STECR/L
Kr:60°
A200

STFCR/L
Kr:90°
A223

VB□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	😊 😊 😐 ☹
S	Heat resistant alloy, Ti alloy	😊 😐 ☹
H	Super hard material	😊 😊 😐 ☹ ☹
N	Non ferrous metal	

Insert shape	Sepcification	Dimsension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
		ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
	VBGW160402AE-2	9.525	4.76	4.4	0.2	3.3	○	○								○	○	○
	VBGW160404AE-2	9.525	4.76	4.4	0.4	2.8	○	○								○	○	○
	VBGW160408AE-2	9.525	4.76	4.4	0.8	2.5	○	○								○	○	○
	VBGW160402AS01225-2	9.525	4.76	4.4	0.2	3.3					○	○	○	○		○	○	○
	VBGW160404AS01225-2	9.525	4.76	4.4	0.4	2.8					○	○	○	○		○	○	○
	VBGW160408AS01225-2	9.525	4.76	4.4	0.8	2.5					○	○	○	○		○	○	○
	VBGW160402AT01225-2	9.525	4.76	4.4	0.2	3.3	○	○								○	○	○
	VBGW160404AT01225-2	9.525	4.76	4.4	0.4	2.8	○	○								○	○	○
	VBGW160408AT01225-2	9.525	4.76	4.4	0.8	2.5	○	○								○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SVJBR/L
Kr:93°
Page A189

SVABR/L
Kr:90°
A190

SVVBN
Kr:72°30'
A191

SVQBR/L
Kr:107°30'
A226

SVUBR/L
Kr:93°
A227

VC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material

K	Cast iron
S	Heat resistant alloy, Ti alloy
H	Super hard material
N	Non ferrous metal

Insert shape	Sepcification	Dimsension(mm)					Cast iron				Hardened steel					Powder alloy& Superalloy		
		ØI.C	S	ød	r	L	BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
	VCGW160402AE-2	9.525	4.76	4.4	0.2	3.3	○	○								○	○	○
	VCGW160404AE-2	9.525	4.76	4.4	0.4	2.8	○	○								○	○	○
	VCGW160408AE-2	9.525	4.76	4.4	0.8	2.5	○	○								○	○	○
	VCGW160402AS01225-2	9.525	4.76	4.4	0.2	3.3					○	○	○	○		○	○	○
	VCGW160404AS01225-2	9.525	4.76	4.4	0.4	2.8					○	○	○	○		○	○	○
	VCGW160408AS01225-2	9.525	4.76	4.4	0.8	2.5					○	○	○	○		○	○	○
	VCGW160402AT01225-2	9.525	4.76	4.4	0.2	3.3	○	○								○	○	○
	VCGW160404AT01225-2	9.525	4.76	4.4	0.4	2.8	○	○								○	○	○
	VCGW160408AT01225-2	9.525	4.76	4.4	0.8	2.5	○	○								○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

When using PCBN blades, please try to keep the cutting depth below. 0.5mm.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SVVCN
Kr:72°30'
Page A192

SVJCR/L
Kr:93°
A193

SVQCR/L
Kr:107°30'
A224

SVUCR/L
Kr:93°
A225

CC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material					
K	Cast iron				
S	Heat resistant alloy, Ti alloy				
H	Super hard material				
N	Non ferrous metal	☺	☺	😐	☹

Type	Shape	Specification	Dimension(mm)					Grade			
			ØI.C	S	ød	r	L	DN0121	DN0511	DN1021	DN3021
0° rake angle		CCGW060202AF	6.35	2.38	2.8	0.2	2.6	○	○	○	○
		CCGW060204AF	6.35	2.38	2.8	0.4	2.5	★	★	★	★
		CCGW060208AF	6.35	2.38	2.8	0.8	2.4	○	○	○	○
		CCGW09T302AF	9.525	3.97	4.4	0.2	2.6	○	○	○	○
		CCGW09T304AF	9.525	3.97	4.4	0.4	2.5	○	○	○	○
		CCGW09T308AF	9.525	3.97	4.4	0.8	2.4	★	★	★	★
		CCGW120402AF	12.7	4.76	5.5	0.2	2.6	○	○	○	○
		CCGW120404AF	12.7	4.76	5.5	0.4	2.5	○	○	○	○
		CCGW120408AF	12.7	4.76	5.5	0.8	2.4	★	★	★	★
7° rake angle		CCMX060202AF	6.35	2.38	2.8	0.2	2.6	○	○	○	○
		CCMX060204AF	6.35	2.38	2.8	0.4	2.5	○	○	○	○
		CCMX060208AF	6.35	2.38	2.8	0.8	2.4	○	○	○	○
		CCMX09T302AF	9.525	3.97	4.4	0.2	2.6	○	○	○	○
		CCMX09T304AF	9.525	3.97	4.4	0.4	2.5	○	○	○	○
		CCMX09T308AF	9.525	3.97	4.4	0.8	2.4	○	○	○	○
		CCMX120402AF	12.7	4.76	5.5	0.2	2.6	○	○	○	○
		CCMX120404AF	12.7	4.76	5.5	0.4	2.5	○	○	○	○
		CCMX120408AF	12.7	4.76	5.5	0.8	2.4	○	○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SCACR/L
Kr:90°
Page A184

SCLCR/L
Kr:95°
A185

SCLCR/L
Kr:95°
A218

SCFCR/L
Kr:90°
A232

SCLCR/L
Kr:95°
A233

DC□□ (Positive angle)



Good working condition Normal working condition Bad working condition

Workpiece material					
K	Cast iron				
S	Heat resistant alloy, Ti alloy				
H	Super hard material				
N	Non ferrous metal	😊	😊	😐	☹

Type	Shape	Specification	Dimension(mm)					Grade			
			ØI.C	S	ød	r	L	DN0121	DN0511	DN1021	DN3021
0° rake angle		**DCGW070202AF**	6.35	2.38	2.8	0.2	2.7	○	○	○	○
		DCGW070204AF	6.35	2.38	2.8	0.4	2.5	○	○	○	○
		DCGW070208AF	6.35	2.38	2.8	0.8	2.1	★	★	★	★
		DCGW11T302AF	9.525	3.97	4.4	0.2	2.7	○	○	○	○
		DCGW11T304AF	9.525	3.97	4.4	0.4	2.5	○	○	○	○
		DCGW11T308AF	9.525	3.97	4.4	0.8	2.1	★	★	★	★
7° rake angle		**DCMX070202AF**	6.35	2.38	2.8	0.2	2.7	○	○	○	○
		DCMX070204AF	6.35	2.38	2.8	0.4	2.5	○	○	○	○
		DCMX070208AF	6.35	2.38	2.8	0.8	2.1	○	○	○	○
		DCMX11T302AF	9.525	3.97	4.4	0.2	2.7	○	○	○	○
		DCMX11T304AF	9.525	3.97	4.4	0.4	2.5	○	○	○	○
		DCMX11T308AF	9.525	3.97	4.4	0.8	2.1	○	○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SDACR/L Kr:90°
Page A186

SDJCR/L Kr:93°
A187

SDNCN Kr:62°30'
A188

SDQCR/L Kr:107°30'
A219

SDUCR/L Kr:93°
A220

SDZCR/L Kr:95°
A221

TC□□ (Positive inserts)



😊 Good working condition 😐 Normal working condition ☹ Bad working condition

Workpiece material					
K	Cast iron				
S	Heat resistant alloy, Ti alloy				
H	Super hard material				
N	Non ferrous metal	😊	😊	😐	☹

Type	Shape	Specification	Dimension(mm)					Grade			
			ØI.C	S	ød	r	L	DN0121	DN0511	DN1021	DN3021
0° rake angle		**TCGW090202AF**	5.56	2.38	2.5	0.2	2.5	○	○	○	○
		TCGW090204AF	5.56	2.38	2.5	0.4	2.5	○	○	○	○
		TCGW090208AF	5.56	2.38	2.5	0.8	2.2	★	★	★	★
		TCGW110202AF	6.35	2.38	2.8	0.2	2.5	○	○	○	○
		TCGW110204AF	6.35	2.38	2.8	0.4	2.5	○	○	○	○
		TCGW110208AF	6.35	2.38	2.8	0.8	2.2	★	★	★	★
7° rake angle		**TCMX090202AF**	5.56	2.38	2.5	0.2	2.5	○	○	○	○
		TCMX090204AF	5.56	2.38	2.5	0.4	2.5	○	○	○	○
		TCMX090208AF	5.56	2.38	2.5	0.8	2.2	○	○	○	○
		TCMX110202AF	6.35	2.38	2.8	0.2	2.5	○	○	○	○
		TCMX110204AF	6.35	2.38	2.8	0.4	2.5	○	○	○	○
		TCMX110208AF	6.35	2.38	2.8	0.8	2.2	○	○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

STACR/L Kr:90°
Page A198

STFCR/L Kr:90°
A198

STGCR/L Kr:91°
A199

STECR/L Kr:60°
A200

STFCR/L Kr:90°
A223

VB□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material					
K	Cast iron				
S	Heat resistant alloy, Ti alloy				
H	Super hard material				
N	Non ferrous metal	😊	😊	😐	☹

Type	Shape	Specification	Dimension(mm)					Grade			
			ØI.C	S	ød	r	L	DN0121	DN0511	DN1021	DN3021
0° rake angle		**VBGW160402AF**	9.525	4.76	4.4	0.2	3.3	○	○	○	○
		VBGW160404AF	9.525	4.76	4.4	0.4	2.8	○	○	○	○
		VBGW160408AF	9.525	4.76	4.4	0.8	2.5	★	★	★	★
5° rake angl		**VBMX160402AF**	9.525	4.76	4.4	0.2	3.3	○	○	○	○
		VBMX160404AF	9.525	4.76	4.4	0.4	2.8	○	○	○	○
		VBMX160408AF	9.525	4.76	4.4	0.8	2.5	○	○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SVJBR/L Kr:93°
Page A189

SVABR/L Kr:90°
A190

SVVBN Kr:72°30'
A191

SVQBR/L Kr:107°30'
A226

SVUBR/L Kr:93°
A227

VC□□ (Positive inserts)



Good working condition Normal working condition Bad working condition

Workpiece material					
K	Cast iron				
S	Heat resistant alloy, Ti alloy				
H	Super hard material				
N	Non ferrous metal	😊	😊	😐	☹

Type	Shape	Specification	Dimension(mm)					Grade			
			ØI.C	S	ød	r	L	DN0121	DN0511	DN1021	DN3021
0° rake angle		**VCGW160402AF**	9.525	4.76	4.4	0.2	3.3	○	○	○	○
		VCGW160404AF	9.525	4.76	4.4	0.4	2.8	○	○	○	○
		VCGW160408AF	9.525	4.76	4.4	0.8	2.5	○	○	○	○
7° rake angl		**VCMX160402AF**	9.525	4.76	4.4	0.2	3.3	○	○	○	○
		VCMX160404AF	9.525	4.76	4.4	0.4	2.8	○	○	○	○
		VCMX160408AF	9.525	4.76	4.4	0.8	2.5	○	○	○	○

According to processing requirements, the size and number of non-standard tool nose arcs can be provided.

★ Recommended grade (always stock available) ○ Make-to-order

Applicable tool

SVVCN
Kr:72°30'
Page A192

SVJCR/L
Kr:93°
A193

SVQCR/L
Kr:107°30'
A224

SVUCR/L
Kr:93°
A225

Abnormal failure and solutions for cast iron machining

Abnormal failure		Solution
Breakage	Breakage occurs on chamfer of rake face	Enlarge chamfered negative rake angle
	Edge crashing appears when finishing grey cast iron	
Abrasion	Abrasion occurs when machining nodular cast iron	Change to dry cutting
	Abrasion under dry cutting conditions	Reduce cutting speed
	Abrasion occurs when machining grey cast iron	Change to dry cutting, increase cutting speed
Surface quality	Bad surface finish	Increase cutting speed, increase nose radius, reduce feed rate
	Bad cylindricity and coaxiality	Reduce nose radius, improve stability, change to positive insert
	Burrs	Change to positive insert, reduce chamfer width

Abnormal failure and solutions for hardened steel

Abnormal failure			Solution
Breakage	Cutting edge breakage		Enlarge chamfered negative rake angle; raise cutting speed and reduce feed
	Flaking and crater wear on rake face		Reduce cutting speed
	Thermal cracks		Change to dry cutting; reduce cutting speed
Abrasion	Wear occurs on chamfer of rake face		Reduce cutting speed
	Rapid wear when finishing grey cast iron		
Surface quality	Bad surface finish	Vibration	Reduce chamfered negative rake angle; reduce nose radius; reduce feed rate; improve stability
		Tool mark	Increase nose radius; reduce feed rate; change to dry cutting; increase cutting speed
	Bad cylindricity and coaxiality		Reduce nose radius; improve stability; change to positive insert

Ceramic inserts code key

Insert shape



Tolerance class



Code	Nose height M Tolerance(mm)	Inscribed circle Tolerance(mm)	Thickness S Tolerance(mm)	Code	Nose height M Tolerance(mm)	Inscribed circle Tolerance(mm)	Thickness S Tolerance(mm)
A	±0.005	±0.025	±0.025	J	±0.005	±0.05-±0.13	±0.025
F	±0.005	±0.013	±0.025	K	±0.013	±0.05-±0.13	±0.025
C	±0.013	±0.025	±0.025	L	±0.025	±0.05-±0.13	±0.025
H	±0.013	±0.013	±0.025	M	±0.08-±0.18	±0.05-±0.13	±0.13
E	±0.025	±0.025	±0.025	N	±0.08-±0.18	±0.05-±0.13	±0.025
G	±0.025	±0.025	±0.13	U	±0.13-±0.38	±0.08-±0.25	±0.13

R P G N

Clearance angle of main cutting edge

Code	Clearance angle	Code	Clearance angle
A	3°	B	5°
C	7°	D	15°
E	20°	F	25°
G	30°	N	0°
P	11°	O	Other clearance angle

Chipbreaker and clamping system

Code	With/Without hole	Section plane of insert
N	Without	
B	With	> 65°
C	With	> 65°
A	With	
W	With	≤ 65°
Q	With	≤ 65°
X	---	Special

Length of cutting edge

Diameter of IC (mm)	Insert shape					
	C	D	S	T	V	W
3.97				06		
5.0						
5.56				09		
6.0						
6.35	06	07		11	11	
8.0						
9.525	09	11	09	16	16	06
10.0						
12.0						
12.7	12	15	12	22	22	08
15.875	16		15	27		
16.0		19				
19.05	19		19	33		
20.0						
25.0	25	25				
25.4			25			
31.75						
32						

Insert thickness



Thickness is defined as height from bottom of insert to the highest part of cutting edge.

Code	Insert thickness(mm)	Code	Insert thickness(mm)
02	2.38	06	6.35
T2	2.58	T6	6.75
03	3.18	07	7.94
T3	3.97	09	9.52
04	4.76	T9	9.72
T4	4.96	11	11.11
05	5.56	12	12.70
T5	5.95		

Nose radius code

Code	Nose radius(mm)
00	No radius
02	0.2
04	0.4
08	0.8
12	1.2
16	1.6
20	2.0
24	2.4
32	3.2
X	Others
Diameter of insert (Metric)	Round insert

09 07 00 T 010 20 - V

Type of cutting edge

Code	Type of cutting edge	Picture
E	Honing	
T	Chamfering	
S	Chamfering +honing	
F	Sharp edges	

Chamfer width (mm)



010	0.10	040	0.40
015	0.15	045	0.45
020	0.20	050	0.50
025	0.25	100	1.00
030	0.30	200	2.00
035	0.35		

Chamfer angle

05	5°
10	10°
15	15°
20	20°
25	25°
30	30°

V-type positioning surface





Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	☹
S	Heat resistant alloy	😐
H	Super hard material	😐

Inserts shape	Type	Dimensions(mm)		Grade
		ØI.C	S	CN3100
	RCGN090700T01015-V	9.525	7.94	○
	RCGN090700T01520-V	9.525	7.94	○
	RCGN090700T01020-V	9.525	7.94	●
	RCGN120700T01015-V	12.7	7.94	○
	RCGN120700T01020-V	12.7	7.94	○
	RCGN120700T01520-V	12.7	7.94	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

1 **CRDCR/L**

Page A205

2.Tailor-made nonstandard CRXCR





Good working condition Normal working condition Bad working condition

Workpiece material		
K	Cast iron	☹
S	Heat resistant alloy	😐
H	Super hard material	😐

Inserts shape	Type	Dimensions(mm)		Grade
		ØI.C	S	CN3100
	RPGN090700T01015-V	9.525	7.94	○
	RPGN090700T01520-V	9.525	7.94	○
	RPGN090700T01020-V	9.525	7.94	●
	RPGN120700T01015-V	12.7	7.94	○
	RPGN120700T01020-V	12.7	7.94	○
	RPGN120700T01520-V	12.7	7.94	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order

Applicable tool

1 **CRDPR/L**

Page A205

2.Tailor-made nonstandard CRXCR

D-type
double-clamping tool holder



Applications sketch map of turning tools

External and internal turning

External turning	Tool holder type						
	DTGNR/L□□	DSBNR/L□□	PCBNR/L□□	PSBNR/L□□	PSSNR/L□□	PTGNR/L□□	PTTNR/L□□
	SCACR/L□□	SSBCR/L□□	SSSCR/L□□	STACR/L□□	STGCR/L□□	STECR/L□□	SWACR/L□□

External and end surface turning	Tool holder type	
	DCLNR/L□□	DWLNR/L□□
	PCLNR/L□□	PWLNR/L□□
	SCLCR/L□□	

Profile turning	Tool holder type			
	DVVNN□□	PDPNN□□	PSDNN□□	SDNCN□□
	SVVBN□□	SVVCN□□	SSDCN□□	SRDCN□□
	CKNNR/L□□			



Profile turning	Tool holder type		
	DDJNR/L□□	DVJNR/L□□	PDJNR/L□□
	SDACR/L□□	SDJCR/L□□	SVABR/L□□
	SVJBR/L□□	SVJCR/L□□	CKJNR/L□□

Profile turning	Tool holder type
	SRGCR/L□□

End surface turning	Tool holder type	
	PSKNR/L□□	PTFNR/L□□
	SSKCR/L□□	STFCR/L□□

Tool holders for internal turning (Steel tool shank)

S□-PSKNR/L□	S□-PCLNR/L□	S□-PDPNR/L□	S□-PDUNR/L□	S□-SDQCR/L□	S□-SDZCR/L□
S□-PTFNR/L□	S□-PWLNR/L□		S□-SDUCR/L□	S□-SDQPR/L□	
S□-SCFCR/L□	S□-SCLCR/L□		S□-SDUPR/L□	S□-SVQBR/L□	
S□-SSKCR/L□	S□-SCLPR/L□		S□-SVUBR/L□	S□-SVQCR/L□	
S□-STFCR/L□			S□-SVUCR/L□		
S□-STUPR/L□					

Tool holders for internal turning (Cemented carbide tool shank)

C□-STUPR/L□	C□-SCLPR/L□	C□-SDUPR/L□	C□-SDQPR/L□
		C□-SVUCR/L□	C□-SVQCR/L□

Parting, grooving and threading tools



External threading tools	ZSER/L□
End surface grooving, turning	QF□D□□R/L□-□H
Parting blade	QE□S26/32N
Parting blade holder	QZS□26/32
Internal threading tools	ZSIR/L□
Internal grooving, turning	C□-Q□DR/L□ the Little Squirrel series
End surface grooving, turning	QF□D□R/L□-□L

External parting, grooving, turning and profilin	QE□D□R/L□	the Little Squirrel series
	QZQ□R/L□	
	ZQS□R/L□	
Precise grooving and turning	QECD□R/L025	the Little Squirrel series
External recess and profiling	QX□D□R/L□-45	the Little Squirrel series
External grooving for hard-to-machine materials	QE□S□R/L□-□N	the Little Squirrel series

How to select external turning tools

Explanation of external turning tools detailed table

- Listed according to clamping types.

Approach angle of tools

Tools type
The first 4 letters in the type description stands for tool shape and application

Inserts type

Specification chart

Application chart
The arrow shows suitable applications such as external turning, profiling and end turning, etc.

Corresponding tool holders of insert CN□□ D-type clamping



Type		Stock R	Stock L	a	b	L	h	s	e	Screw	Shim	Wrench	Clamp	Shim screw	Spring
DCLNR/L	1616H09	▲	△	16	16	100	16	20	24	CM5×22C	C09BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K09	▲	△	20	20	125	20	25	24						
	2525M09	▲	△	25	25	150	25	32	24						
	2020K12	▲	▲	20	20	125	20	25	28	CM6×25C	C12BM	WH40L	C2RA	SM6×10XA1	SPR4
	2525M12	▲	▲	25	25	150	25	32	28						
	3225P12	▲	▲	32	25	170	32	32	28						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	DF A54	WGM Wiper A55	DR Double-side A58	HDR A59	Without chipbreaker A59	A118
	WGF Wiper A54	PM A55	DR Single-side A58	HPR A59		A118 -A119
	SF A54	DM A56	ER Double-side A58			A119
	EF A54	EM A56	ER Single-side A58			
	NF A55	NM A57	SNR Double-side A58			
			LR Single-side A57			
Tool holder type	DCLNR/L□□H/K/M09 CN□□0903□□ CN□□0903□□					
	DCLNR/L□□K/M/P12 CN□□1204□□ CN□□1204□□ CN□□1204□□ CN□□1204□□ CN□□1204□□ CN□□1204□□					

Products specification
Including product description, stock (left and right hand), basic dimensions and applicable spare parts.

Applicable inserts
Including applications of inserts, reference page, insert shape and corresponding tool holders.



TURNING A

External Turning Tools

External turning tools overview A158-A161

External turning tools code key A162-A163

Detailed table of external turning tools A166-A204

External turning tool holders by D type clamping A166-A171

External turning tool holders by P type clamping A172-A183

External turning tool holders by S type clamping A184-A203

External turning tool holders by C type clamping A204

Detailed table of external turning tools (ceramic) A205

External turning tools overview

Clamping system	Tool type	Approach angle(Kr°)	Turning type						Applicable workpiece shape		Page
			External turning	End surface turning	External and end surface turning	Profile turning	Profile turning	Profile turning	Short, Thick	Thin, Long	
											
D	DCLNR/L	95			☺				☺		A166
	DDJNR/L	93					☺		☺	☺	A167
	DSBNR/L	75	☺						☺		A168
	DTGNR/L	91	☺						☺	☺	A169
	DVVNN	72.5						☺	☺		A170
	DVJNR/L	93					☺		☺	☺	A170
	DWLNR/L	95			☺				☺		A171
P	PCBNR/L	75	☺						☺		A172
	PCLNR/L	95			☺				☺		A173
	PDJNR/L	93					☺		☺	☺	A174
	PDPNN	62.5						☺	☺		A175

☺ Recommended ☺ Available

Clamping system	Tool type	Approach angle(Kr°)	Turning type						Applicable workpiece shape		Page
			External turning	End surface turning	External and end surface turning	Profile turning	Profile turning	Profile turning	Short, Thick	Thin, Long	
											
P	PSBNR/L	75	☺						☺		A176
	PSDNN	45						☺	☺		A177
	PSKNR/L	75		☺					☺		A178
	PSSNR/L	45	☺						☺		A179
	PTFNR/L	90		☺					☺	☺	A180
	PTTNR/L	60	☺						☺		A181
	PTGNR/L	90	☺						☺	☺	A182
	PWLNR/L	95			☺				☺		A183
S	SCACR/L	90	☺						☺	☺	A184
	SCLCR/L	95			☺				☺	☺	A185
	SDACR/L	90					☺		☺	☺	A186

☺ Recommended ☺ Available

Clamping system	Tool type	Approach angle(Kr°)	Turning type						Applicable workpiece shape		Page
			External turning	End surface turning	External and end surface turning	Profile turning	Profile turning	Profile turning	Short, Thick	Thin, Long	
											
S	SDJCR/L	93					☺		☺	☺	A187
	SDNCN	62.5						☺	☺	☺	A188
	SVJBR/L	93					☺		☺	☺	A189
	SVABR/L	90					☺		☺	☺	A190
	SVVBN	72.5						☺	☺	☺	A191
	SVVCN	72.5						☺	☺	☺	A192
	SVJCR/L	93					☺		☺	☺	A193
	SSBCR/L	75	☺						☺		A194
	SSDCN	45						☺	☺		A195
	SSKCR/L	75		☺					☺		A196
	SSSCR/L	45	☺						☺		A197

☺ Recommended ☺ Available

Clamping system	Tool type	Approach angle(K_r°)	Turning type						Applicable workpiece shape		Page
			External turning	End surface turning	External and end surface turning	Profile turning	Profile turning	Profile turning	Short, Thick	Thin, Long	
											
S	STACR/L	90	☺						☺	☺	A198
S	STFCR/L	90		☺					☺		A198
S	STGCR/L	91	☺						☺	☺	A199
S	STECR/L	60	☺						☺		A200
S	SWACR/L	90	☺						☺	☺	A201
S	SRDCN	--						☺	☺		A202
S	SRGCR/L	--				☺			☺		A203
C	CKJNR/L	93					☺		☺		A204
C	CKNNR/L	63						☺	☺		A204
C	CRDCR/L CRDPR/L	--					☺		☺		A205

☺ Recommended ☺ Available

External turning tools code key

Clamping system

D – double clamping

P – Hole clamping

S – Screw on

C – Top clamping

Insert shape

C



D

R

S

T

V

W

Clearance angle of insert



B



C



D



E



N



P

Cutting direction



L - Left-hand



R - Right-hand



N - Right and left hand

P C L N L

Tool holder style and approach angle

A	B	C	D	E	F	G	H
							

J	K	L	M	N	O	P	Q
							

R	S	T	U	V	W	X	
							

External turning tools code key

Nose height (mm)



Code	Height
12	12
16	16
20	20
25	25
32	32
40	40
50	50

Width of tool holder (mm)

Code	Width
12	12
16	16
20	20
25	25
32	32
40	40
50	50

Length of tool holder (mm)



Code	Length
E	70
F	80
H	100
K	125
M	150
P	170
Q	180
R	200
S	250
T	300

25 25 M 12

Length of cutting edge

Inserts shape	C	D	R	S	T	V	W
Inscribed circle (mm)	Length of cutting edge(mm)						
5.556	---	---	---	---	09	---	---
6.350	06	07	---	---	11	---	---
9.525	09	11	09	09	16	16	06
12.700	12	15	12	12	22	22	08
15.875	16	19	15	15	27	---	---
19.050	19	---	19	19	33	---	---
25.400	25	---	25	25	44	---	---
32.000	---	---	32	---	---	---	---





D-type double-clamping tool holder

With newly developed double-clamping structure, D-type turning tools have high clamping rigidity and high positioning accuracy, achieving easy and secure clamping of inserts. It is the best choice for the clamping of straight hole negative inserts.



Uniquely clamp

The clamp and the inner wall of insert hole make an arc contact. The stable and evenly distributed clamping force ensures more secure clamping.



lug boss on both ends and double-locating make more insert clamp secure .

Arc locating surface makes large contact area and the force is evenly distributed.

Simple and compact structure effectively prevents chip blocking while ensuring high clamping rigidity.

Convenient secure clamping device



Slots in the tool body match perfectly with the clamp, realizing simple and easy clamping.

Compared with lever-clamping:

① Accurate locating ensures more stable machining accuracy.



② High clamping rigidity effectively improves resistance to breakage of insert.



Compared with similar products of company A:

① Locating surface contact: (checking the contact location of clamp by dyeing)

Force evenly distributed, firm clamping, high locating accuracy.



ZCC-CT

Similar product of company A

② Effect on tool life:

Tool holder：DCLNL3225P12
Insert：YBC252/CNMG120408-DR
Cutting material：45# steel
Cutting parameters：V_c=250m/min
a_p=2mm
f=0.6mm/r

After 60 minutes of cutting

ZCC-CT

Similar product of company A



Corresponding tool holders of insert CN□□ D-type clamping

DCLNR/L
Kr:95°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DCLNR/L	1616H09	▲	△	16	16	100	16	20	24	CM5×22C	C09BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K09	▲	△	20	20	125	20	25	24						
	2525M09	▲	△	25	25	150	25	32	24						
	2020K12	▲	▲	20	20	125	20	25	28	CM6×25C	C12BM	WH40L	C2RA	SM6×10XA1	SPR4
	2525M12	▲	▲	25	25	150	25	32	28						
	3225P12	▲	▲	32	25	170	32	32	28						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	DF A54	WGM Wiper A55	DR Double-side A58	HDR A59	Without chipbreaker A59	A118
	WGF Wiper A54	PM A55	DR Single-side A58	HPR A59		A118 -A119
	SF A54	DM A56	ER Double-side A58			A119
	EF A54	EM A56	ER Single-side A58			
	NF A55	NM A57	SNR Double-side A58			
			LR Single-side A57			

Tool holder type							
	DCLNR/L□□H/K/M09	CN□□0903□□	CN□□0903□□				
	DCLNR/L□□K/M/P12	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□

Corresponding tool holders of insert DN□□ D-type clamping

DDJNR/L
Kr:93°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DDJNR/L	**1616H11**	△	△	16	16	100	16	20	30	CM5×22C	D11BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K11	▲	△	20	20	125	20	25	30						
	2525M11	▲	△	25	25	150	25	32	30						
	3225P11	△	△	32	25	170	32	32	30						
	2020K15	▲	▲	20	20	125	20	25	35	CM6×25C	D15BM	WH40L	C2RA	SM6×10XA1	SPR4
	2525M15	▲	▲	25	25	150	25	32	35						
	3232P15	▲	▲	32	32	170	32	40	35						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A61	**WGM** Wiper A63	**DR** Double-side A65	**HDR** A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	**PM** A63	**DR** Single-side A65			A122 -A123
	SF A62	**DM** A64	**ER** Double-side A65			A124
	EF A62	**EM** A64	**ER** Single-side A65			
	NF A62	**NM** A64	**SNR** Double-side A65			
	NGF A62		**LR** Single-side A65			

Tool holder type							
	DDJNR/L□□H/K/M/P11	DN□□1104□□	DN□□1104□□			DN□□1104□□	
	DDJNR/L□□K/M/P15	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□

Corresponding tool holders of insert SN□□ D-type clamping

DSBNR/L
Kr:75°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DSBNR/L	**1616H09**	▲	△	16	16	100	16	13	26	CM5×22C	S09BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K12	▲	▲	20	20	125	20	17	34	CM6×25C	S12BM	WH40L	C2RA	SM6×10XA1	SPR4
	2525M12	▲	▲	25	25	150	25	22	34						
	3225P12	▲	▲	32	25	170	32	22	34						
	3232P15	▲	▲	32	32	170	32	27	41	CM6×25C	S15BM	WH40L	C3RA	SM6×10XA2	SPR4

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A67	**PM** A68	**DR** Double-side A70	**HDR** A72	Without chipbreaker A74	A126
	EF A67	**DM** A68	**DR** Single-side A70 -71	**HPR** A72		A127
	SF A67	**EM** A69	**ER** Double-side A71			A128
		NM A69	**ER** Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			

Tool holder type							
	DSBNR/L□□H09	SN□□0903□□	SN□□0903□□			SN□□0903□□	
	DSBNR/L□□K/M/P12	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□
	DSBNR/L□□P15	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	

Corresponding tool holders of insert TN□□ D-type clamping

DTGNR/L
Kr:91°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DTGNR/L	**1616H16**	△	△	16	16	100	16	20	25	CM5×22C	T16BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K16	▲	▲	20	20	125	20	25	25						
	2525M16	▲	▲	25	25	150	25	32	25						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A75	**WGM** Wiper A76	**DR** Double-side A78	**HDR** A79	Without chipbreaker A80	A130
	WGF Wiper A75	**PM** A76	**DR** Single-side A78			A130 -A131
	SF A75	**DM** A77	**ER** Double-side A78			A131
	EF A76	**EM** A77	**SNR** Double-side A78			
			LR Single-side A77			
Tool holder type **DTGNR/L□□H/K/M16**	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□

Corresponding tool holders of insert VN□□ D-type clamping

DVVNN
Kr:72°30'



Type		Stock	Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
			a	b	L	h	s	e						
DVVNN	2020K16	△	20	20	125	20	10	44	CM5×22C	V16BM	WH30L	C6RA	SM5×8.65XA1	SPR6
	2525M16	▲	25	25	150	25	12.5	44						

▲Stock available △Make-to-order

DVJNR/L
Kr:93°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DVJNR/L	2020K16	▲	▲	20	20	125	20	25	41	CM5×22C	V16BM	WH30L	C6RA	SM5×8.65XA1	SPR6
	2525M16	▲	▲	25	25	150	25	32	41						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	PCBN&PCD inserts
Inserts shape	DF A81	PM A82	SNR A82	A133
	EF A81	DM A82		A133 -A134
	SF A81	EM A82		A134
	NF A81	NM A82		
	NGF A81			
Tool holder type	DVVNN□□K/M16	VN□□1604□□	VN□□1604□□	VN□□1604□□	VN□□1604□□
	DVJNR/L□□K/M16	VN□□1604□□	VN□□1604□□	VN□□1604□□	VN□□1604□□

Corresponding tool holders of insert WN□□ D-type clamping

DWLNR/L
Kr:95°



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Clamp	Shim screw	Spring
		R	L	a	b	L	h	s	e						
DWLNR/L	**1616H06**	▲	△	16	16	100	16	25	25	CM5×22C	W06BM	WH30L	C1RA	SM5×8.65XA1	SPR6
	2020K06	▲	▲	20	20	125	20	25	24						
	2525M06	▲	▲	25	25	150	25	32	24						
	2020K08	▲	▲	20	20	125	20	25	31	CM6×25C	W08BM	WH40L	C2RA	SM6×10XA1	SPR4
	2525M08	▲	▲	25	25	150	25	32	31						
	3225P08	△	△	32	25	170	32	32	31						

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A83	**WGM** Wiper A84	**DR** Double -side A86	Without chipbreaker A86	A136
	WGF Wiper A83	**PM** A85	**SNR** Double -side A86		A136 -A137
	SF A83	**DM** A85			A137
	EF A84	**EM** A85			
	NF A84	**NM** A86			
Tool holder type **DWLNR/L□□H/K/M06**	WN□□0604□□	WN□□0604□□	WN□□0604□□	WN□□0604□□	
DWLNR/L□□K/M/P08	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□

Corresponding tool holders of insert CN□□ P-type clamping

PCBNR/L

Kr:75°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PCBNR/L	2020K12	▲	▲	20	20	125	20	17	27	LEM8×21	C12AP	WH30L	L4	SP4
	2525M12	▲	▲	25	25	150	25	22	27					
	3232P12	▲	▲	32	32	170	32	27	33					
	2525M16	▲	▲	25	25	150	25	22	33	LEM8×25	C16AP	WH30L	L5	SP5
	3232P16	▲	▲	32	32	170	32	27	33					
	4040R16	▲	▲	40	40	200	40	35	38					
	3232P19	▲	▲	32	32	170	32	27	38	LEM10×27	C19AP	WH40L	L6	SP6
	4040R19	▲	▲	40	40	200	40	35	40					
	4040S2507	▲	▲	40	40	250	40	35	50	LEM12×36A	C25AP-07	WH50L	L8	SP8
	4040S2509	▲	▲	40	40	250	40	35	50		C25AP			

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining
Inserts shape	**DF** A54	**WGM** Wiper A55	**DR** Double-side A58	**HDR** A59	Without chipbreaker A59
	WGF Wiper A54	**PM** A55	**DR** Single-side A58	**HPR** A59	
	SF A54	**DM** A55	**ER** Double-side A58		
	EF A54	**EM** A56	**ER** Single-side A58		
	NF A55	**NM** A57	**SNR** Double-side A58		
			LR Single-side A57		

Tool holder type	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining
PCBNR/L□□K/M/P12	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□
PCBNR/L□□M/P/R16	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□
PCBNR/L□□P/R19		CN□□1906□□	CN□□1906□□	CN□□1906□□	CN□□1906□□
PCBNR/L□□S2507			CN□□2507□□		
PCBNR/L□□S2509			CN□□2509□□		

Corresponding tool holders of insert CN□□ P-type clamping

PCLNR/L
Kr:95°



R-type shown

Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PCLNR/L	**2020K12**	▲	▲	20	20	125	20	25	28	LEM8×21	C12AP	WH30L	L4	SP4
	2525M12	▲	▲	25	25	150	25	32	28					
	3225P12	△	△	32	25	170	32	32	33					
	3232P12	▲	▲	32	32	170	32	40	28					
	2525M16	▲	▲	25	25	150	25	32	33	LEM8×25	C16AP	WH30L	L5	SP5
	3225P16	△	△	32	25	170	32	32	33					
	3232P16	▲	▲	32	32	170	32	40	33					
	4040R16	△	△	40	40	200	40	50	42					
	3232P19	▲	▲	32	32	170	32	40	38	LEM10×27	C19AP	WH40L	L6	SP6
	4040R19	▲	▲	40	40	200	40	50	40					
	4040S2507	▲	▲	40	40	250	40	50	49	LEM12×36A	C25AP-07	WH50L	L8	SP8
	4040S2509	▲	▲	40	40	250	40	50	49		C25AP			

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A54	**WGM** Wiper A55	**DR** Double-side A58	**HDR** A59	Without chipbreaker A59	A118
	WGF Wiper A54	**PM** A55	**DR** Single-side A58	**HPR** A59		A118 -A119
	SF A54	**DM** A56	**ER** Double-side A58			A119
	EF A54	**EM** A56	**ER** Single-side A58			
	NF A55	**NM** A57	**SNR** Double-side A58			
			LR Single-side A57			

Tool holder type							
	PCLNR/L□□K/M/P12	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□
	PCLNR/L□□M/P/R16	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□	
	PCLNR/L□□P/R19		CN□□1906□□	CN□□1906□□	CN□□1906□□	CN□□1906□□	
	PCLNR/L□□S2507			CN□□2507□□			
	PCLNR/L□□S2509			CN□□2509□□			

Corresponding tool holders of insert DN□□ P-type clamping

PDJNR/L

Kr:93°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PDJNR/L	1616H11	▲	▲	16	16	100	16	20	25	LEM6×17	D11AP	WH25L	L3	SP3
	2020K11	▲	▲	20	20	125	20	25	25					
	2525M11	▲	▲	25	25	150	25	32	30					
	2020K15	▲	▲	20	20	125	20	25	35	LEM8×21	D15AP	WH30L	L4B	SP4
	2525M15	▲	▲	25	25	150	25	32	35					
	3232P15	▲	▲	32	32	170	32	40	35					
	2020K15-3	▲	△	20	20	125	20	25	35	LEM8×21	D15AP	WH30L	L4	SP4
	2525M15-3	▲	▲	25	25	150	25	32	35					
	3232P15-3	▲	△	32	32	170	32	40	35					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	DF A61	WGM Wiper A63	DR Double-side A65	HDR A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	PM A63	DR Single-side A65			A122 -A123
	SF A62	DM A64	ER Double-side A65			A124
	EF A62	EM A64	ER Single-side A65			
	NF A62	NM A64	SNR Double-side A65			
	NGF A62		LR Single-side A65			

Tool holder type							
	PDJNR/L□□H/K/M11	DN□□1104□□	DN□□1104□□			DN□□1104□□	
	PDJNR/L□□K/M/P15	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□
	PDJNR/L□□K/M/P15-3	DN□□1504□□	DN□□1504□□			DN□□1504□□	DN□□1504□□

Corresponding tool holders of insert DN□□ P-type clamping

PDPNN
Kr:62°30'



R-type shown



Type		Stock	Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
			a	b	L	h	s	e					
PDPNN	**2020K15**	▲	20	20	125	20	8	38	LEM8×21	D15AP	WH30L	L4B	SP4
	2525M15	▲	25	25	150	25	12.5	38					
	3232P15	▲	32	32	170	32	16	38					
	2020K15-3	▲	20	20	125	20	8	38	LEM8×21	D15AP	WH30L	L4	SP4
	2525M15-3	▲	25	25	150	25	12.5	38					
	3232P15-3	▲	32	32	170	32	16	38					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A61	**WGM** Wiper A63	**DR** Double-side A65	**HDR** A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	**PM** A63	**DR** Single-side A65			A122 -A123
	SF A62	**DM** A64	**ER** Double-side A65			A124
	EF A62	**EM** A64	**ER** Single-side A65			
	NF A62	**NM** A64	**SNR** Double-side A65			
	NGF A62		**LR** Single-side A65			
Tool holder type **PDPNN□□K/M/P15**	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□
PDPNN□□K/M/P15-3	DN□□1504□□	DN□□1504□□			DN□□1504□□	DN□□1504□□

Corresponding tool holders of insert SN□□ P-type clamping

PSBNR/L
Kr:75°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PSBNR/L	1616H09	▲	▲	16	16	100	16	13	21	LEM6×13.4A	S09AP	WH25L	L3	SP3
	2020K09	▲	▲	20	20	125	20	17	23					
	2020K12	▲	▲	20	20	125	20	17	28	LEM8×21	S12AP	WH30L	L4	SP4
	2525M12	▲	▲	25	25	150	25	22	28					
	3225P12	▲	△	32	25	170	32	22	28					
	3232P12	▲	▲	32	32	170	32	27	28					
	2525M15	▲	▲	25	25	150	25	22	35	LEM8×25	S15AP	WH30L	L5	SP5
	3232P15	▲	▲	32	32	170	32	27	35					
	3232P19	▲	▲	32	32	170	32	27	40	LEM10×27	S19AP	WH40L	L6	SP6
	4040R19	▲	▲	40	40	200	40	35	40					
	4040S2507	▲	▲	40	40	250	40	35	48	LEM12×36A	S25AP	WH50L	L8	SP8
	4040S2509	▲	▲	40	40	250	40	35	48		S25AP-09			

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A67	**PM** A68	**DR** Double-side A70	**HDR** A72	Without chipbreaker A74	A126
	EF A67	**DM** A68	**DR** Single-side A70 -71	**HPR** A72		A127
	SF A67	**EM** A69	**ER** Double-side A71			A128
		NM A69	**ER** Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			

Tool holder type							
	PSBNR/L□□H/K09	SN□□0903□□	SN□□0903□□			SN□□0903□□	
	PSBNR/L□□K/M/P12	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□
	PSBNR/L□□M/P15	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	
	PSBNR/L□□P/R19		SN□□1906□□	SN□□1906□□	SN□□1906□□	SN□□1906□□	
	PSBNR/L□□S2507			SN□□2507□□	SN□□2507□□		
	PSBNR/L□□S2509			SN□□2509□□	SN□□2509□□		

Corresponding tool holders of insert SN□□ P-type clamping

PSDNN
Kr:45°





Type		Stock	Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
			a	b	L	h	s	e					
PSDNN	**2020K12**	▲	20	20	125	20	10	30	LEM8×21	S12AP	WH30L	L4	SP4
	2525M12	▲	25	25	150	25	12.5	30					
	3232P12	▲	32	32	170	32	16	40					
	2525M15	▲	25	25	150	25	12.5	40	LEM8×25	S15AP	WH30L	L5	SP5
	3232P15	▲	32	32	170	32	16	40					
	3232P19	▲	32	32	170	32	16	40	LEM10×27	S19AP	WH40L	L6	SP6
	4040R19	▲	40	40	200	40	20	40					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A67	**PM** A68	**DR** Double-side A70	**HDR** A72	Without chipbreaker A74	A126
	EF A67	**DM** A68	**DR** Single-side A70 -71	**HPR** A72		A127
	SF A67	**EM** A69	**ER** Double-side A71			A128
		NM A69	**ER** Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			

Tool holder type							
	PSDNN□□K/M/P12	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□
	PSDNN□□M/P15	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	
	PSDNN□□P/R19		SN□□1906□□	SN□□1906□□	SN□□1906□□	SN□□1906□□	

Corresponding tool holders of insert SN□□ P-type clamping

PSKNR/L

Kr:75°

R-type shown

Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PSKNR/L	1616H09	▲	▲	16	16	100	16	20	17	LEM6×13.4A	S09AP	WH25L	L3	SP3
	2020K09	▲	△	20	20	125	20	25	20					
	2020K12	▲	▲	20	20	125	20	25	26	LEM8×21	S12AP	WH30L	L4	SP4
	2525M12	▲	▲	25	25	150	25	32	26					
	3232P12	▲	▲	32	32	170	32	40	26					
	2525M15	▲	▲	25	25	150	25	32	32	LEM8×25	S15AP	WH30L	L5	SP5
	3232P15	▲	▲	32	32	170	32	40	32					
	3232P19	▲	▲	32	32	170	32	40	36	LEM10×27	S19AP	WH40L	L6	SP6
	4040R19	▲	▲	40	40	200	40	50	40					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	DF A67	PM A68	DR Double-side A70	HDR A72	Without chipbreaker A74	A126
	EF A67	DM A68	DR Single-side A70 -71	HPR A72		A127
	SF A67	EM A69	ER Double-side A71			A128
		NM A69	ER Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			

Tool holder type							
	PSKNR/L□□H/K09	SN□□0903□□	SN□□0903□□			SN□□0903□□	
	PSKNR/L□□K/M/P12	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□
	PSKNR/L□□M/P15	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	
	PSKNR/L□□P/R19		SN□□1906□□	SN□□1906□□	SN□□1906□□	SN□□1906□□	

Corresponding tool holders of insert SN□□ P-type clamping

PSSNR/L
Kr:45°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PSSNR/L	**1616H09**	▲	▲	16	16	100	16	20	25	LEM6×13.4A	S09AP	WH25L	L3	SP3
	2020K09	△	△	20	20	125	20	25	25					
	2020K12	▲	▲	20	20	125	20	25	30	LEM8×21	S12AP	WH30L	L4	SP4
	2525M12	▲	▲	25	25	150	25	32	30					
	3232P12	▲	▲	32	32	170	32	40	40					
	2525M15	▲	▲	25	25	150	25	32	30	LEM8×25	S15AP	WH30L	L5	SP5
	3232P15	▲	▲	32	32	170	32	40	40					
	3232P19	▲	▲	32	32	170	32	40	40	LEM10×27	S19AP	WH40L	L6	SP6
	4040R19	▲	▲	40	40	200	40	50	40					
	4040S2507	▲	▲	40	40	250	40	50	50	LEM12×36A	S25AP	WH50L	L8	SP8
	4040S2509	▲	▲	40	40	250	40	50	50		S25AP-09			

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A67	**PM** A68	**DR** Double-side A70	**HDR** A72	Without chipbreaker A74	A126
	EF A67	**DM** A68	**DR** Single-side A70 -71	**HPR** A72		A127
	SF A67	**EM** A69	**ER** Double-side A71			A128
		NM A69	**ER** Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			

Tool holder type							
	PSSNR/L□□H/K09	SN□□0903□□	SN□□0903□□	SN□□0903□□		SN□□0903□□	
	PSSNR/L□□K/M/P12	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□
	PSSNR/L□□M/P15	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	SN□□1506□□	
	PSSNR/L□□P/R19		SN□□1906□□	SN□□1906□□	SN□□1906□□	SN□□1906□□	
	PSSNR/L□□S2507			SN□□2507□□	SN□□2507□□		
	PSSNR/L□□S2509			SN□□2509□□	SN□□2509□□		

Corresponding tool holders of insert TN□□ P-type clamping

PTFNR/L
Kr:90°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PTFNR/L	**1616H16**	△	▲	16	16	100	16	20	20	LEM6×13.4A	T16AP	WH25L	L3	SP3
	2020K16	▲	▲	20	20	125	20	25	20					
	2525M16	▲	▲	25	25	150	25	32	20					
	2525M22	▲	▲	25	25	150	25	32	25	LEM8×21	T22AP	WH30L	L4	SP4
	3232P22	▲	▲	32	32	170	32	40	25					
	3232P27	▲	▲	32	32	170	32	40	34	LEM8×25	T27AP	WH30L	L5	SP5
	4040S27	▲	▲	40	40	250	40	50	34					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A75	**WGM** Wiper A76	**DR** Double-side A78	**HDR** A79	Without chipbreaker A80	A130
	WGF Wiper A75	**PM** A76	**DR** Single-side A78			A130 -A131
	SF A75	**DM** A77	**ER** Double-side A78			A131
	EF A76	**EM** A77	**SNR** A78			
			LR Single-side A77			

Tool holder type							
	PTFNR/L□□H/K/M16	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□
	PTFNR/L□□M/P22	TN□□2204□□	TN□□2204□□	TN□□2204□□	TN□□2204□□	TN□□2204□□	
	PTFNR/L□□P/S27			TN□□2706□□	TN□□2706□□	TN□□2706□□	

Corresponding tool holders of insert TN□□ P-type clamping

PTTNR/L
Kr:60°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PTTNR/L	**1616H16**	▲	▲	16	16	100	16	13	25	LEM6×13.4A	T16AP	WH25L	L3	SP3
	2020K16	▲	▲	20	20	125	20	17	25					
	2525M16	△	△	25	25	150	25	22	25					
	2525M22	▲	▲	25	25	150	20	22	32	LEM8×21	T22AP	WH30L	L4	SP4

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A75	**WGM** Wiper A76	**DR** Double-side A78	**HDR** A79	Without chipbreaker A80	A130
	WGF Wiper A75	**PM** A76	**DR** Single-side A78			A130 -A131
	SF A75	**DM** A77	**ER** Double-side A78			A131
	EF A76	**EM** A77	**SNR** A78			
			LR Single-side A77			

Tool holder type							
	PTTNR/L□□H/K/M16	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□
	PTTNR/L□□M22	TN□□2204□□	TN□□2204□□	TN□□2204□□	TN□□2204□□		

Corresponding tool holders of insert TN□□ P-type clamping

PTGNR/L
Kr:90°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PTGNR/L	**1616H16**	▲	▲	16	16	100	16	20	20	LEM6×13.4A	T16AP	WH25L	L3	SP3
	2020K16	▲	▲	20	20	125	20	25	20					
	2525M16	▲	▲	25	25	150	25	32	20					
	3232P16	▲	▲	32	32	170	32	40	20					
	2525M22	▲	▲	25	25	150	25	32	28	LEM8×21	T22AP	WH30L	L4	SP4
	3232P22	▲	▲	32	32	170	32	40	28					
	3232P27	▲	▲	32	32	170	32	40	33	LEM8×25	T27AP	WH30L	L5	SP5
	4040S27	▲	▲	40	40	250	40	50	33					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A75	**WGM** Wiper A76	**DR** Double-side A78	**HDR** A79	Without chipbreaker A80	A130
	WGF Wiper A75	**PM** A76	**DR** Single-side A78			A130 -A131
	SF A75	**DM** A77	**ER** Double-side A78			A131
	EF A76	**EM** A77	**SNR** A78			
			LR Single-side A77			

Tool holder type							
	PTGNR/L□□H/K/M/P16	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□
	PTGNR/L□□M/P22	TN□□2204□□	TN□□2204□□	TN□□2204□□	TN□□2204□□		
	PTGNR/L□□P/S27			TN□□2706□□	TN□□2706□□		

Corresponding tool holders of insert WN□□ P-type clamping

PWLNR/L

Kr:95°



R-type shown

Type		Stock		Basic dimensions(mm)						Screw	Shim	Wrench	Lever	Shim pin
		R	L	a	b	L	h	s	e					
PWLNR/L	**1616H06**	▲	▲	16	16	100	16	20	20	LEM6×13.4A	W06AP	WH25L	L3	SP3
	2020K06	▲	▲	20	20	125	20	25	20					
	2525M06	▲	▲	25	25	150	25	32	20					
	2020K08	▲	▲	20	20	125	20	25	26	LEM8×21	W08AP	WH30L	L4	SP4
	2525M08	▲	▲	25	25	150	25	32	26					
	3232P08	△	△	32	32	170	32	40	28					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For cast iron machining	PCBN&PCD inserts
Inserts shape	**DF** A83	**WGM** Wiper A84	**DR** Double -side A86	Without chipbreaker A86	A136
	WGF Wiper A83	**PM** A85	**SNR** Double -side A86		A136 -A137
	SF A83	**DM** A85			A137
	EF A84	**EM** A85			
	NF A84	**NM** A86			
Tool holder type **PWLNR/L□□H/K/M06**	WN□□0604□□	WN□□0604□□	WN□□0604□□	WN□□0604□□	
PWLNR/L□□K/M/P08	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□

Corresponding tool holders of insert CC□□ S-type clamping

SCACR/L

Kr:90°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Wrench
		R	L	a	b	L	h	s	e		
SCACR/L	0808F06	△	△	8	8	80	8	8	16		
	1010H06	▲	△	10	10	100	10	10	16	I60M2.5×6.5	WT07IP
	1212H06	△	△	12	12	100	12	12	16		
	1212H09	▲	▲	12	12	100	12	12	20	I60M3.5×8	WT15IP
	1616H09	△	△	16	16	100	16	16	20		

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**USF** A89	**HF** A89	**HM** A90	**HR** A91	**LH** A91-92	Without chipbreaker A92	A139
	SF A89	**EF** A90	**EM** A90		**LC** A91		A144
Tool holder type **SCACR/L□□H/F06**	CC□□0602□□	CC□□0602□□	CC□□0602□□	CC□□0602□□	CCGX 0602□□	CC□□ 0602□□	CC□□ 0602□□
SCACR/L□□H09	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CCGX 09T3□□	CC□□ 09T3□□	CC□□ 09T3□□

Corresponding tool holders of insert CC□□ S-type clamping

SCLCR/L
Kr:95°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SCLCR/L	**0808F06**	▲	△	08	08	80	08	10	12	I60M2.5×6.5	---	---	WT07IP
	1010F06	▲	▲	10	10	80	10	12	12				
	1212H06	△	△	12	12	100	12	16	12				
	1616H06	△	△	16	16	100	16	20	16				
	1212H09	▲	▲	12	12	100	12	16	16	I60M3.5×8	---	---	WT15IP
	1616H09	▲	▲	16	16	100	16	20	16				
	2020K09	△	△	20	20	125	20	25	16				
	2525M09	△	△	25	25	150	25	32	16				
	2020K12	▲	▲	20	20	125	20	25	20	I60M4×11X	C12BS	SM6×10XA	WT15IP WH40L
	2525M12	▲	▲	25	25	150	25	32	20				
	3225M12	▲	▲	32	25	150	32	32	20				

▲Stock available △Make-to-order

Applicable inserts

Application		For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape		**USF** A89	**HF** A89	**HM** A90	**HR** A91	**LH** A91-92	Without chipbreaker A92	A139
		SF A89	**EF** A90	**EM** A90		**LC** A91		A144
Tool holder type	**SCLCR/L□□H/F06**	CC□□ 0602□□	CC□□ 0602□□	CC□□ 0602□□	CC□□ 0602□□	CCGX 0602□□	CC□□ 0602□□	CC□□ 0602□□
	SCLCR/L□□H/K/M09	CC□□ 09T3□□	CC□□ 09T3□□	CC□□ 09T3□□	CC□□ 09T3□□	CCGX 09T3□□	CC□□ 09T3□□	CC□□ 09T3□□
	SCLCR/L□□K/M12		CC□□ 1204□□	CC□□ 1204□□	CC□□ 1204□□	CCGX 1204□□	CC□□ 1204□□	CC□□ 1204□□

Corresponding tool holders of insert DC□□ S-type clamping

SDACR/L

Kr:90°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SDACR/L	0808K07	△	△	8	8	125	8	8	15	I60M2.5×6.5	---	---	WT07IP
	1010K07	△	△	10	10	125	10	10	15				
	1212K07	△	△	12	12	125	10	10	15				
	1212K11	△	△	12	12	125	12	12	22	I60M3.5×8	---	---	WT15IP
	1616K11	△	△	16	16	125	16	16	22	I60M3.5×12	D11BS	SM5×8.65XA	WT15IP WH35L
	2020K11	△	△	20	20	125	20	20	22				
	2525M11	△	△	25	25	150	25	25	22				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**USF** A93	**HF**  A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
	SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type **SDACR/L□□K07**	DC□□ 0702□□	DC□□ 0702□□	DC□□ 0702□□		DCGX 0702□□	DC□□0702□□	DC□□0702□□
SDACR/L□□K/M11	DC□□ 11T3□□	DC□□ 11T3□□	DC□□ 11T3□□	DC□□ 11T3□□	DCGX 11T3□□	DC□□ 11T3□□	DC□□ 11T3□□

Corresponding tool holders of insert DC□□ S-type clamping

SDJCR/L
Kr:93°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SDJCR/L	**0808F07**	△	△	8	8	80	8	10	15	I60M2.5×6.5	---	---	WT07IP
	1010F07	▲	△	10	10	80	10	12	15				
	1212H07	▲	▲	12	12	100	12	16	15				
	1414H07	△	△	14	14	100	14	18	15				
	1616H07	▲	▲	16	16	100	16	20	15				
	2020K07	△	△	20	20	125	20	25	28				
	2525M07	△	△	25	25	150	25	32	28				
	1212K11	△	△	12	12	125	12	16	22	I60M3.5×12	D11BS	SM5×8.65XA	WT15IP WH35L
	1616K11	▲	▲	16	16	125	16	20	22				
	2020K11	▲	▲	20	20	125	20	25	22				
	2525M11	▲	▲	25	25	150	25	32	22				

▲Stock available △Make-to-order

Applicable inserts

Application		For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape		**USF** A93	**HF** A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
		SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type	**SDJCR/L□□F/H/K/M07**	DC□□0702□□	DC□□ 0702□□	DC□□0702□□		DCGX 0702□□	DC□□ 0702□□	DC□□ 0702□□
	SDJCR/L□□K/M11	DC□□ 11T3□□	DC□□ 11T3□□	DC□□11T3□□	DC□□11T3□□	DCGX 11T3□□	DC□□ 11T3□□	DC□□ 11T3□□

Corresponding tool holders of insert DC□□ S-type clamping

SDNCN
Kr:62°30'





Type		Stock	Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
			a	b	L	h	s	e				
SDNCN	**0808F07**	△	8	8	80	8	4	15	I60M2.5×6.5	---	---	WT07IP
	1010F07	▲	10	10	80	10	5	15				
	1212H07	▲	12	12	100	12	6	15				
	1616H07	△	16	16	100	16	8	15				
	2020K07	△	20	20	125	20	10	20				
	2525M07	△	25	25	150	25	12.5	20				
	1616K11	▲	16	16	125	16	8	22	I60M3.5×12	D11BS	SM5×8.65XA	WT15IP WH35L
	2020K11	▲	20	20	125	20	10	22				
	2525M11	▲	25	25	150	25	12.5	22				
	3225M11	△	32	25	150	32	12.5	22				
	3232P11	△	32	32	170	32	16	22				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	**USF** A93	**HF** A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
	SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type **SDNCN□□F/H/K/M07**	DC□□0702□□	DC□□ 0702□□	DC□□0702□□		DCGX 0702□□	DC□□ 0702□□	DC□□ 0702□□
Tool holder type **SDNCN□□K/M/P11**	DC□□ 11T3□□	DC□□ 11T3□□	DC□□11T3□□	DC□□11T3□□	DCGX 11T3□□	DC□□ 11T3□□	DC□□ 11T3□□

Corresponding tool holders of insert VB□□ S-type clamping

SVJBR/L
Kr:93°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SVJBR/L	**1212H11**	▲	▲	12	12	100	12	16	25	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	▲	16	16	100	16	20	25				
	2020K11	▲	▲	20	20	125	20	25	25				
	2525M11	▲	▲	25	25	150	25	32	25				
	1616H16	▲	▲	16	16	100	16	20	35	I60M3.5×12	V16BS	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	▲	20	20	125	20	25	35				
	2525M16	▲	▲	25	25	150	25	32	35				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	PCBN&PCD inserts
Inserts shape	**SF** A108	**HF** A108	**HM** A109	**HR** A109	A142
		NF A108	**EM** A109	**SNR** A109	A147
		EF A108			
		NGF A108			
Tool holder type **SVJBR/L□□H/K/M11**	VB□□1103□□	VB□□1103□□	VB□□1103□□		
SVJBR/L□□H/K/M16		VB□□1604□□	VB□□1604□□	VB□□1604□□	VB□□1604□□

Corresponding tool holders of insert VB□□ S-type clamping

SVABR/L
Kr:90°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SVABR/L	**1010F11**	△	△	10	10	80	10	10	25	I60M2.5×6.5	---	---	WT07IP
	1616H16	△	△	16	16	100	16	16	28	I60M3.5×12	V16BS	SM5×8.65XA	WT15IP WH35L
	2020K16	△	△	20	20	125	20	20	28				
	2525M16	△	△	25	25	150	25	25	28				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	PCBN&PCD inserts
Inserts shape	**SF** A108	**HF** A108	**HM** A109	**HR** A109	A142
		NF A108	**EM** A109	**SNR** A109	A147
		EF A108			
		NGF A108			

Tool holder type						
	SVABR/L□□F11	VB□□1103□□	VB□□1103□□	VB□□1103□□		
	SVABR/L□□H/K/M16		VB□□1604□□	VB□□1604□□	VB□□1604□□	VB□□1604□□

Corresponding tool holders of insert VB□□ S-type clamping

SVVBN
Kr:72°30'





Type		Stock	Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
			a	b	L	h	s	e				
SVVBN	**1212H11**	▲	12	12	100	12	6	25	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	16	16	100	16	8	25				
	2020K11	▲	20	20	125	20	10	25				
	2525M11	△	25	25	150	25	12.5	35				
	1616H16	▲	16	16	100	16	8	35	I60M3.5×12	V16BS	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	20	20	125	20	10	35				
	2525M16	▲	25	25	150	25	12.5	35				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	PCBN&PCD inserts
Inserts shape	**SF** A108	**HF** A108	**HM** A109	**HR** A109	A142
		NF A108	**EM** A109	**SNR** A109	A147
		EF A108			
		NGF A108			
Tool holder type **SVVBN□□H/K/M11**	VB□□1103□□	VB□□1103□□	VB□□1103□□		
SVVBN□□H/K/M16		VB□□1604□□	VB□□1604□□	VB□□1604□□	VB□□1604□□

Corresponding tool holders of insert VC□□ S-type clamping

SVVCN
Kr:72°30'





Type		Stock	Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
			a	b	L	h	s	e				
SVVCN	1212H11	▲	12	12	100	12	6	25	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	16	16	100	16	8	27				
	2020K11	▲	20	20	125	20	10	30				
	2525M11	△	25	25	150	25	12.5	38				
	1616H16	▲	16	16	100	16	8	33	I60M3.5×12	V16BSC	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	20	20	125	20	10	33				
	2525M16	▲	25	25	150	25	12.5	38				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For Al machining	PCBN&PCD inserts
Inserts shape	USF A105	HF A105	LH A106	A143
	SF A105	NF A105	LC A106	A148
		NGF A105		
Tool holder type SVVCN□□H/K/M11	VC□□1103□□	VC□□1103□□	VCGX1103□□	
SVVCN□□H/K/M16		VC□□1604□□	VCGX1604□□	VC□□1604□□

Corresponding tool holders of insert VC□□ S-type clamping

SVJCR/L
Kr:93°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SVJCR/L	**1212H11**	△	△	12	12	100	12	16	25	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	▲	16	16	100	16	20	25				
	2020K11	▲	▲	20	20	125	20	25	25				
	2525M11	▲	▲	25	25	150	25	32	35				
	1616H16	▲	▲	16	16	100	16	20	35	I60M3.5×12	V16BSC	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	▲	20	20	125	20	25	35				
	2525M16	▲	▲	25	25	150	25	32	35				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For Al machining	PCBN&PCD inserts
Inserts shape	**USF** A105	**HF** A105	**LH** A106	A143
	SF A105	**NF** A105	**LC** A106	A148
		NGF A105		
Tool holder type **SVJCR/L□□H/K/M11**	VC□□1103□□	VC□□1103□□	VCGX1103□□	
SVJCR/L□□H/K/M16		VC□□1604□□	VCGX1604□□	VC□□1604□□

Corresponding tool holders of insert SC□□ S-type clamping

SSBCR/L

Kr:75°

R-type shown

Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SSBCR/L	1212H09	▲	▲	12	12	100	12	9	16	I60M3.5×8	---	---	WT15IP
	1616H09	▲	▲	16	16	100	16	13	16	I60M3.5×12	S09BS	SM5×8.65XA	WT15IP WH35L
	2020K09	△	△	20	20	125	20	17	20				
	2525M09	△	△	25	25	150	25	22	20				
	2020K12	▲	▲	20	20	125	20	17	25	I60M4×11X	S12BS	SM6×10XA	WT15IP WH40L
	2525M12	△	△	25	25	150	25	22	25				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining
Inserts shape	HF A98	HM A98	HR A99	LH A99	Without chipbreaker A99
	EF A98	EM A98		LC A99	
Tool holder type SSBCR/L□□H/K/M09	SC□□09T3□□	SC□□09T3□□	SC□□09T3□□	SCGX09T3□□	SC□□09T3□□
Tool holder type SSBCR/L□□K/M12		SC□□1204□□	SC□□1204□□	SCGX1204□□	SC□□1204□□

Corresponding tool holders of insert SC□□ S-type clamping

SSDCN
Kr:45°



Type		Stock	Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
			a	b	L	h	s	e				
SSDCN	**1212H09**	▲	12	12	100	12	6	16	I60M3.5×8	---	---	WT15IP
	1616H09	▲	16	16	100	16	8	16	I60M3.5×12	S09BS	SM5×8.65XA	WT15IP WH35L
	2020K09	△	20	20	125	20	10	20				
	2525M09	△	25	25	150	25	12.5	20				
	2525M12	▲	25	25	150	25	12.5	22	I60M4×11	S12BS	SM6×10XA	WT15IP WH40L

▲Stock available △Make-to-order

Applicable inserts

Application		For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining
Inserts shape		**HF** A98	**HM** A98	**HR** A99	**LH** A99	Without chipbreaker A99
		EF A98	**EM** A98		**LC** A99	
Tool holder type	**SSDCN□□H/K/M09**	SC□□09T3□□	SC□□09T3□□	SC□□09T3□□	SCGX09T3□□	SC□□09T3□□
	SSDCN□□M12		SC□□1204□□	SC□□1204□□	SCGX1204□□	SC□□1204□□

Corresponding tool holders of insert SC□□ S-type clamping

SSKCR/L

Kr:75°



R-type shown

Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SSKCR/L	**1212H09**	△	△	12	12	100	12	16	16	I60M3.5×8	---	---	WT15IP
	1616H09	▲	△	16	16	100	16	20	16	I60M3.5×12	S09BS	SM5×8.65XA	WT15IP WH35L
	2020K09	△	△	20	20	125	20	25	20				
	2525M09	△	△	25	25	150	25	32	20				
	2020K12	△	△	20	20	125	20	25	22	I60M4×11X	S12BS	SM6×10XA	WT15IP WH40L
	2525M12	△	△	25	25	150	25	32	22				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining
Inserts shape	**HF** A98	**HM** A98	**HR** A99	**LH** A99	Without chipbreaker A99
	EF A98	**EM** A98		**LC** A99	
Tool holder type **SSKCR/L□□H/K/M09**	SC□□09T3□□	SC□□09T3□□	SC□□09T3□□	SCGX09T3□□	SC□□09T3□□
SSKCR/L□□K/M12		SC□□1204□□	SC□□1204□□	SCGX1204□□	SC□□1204□□

Corresponding tool holders of insert SC□□ S-type clamping

SSSCR/L
Kr:45°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
SSSCR/L	**1212H09**	△	△	12	12	100	12	16	16	I60M3.5×8	---	---	WT15IP
	1616H09	▲	▲	16	16	100	16	17	16	I60M3.5×12	S09BS	SM5×8.65XA	WT15IP WH35L
	2020K09	△	△	20	20	125	20	21	20				
	2525M09	△	△	25	25	150	25	32	20				
	2020K12	▲	▲	20	20	125	20	21	24	I60M4×11X	S12BS	SM6×10XA	WT15IP WH40L
	2525M12	△	△	25	25	150	25	32	22				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining
Inserts shape	**HF** A98	**HM** A98	**HR** A99	**LH** A99	Without chipbreaker A99
	EF A98	**EM** A98		**LC** A99	
Tool holder type **SSSCR/L□□H/K/M09**	SC□□09T3□□	SC□□09T3□□	SC□□09T3□□	SCGX09T3□□	SC□□09T3□□
SSSCR/L□□K/M12		SC□□1204□□	SC□□1204□□	SCGX1204□□	SC□□1204□□

Corresponding tool holders of insert TC□□ S-type clamping

STACR/L
Kr:90°


R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Wrench	---	---
		R	L	a	b	L	h	s	e			---	---
STACR/L	1010K11	△	△	10	10	100	10	10	12	I60M2.5×6.5	WT07IP	---	---
	1212F11	△	△	12	12	100	12	12	14				
	1616K11	△	△	16	16	100	16	16	16				

▲Stock available △Make-to-order

STFCR/L
Kr:90°


R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
STFCR/L	1212H11	▲	▲	12	12	100	12	16	14	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	▲	16	16	100	16	20	14				
	2020K11	△	△	20	20	125	20	25	20				
	2525M11	△	△	25	25	150	25	32	20				
	1616K16	▲	▲	16	16	125	16	20	20	I60M3.5×12	T16BS	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	▲	20	20	125	20	25	20				
	2525M16	△	△	25	25	150	25	32	25				

▲Stock available △Make-to-order

Applicable inserts

Application		For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape		HF A101	HM A103	HR A103	LH A104	Without chipbreaker A104	A141
		EF A102	EM A102		LC A103		
Tool holder type	STACR/L□□K/F11	TC□□1102□□	TC□□1102□□	TC□□1102□□	TCGX1102□□	TC□□1102□□	TC□□1102□□
	STFCR/L□□H/K/M11	TC□□1102□□	TC□□1102□□	TC□□1102□□	TCGX1102□□	TC□□1102□□	TC□□1102□□
	STFCR/L□□K/M16	TC□□16T3□□	TC□□16T3□□	TC□□16T3□□	TCGX16T3□□	TC□□16T3□□	

Corresponding tool holders of insert TC□□ S-type clamping

STGCR/L

Kr:91°



R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
STGCR/L	0808F09	▲	△	08	08	80	8	10	12	I60M2.2×5.5	---	---	WT06IP
	1010F09	▲	▲	10	10	80	10	12	12				
	1212H09	△	△	12	12	100	12	16	12				
	1212H11	▲	▲	12	12	100	12	16	16	I60M2.5×6.5	---	---	WT07IP
	1616H11	▲	▲	16	16	100	16	20	16				
	2020K11	△	△	20	20	125	20	25	20				
	2525M11	△	△	25	25	150	25	32	20				
	1616K16	△	△	16	16	125	16	20	20	I60M3.5×12	T16BS	SM5×8.65XA	WT15IP WH35L
	2020K16	▲	▲	20	20	125	20	25	21				
	2525M16	▲	▲	25	25	150	25	32	21				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape	USF A100	HF A101	HM A103	HR A103	LH A104	Without chipbreaker A104	A141
	SF A100	EF A102	EM A102		LC A103		
Tool holder type STGCR/L□□F/H09	TC□□0902□□	TC□□0902□□	TC□□0902□□	TC□□0902□□	TCGX0902□□	TC□□0902□□	TC□□0902□□
STGCR/L□□H/K/M11		TC□□1102□□	TC□□1102□□	TC□□1102□□	TCGX1102□□	TC□□1102□□	TC□□1102□□
STGCR/L□□K/M16		TC□□16T3□□	TC□□16T3□□	TC□□16T3□□	TCGX16T3□□	TC□□16T3□□	

Corresponding tool holders of insert TC□□ S-type clamping

STECR/L

Kr:60°

R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s	e				
STECR/L	**1616H11**	△	△	16	16	100	16	10.5	16	I60M2.5×6.5	---	---	WT07IP
	2020K11	△	△	20	20	125	20	14.5	20				
	2020K16	△	△	20	20	125	20	12.5	20	I60M3.5×12	T16BS	SM5×8.65XA	WT15IP
	2525M16	△	△	25	25	150	25	17.0	25				WT35IP

▲Stock available △Make-to-order

Applicable inserts

Application		For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN&PCD inserts
Inserts shape		**HF** A101	**HM** A103	**HR** A103	**LH** A104	Without chipbreaker A104	A141
		EF A102	**EM** A102		**LC** A103		
Tool holder type	**STECR/L□□H/K11**	TC□□1102□□	TC□□1102□□	TC□□1102□□	TCGX1102□□	TC□□1102□□	TC□□1102□□
	STECR/L□□K/M16	TC□□16T3□□	TC□□16T3□□	TC□□16T3□□	TCGX16T3□□	TC□□16T3□□	

Corresponding tool holders of insert WC□□ S-type clamping

SWACR/L
Kr:90°

R-type shown



Type		Stock		Basic dimensions(mm)						Screw	Wrench	—	—
		R	L	a	b	L	h	s	e			—	—
SWACR/L	**1010E04**	△	△	10	10	70	10	10	10	I60M2.5×6.5	WT07IP	---	---
	1212F04	▲	△	12	12	80	12	12	14				
	1616H06	▲	△	16	16	100	16	16	20	I60M3×7	WT10IP	---	---
	2020K08	▲	▲	20	20	125	20	20	24	I60M3.5×12	WT15IP	---	---

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing
Inserts shape	**53** A107
Tool holder type **SWACR/L□□E/F04**	WC□X0402□□
Tool holder type **SWACR/L□□H06**	WC□X06T3□□
Tool holder type **SWACR/L□□K08**	WC□X0804□□

Corresponding tool holders of insert RC□□ S-type clamping

SRDCN





Type		Stock	Basic dimensions(mm)						Screw	Shim	Shim screw	Wrench
			a	b	L	h	s	e				
SRDCN	1616H08	△	16	16	100	16	8	16	I60M3×7	---	---	WT10IP
	2020K08	△	20	20	125	20	10	16				
	2525M08	△	25	25	150	25	12.5	16				
	2020K10	△	20	20	125	20	10	20	I60M3.5×10	---	---	WT15IP
	2525M10	▲	25	25	150	25	12.5	20				
	2525M12	▲	25	25	150	25	12.5	35	I60M3.5×12	R12BS	SM5×8.65XA	WT15IP WH35L
	3232P12	△	32	32	170	32	16	35				
	3225P16	▲	32	25	170	32	12.5	35	I60M4×15X	R16BS	SM6×10XA	WT15IP WH40L
	4040S16	△	40	40	250	40	20	40				

▲Stock available △Make-to-order

Applicable inserts

Application	For semi-finishing	For roughing	For Al machining
Inserts shape	A96	A96	LH A96
Tool holder type: SRDCN□□K/M/H08	RCMT0803MO	RCMT0803MO	RCGX0803MO-LH
SRDCN□□K/M10	RCMT10T3MO	RCMT10T3MO	
SRDCN□□M/P12	RCMT1204MO	RCMT1204MO	
SRDCN□□P/S16	RCMT1606MO	RCMT1606MO	

Corresponding tool holders of insert RC□□ S-type clamping

SRGCR/L



R-type shown





Type		Stock		Basic dimensions(mm)					Screw	Shim	Shim screw	Wrench
		R	L	a	b	L	h	s				
SRGCR/L	1616H08	△	△	16	16	100	16	20	I60M3×7	---	---	WT10IP
	2020K08	△	△	20	20	125	20	25				
	2525M08	△	△	25	25	150	25	32				
	1616H10	△	△	16	16	100	16	20	I60M3.5×10	---	---	WT15IP
	2020K10	▲	▲	20	20	125	20	25				
	2525M10	▲	▲	25	25	150	25	32				
	2020K12	▲	△	20	20	125	20	27	I60M3.5×12	R12BS	SM5×8.65XA	WT15IP WH35L
	2525M12	▲	▲	25	25	150	25	32				
	3232P16	▲	△	32	32	170	32	40	I60M4×15X	R16BS	SM6×10XA	WT15IP WH40L

▲Stock available △Make-to-order

Applicable inserts

Application	For semi-finishing	For roughing	For Al machining
Inserts shape	A96	A96	LH A96
Tool holder type: SRGCR/L□□H/K/M08	RCMT0803MO	RCMT0803MO	RCGX0803MO-LH
SRGCR/L□□H/K/M10	RCMT10T3MO	RCMT10T3MO	
SRGCR/L□□K/M12	RCMT1204MO	RCMT1204MO	
SRGCR/L□□P16	RCMT1606MO	RCMT1606MO	

Corresponding tool holders of insert KNUX□□ C-type clamping

CKJNR/L
Kr:93°



R-type shown



Type		Stock	Basic dimensions(mm)						Applicable inserts	Clamp	Clamp screw	Spring	Clamping stud	Shim	Shim screw	Wrench
			a	b	L	h	s	e								
CKJNR	2525M16	△	25	25	150	25	32	32	KNUX1604□□R A87	C6R1T	CM6×25A	SPR1 SPR2	P0515	K16CC	SM3×10B	WH20L WH40L
	3232P16	△	32	32	170	32	40	32								
	4040R16	△	40	40	200	40	50	32								
CKJNL	2525M16	△	25	25	150	25	32	32	KNUX1604□□L A87	C6L1T				K16CCL		
	3232P16	△	32	32	170	32	40	32								
	4040R16	△	40	40	200	40	50	32								

▲Stock available △Make-to-order

CKNNR/L
Kr:63°

R-type shown



Type		Stock	Basic dimensions(mm)					Applicable inserts	Clamp	Clamp screw	Spring	Clamping stud	Shim	Shim screw	Wrench
			a	b	L	h	s								
CKNNR	2525M16	△	25	25	150	25	14.3	KNUX1604□□R A87	C6R1T	CM6×25A	SPR1 SPR2	P0515	K16CC	SM3×10B	WH20L WH40L
	3232P16	△	32	32	170	32	16.8								
CKNNL	2525M16	△	25	25	150	25	14.3	KNUX1604□□L A87	C6L1T	CM6×25A	SPR1 SPR2	P0515	K16CCL	SM3×10B	
	3232P16	△	32	32	170	32	16.8								

▲Stock available △Make-to-order

Corresponding tool holders of insert RC/P□□ C-type clamping

CRDCR/L
CRDPR/L



R-type shown



Type		Stock		Basic dimensions(mm)						Applicable inserts	Clamp	Clamping screw	Wrench	Shim
		R	L	a	b	L	h	s	Ar					
CRDCR/L	**2525M09V-19**	△	△	25	25	150	25	25.5	19	RCGN0907□□ A152	C3RH	M5*16(GB70-85)	WH40L	RC09XC
	3232P09V-28	△	△	32	32	170	32	32.5	28					
	4040S09V-38	△	△	40	40	250	40	40.5	38					
	2525M12V-19	△	△	25	25	150	25	25.5	19	RCGN1207□□ A152	C4RH	M6*20(GB70-85)	WH50L	RC12XC
	3232P12V-28	△	△	32	32	170	32	32.5	28					
	4040S12V-38	△	△	40	40	250	40	40.5	38					
CRDPR/L	**2525M09V-19**	△	△	25	25	150	25	25.5	19	RPGN0907□□ A152	C3RH	M5*16(GB70-85)	WH40L	RP09XC
	3232P09V-28	△	△	32	32	170	32	32.5	28					
	4040S09V-38	△	△	40	40	250	40	40.5	38					
	2525M12V-19	△	△	25	25	150	25	25.5	19	RPGN1207□□ A152	C4RH	M6*20(GB70-85)	WH50L	RP12XC
	3232P12V-28	△	△	32	32	170	32	32.5	28					
	4040S12V-38	△	△	40	40	250	40	40.5	38					

▲Stock available △Make-to-order

How to select internal turning tools

Explanation of internal turning tools detailed table

- Listed according to clamping types.

Approach angle of tools

Tools type
The first 4 letters in the type description stands for tool shape and applicatio.

Insert type

Specification chart

Application chart
The arrow shows suitable applications such as internal turning, profiling and end turning, etc.

Corresponding tool holders of insert DN□□ P-type clamping



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S32T-PDPNR/L15-3	▲	▲	40	32	30	300	22	LEM8×21	WH30L	L4	D15AP	SP4
S40U-PDPNR/L15-3	▲	▲	50	40	38	350	27					
S32T-PDPNR/L15	△	△	40	32	30	300	22	LEM8×21	WH30L	L4B	D15AP	SP4
S40U-PDPNR/L15	△	△	50	40	38	350	27					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	DF A61	WGM Wiper A63	DR Double-side A65	HDR A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	PM A63	DR Single-side A65			A122 -A123
	SF A62	DM A64	ER Double-side A65			A123
	EF A62	EM A64	ER Single-side A65			
	NF A62	NM A64	SNR Double-side A65			
	NGF A62		LR Single-side A65			
Tool holder type □□-PDPNR/L15-3	DN□□1504□□	DN□□1504□□	DN□□1504□□		DN□□1504□□	DN□□1504□□
□□-PDPNR/L15	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□

Tool holders with oil hole

Products specification
Including product description, stock (left and right hand), basic dimensions and applicable spare parts.

Applicable inserts
Including applications of inserts, reference page, insert shape and corresponding tool holders.

TURNING A

Internal turning tools

Internal turning tools overview A209

Internal turning tools code key A210-A211

Detailed table of internal turning tools A212-A240

Internal turning Tools by P-type clamping A212-A217

Internal turning tools by S-type clamping A218-A233

Damping internal turning tools and their features A234-A240

Internal turning tools

Name	Feature	62°30′	75°	90°	90°	93°	93°	95°	95°	107°30′
P-type internal turning tools	●The minimum machining diameter is 20mm. ●Applicable inserts are economic negative inserts. ●Hole clamping	PDPN A213	PSKN A215	PTFN A216			PDUN A214		PCLN A212	
									PWLN A217	
S-type internal turning tools	●The minimum machining diameter is 10mm. ●Applicable inserts are 5°, 7° and 11° positive inserts. ●Screw clamping.		SSKC A222	SCFC A232	STFC A223	STUP A231	SDUC A220	SDZC A221		SDQC A219
							SDUP A230		SCLC A218	SDQP A229
							SVUC A225		SVUB A233	SVQB A226
							SVUB A227		SCLP A228	SVQC A224
Damping internal turning tools	●The minimum diameter can be machined is 12mm. ●Applicable inserts are 7°、11° positive inserts. ●Good Performance on reducing shake.					STUP A238	SDUP A237		SCLP A235	SDQP A236
							SVUC A240			SVQC A239

Internal turning tools code key

Type of tool holder

Code	Type
A	Steel tool holder with oil-hole
C	Cemented carbide tool holder
E	Cemented carbide tool holder with oil hole
S	Steel tool holder
X	Special inserts applied

Diameter of tool holder



Code	Diameter
08	08
10	10
16	16
20	20
25	25
32	32
40	40
50	50

Length of tool holder



Code	Length
H	100
K	125
M	150
N	160
Q	180
R	200
S	250
T	300
U	350
V	400

Clamping system

P-Hole clamping

M-Top and hole clamping

S-Screw on

C-Top clamping

Inserts shape



S **16** **R** - **S** **D** **U**

Tool holder style and approach angle



Clearance angle of insert	
	B
	C
	D
	E
	N
	P

Cutting direction	
	L - Left hand
	R - Right hand

Manufacture option	
D	Increase offset f size+1.0mm
E	Increase offset f size+2.0mm
R	Round shank
W	Wedge clamping
X	Back boring

Length of cutting edge							
Inserts shape	C	D	R	S	T	V	W
							
Inscribed circle	Length of cutting edge(mm)						
5.556	---	---	---	---	09	---	---
6.350	06	07	---	---	11	---	---
9.525	09	11	09	09	16	16	06
12.700	12	15	12	12	22	22	08
15.875	16	19	15	15	27	---	---
19.050	19	---	19	19	33	---	---
25.400	25	---	25	25	44	---	---

Corresponding tool holders of insert CN□□ P-type clamping

PCLNR/L

Kr:95°



R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S16Q-PCLNR/L09	△	△	20	16	15	180	10	LEM5×12	WH20L	L3C	---	---
S20R-PCLNR/L09	△	△	25	20	19	200	12.5					
S25S-PCLNR/L09	△	△	32	25	24	250	15					
S25S-PCLNR/L12	△	△	32	25	24	250	16	LEM6×14	WH25L	L4A	---	---
S32T-PCLNR/L12	▲	▲	40	32	30	300	21	LEM8×21	WH30L	L4	C12APB	SP4
S40U-PCLNR/L12	▲	▲	50	40	38	350	26					
S50V-PCLNR/L12	▲	▲	63	50	48	400	31					
S50V-PCLNR/L16	△	△	63	50	48	400	31	LEM8×25	WH30L	L5	C16AP	SP5
S50S-PCLNR/L19	△	△	63	50	47	250	35	LEM10×27	WH40L	L6	C19AP	SP6
S50W-PCLNR/L19	▲	▲	63	50	47	450	35					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**DF** A54	**WGM** Wiper A55	**DR** Double-side A58	**HDR** A59	Without chipbreaker A59	A118
	WGF Wiper A54	**PM** A55	**DR** Single-side A58	**HPR** A59		A118 -A119
	SF A54	**DM** A56	**ER** Double-side A58			A119
	EF A54	**EM** A56	**ER** Single-side A58			
	NF A55	**NM** A57	**SNR** Double-side A58			
			LR Single-side A57			

Tool holder type							
	□□-PCLNR/L09	CN□□0903□□	CN□□0903□□				
	□□-PCLNR/L12	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□	CN□□1204□□
	□□-PCLNR/L16	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□	CN□□1606□□	
	□□-PCLNR/L19		CN□□1906□□	CN□□1906□□	CN□□1906□□	CN□□1906□□	

Corresponding tool holders of insert DN□□ P-type clamping

PDPNR/L

Kr:62°30'

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S32T-PDPNR/L15-3	▲	▲	40	32	30	300	22	LEM8×21	WH30L	L4	D15AP	SP4
S40U-PDPNR/L15-3	▲	▲	50	40	38	350	27					
S32T-PDPNR/L15	△	△	40	32	30	300	22	LEM8×21	WH30L	L4B	D15AP	SP4
S40U-PDPNR/L15	△	△	50	40	38	350	27					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**DF** A61	**WGM** Wiper A63	**DR** Double-side A65	**HDR** A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	**PM** A63	**DR** Single-side A65			A122 -A123
	SF A62	**DM** A64	**ER** Double-side A65			A123
	EF A62	**EM** A64	**ER** Single-side A65			
	NF A62	**NM** A64	**SNR** Double-side A65			
	NGF A62		**LR** Single-side A65			
Tool holder type **□□-PDPNR/L15-3**	DN□□1504□□	DN□□1504□□	DN□□1504□□		DN□□1504□□	DN□□1504□□
□□-PDPNR/L15	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□

Corresponding tool holders of insert DN□□ P-type clamping

PDUNR/L

Kr:93°



R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S20R-PDUNR/L11	△	△	25	20	19	200	13	LEM5×12	WH20L	L3D	---	---
S25S-PDUNR/L11	△	△	32	25	24	250	17					
S32T-PDUNR/L15	△	△	40	32	30	300	23	LEM8×21	WH30L	L4B	D15AP	SP4
S32T-PDUNR/L15-3	△	△	40	32	30	300	23	LEM8×21	WH30L	L4	D15AP	SP4
S40U-PDUNR/L15	△	△	50	40	38	350	27	LEM8×21	WH30L	L4B	D15AP	SP4
S40U-PDUNR/L15-3	▲	▲	50	40	38	350	27	LEM8×21	WH30L	L4	D15AP	SP4

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**DF** A61	**WGM** Wiper A63	**DR** Double-side A65	**HDR** A66	Without chipbreaker A66	A121 -A122
	WGF Wiper A61	**PM** A63	**DR** Single-side A65			A122 -A123
	SF A62	**DM** A64	**ER** Double-side A65			A123
	EF A62	**EM** A64	**ER** Single-side A65			
	NF A62	**NM** A64	**SNR** Double-side A65			
	NGF A62		**LR** Single-side A65			

Tool holder type							
	□□-PDUNR/L11	DN□□1104□□	DN□□1104□□		DN□□1104□□		
	□□-PDUNR/L15-3	DN□□1504□□	DN□□1504□□	DN□□1504□□	DN□□1504□□	DN□□1504□□	DN□□1504□□
	□□-PDUNR/L15	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□	DN□□1506□□

Corresponding tool holders of insert SN□□ P-type clamping

PSKNR/L
Kr:75°

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S25S-PSKNR/L12	▲	▲	32	25	24	250	17	LEM6×14	WH25L	L4A	---	---
S32T-PSKNR/L12	△	△	41	32	30	300	22	LEM8×21	WH30L	L4	S12APB	SP4
S40U-PSKNR/L12	△	△	50	40	38	350	27					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For roughing	PCBN/PCD inserts
Inserts shape	**DF** A67	**PM** A68	**DR** Double-side A70	**HDR** A72	Without chipbreaker A74	A126
	EF A67	**DM** A68	**DR** Single-side A70-71	**HPR** A72		A127
	SF A67	**EM** A69	**ER** Double-side A71			A128
		NM A69	**ER** Single-side A71			
			SNR Double-side A71			
			LR Single-side A69			
Tool holder type **□□-PSKNR/L12**	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□	SN□□1204□□

Corresponding tool holders of insert TN□□ P-type clamping

PTFNR/L
Kr:90°

R-type shown





Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S25S-PTFNR/L16	▲	▲	32	25	24	250	16	LEM5×12	WH20L	L3B	---	---
S32T-PTFNR/L16	△	△	41	32	30	300	21	LEM6×17	WH25L	L3	T16APB	SP3
S40U-PTFNR/L16	△	△	50	40	38	350	26					

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For heavy machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**DF** A75	**WGM** Wiper A76	**DR** Double-side A78	**HDR** A79	Without chipbreaker A80	A130
	WG Wiper A75	**PM** A76	**DR** Single-side A78			A130 -A131
	SF A75	**DM** A77	**ER** Double-side A78			A131
	EF A76	**EM** A77	**SNR** Double-side A78			
			LR Single-side A77			
Tool holder type **□□-PTFNR/L16**	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□	TN□□1604□□

Corresponding tool holders of insert WN□□ P-type clamping

PWLNR/L
Kr:95°

R-type shown





Type	Stock		Basic dimensions(mm)					Screw	Wrench	Lever	Shim	Shim pin
	R	L	Dmin	ød	h	L	S					
S16R-PWLNR/L06	△	△	20	16	15	200	10	LEM5X12	WH20L	L3D	---	---
S20R-PWLNR/L06	△	△	25	20	19	200	12			L3B		
S25S-PWLNR/L06	△	△	35	25	24	250	15					
S20R-PWLNR/L08	△	△	23	20	19	200	12.5	LEM6X14	WH25L	L4A	---	---
S25S-PWLNR/L08	△	△	32	25	24	250	16					
S32T-PWLNR/L08	△	△	41	32	30	300	21	LEM8X21	WH30L	L4	W08AP	SP4

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For cast iron machining	PCBN/PCD inserts
Inserts shape	**DF** A83	**WGM** Wiper A84	**DR** Double -side A86	Without chipbreaker A86	A136
	WGF Wiper A83	**PM** A85	**SNR** Double -side A86		A136 -A137
	SF A83	**DM** A85			A137
	EF A84	**EM** A85			
	NF A84	**NM** A86			
Tool holder type **□□-PWLNR/L06**	WN□□0604□□	WN□□0604□□	WN□□0604□□	WN□□0604□□	
□□-PWLNR/L08	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□	WN□□0804□□

Corresponding tool holders of insert CC□□ S-type clamping

SCLCR/L

Kr:95°



R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S08K-SCLCR/L06	▲	▲	10	8	7.4	125	5	I60M2.5×5.5	WT07IP	---	---
S10K-SCLCR/L06	▲	▲	13	10	9	125	6.5				
S12M-SCLCR/L06	▲	▲	16	12	11	150	9				
S12M-SCLCR/L09	▲	▲	16	12	11	150	9	I60M3.5×8	WT15IP	---	---
S14N-SCLCR/L09	△	△	18	14	13	160	9				
S16Q-SCLCR/L09	△	△	20	16	15	180	10				
S20R-SCLCR/L09	△	△	25	20	19	200	12	I60M3.5×10			
S25S-SCLCR/L09	△	△	32	25	24	250	15.5		WT15IP	---	---
S20R-SCLCR/L12	△	△	25	20	19	200	12.5	I60M4×11X	WT15IP	---	---
S25S-SCLCR/L12	▲	▲	32	25	24	250	15.5	I60M4×11X	WT15IP	---	---
S32T-SCLCR/L12	△	△	39	32	30	300	20	I60M4×11X	WH40L WT15IP	C12BS	SM6×10×A
S40U-SCLCR/L12	△	△	50	40	38	350	24.5				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**USF** A89	**HF** A89	**HM** A90	**HR** A91	**LH** A91-92	Without chipbreaker A92	A139
	SF A89	**EF** A90	**EM** A90		**LC** A91		A144
Tool holder type **□□-SCLCR/L06**	CC□□0602□□	CC□□0602□□	CC□□0602□□	CC□□0602□□	CCGX0602□□	CC□□0602□□	CC□□0602□□
□□-SCLCR/L09	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CCGX09T3□□	CC□□09T3□□	CC□□09T3□□
□□-SCLCR/L12		CC□□1204□□	CC□□1204□□	CC□□1204□□	CCGX1204□□	CC□□1204□□	CC□□1204□□

Corresponding tool holders of insert DC□□ S-type clamping

SDQCR/L
Kr:107°30'

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S			---	---
S10K-SDQCR/L07	▲	▲	13	10	9	125	7	I60M2.5×5.5	WT07IP	---	---
S12M-SDQCR/L07	▲	▲	16	12	11	150	9	I60M2.5×6.5			
S16Q-SDQCR/L07	△	△	20	16	15	180	11				
S20R-SDQCR/L11	△	△	25	20	19	200	13	I60M3.5×8	WT15IP	---	---
S25S-SDQCR/L11	△	△	32	25	24	250	17	I60M3.5×10			
S32T-SDQCR/L11	△	△	40	32	30	300	22				
S40T-SDQCR/L11	△	△	50	40	38	350	27				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**USF** A93	**HF** A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
	SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type **□□-SDQCR/L07**	DC□□0702□□	DC□□0702□□	DC□□0702□□		DCGX0702□□	DC□□0702□□	DC□□0702□□
□□-SDQCR/L11	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DCGX11T3□□	DC□□11T3□□	DC□□11T3□□

Corresponding tool holders of insert DC□□ S-type clamping

SDUCR/L

Kr:93°

R-type shown





Type	Stock		Basic dimensions(mm)					Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S			---	---
S10K-SDUCR/L07	▲	▲	13	10	9	125	7	I60M2.5×5.5	WT07IP	---	---
S12M-SDUCR/L07	▲	▲	16	12	11	150	9	I60M2.5×6.5			
S16Q-SDUCR/L07	△	△	20	16	15	180	11				
S20R-SDUCR/L11	△	△	25	20	19	200	13	I60M3.5×8	WT15IP	---	---
S25S-SDUCR/L11	△	△	32	25	24	250	17	I60M3.5×10			
S32T-SDUCR/L11	△	△	40	32	30	300	22				
S40U-SDUCR/L11	△	△	50	40	38	350	27				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**USF** A93	**HF** A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
	SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type **□□-SDUCR/L07**	DC□□0702□□	DC□□0702□□	DC□□0702□□		DCGX0702□□	DC□□0702□□	DC□□0702□□
□□-SDUCR/L11	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DCGX11T3□□	DC□□11T3□□	DC□□11T3□□

Corresponding tool holders of insert DC□□ S-type clamping

SDZCR/L

Kr:95°



R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S25S-SDZCR/L11	△	△	33	25	24	250	18	I60M3.5×10	WT15IP	---	---
S32T-SDZCR/L11	△	△	40	32	30	300	22	I60M3.5×12	WT15IP WH35L	D11BS	SM5×8.65XA
S40U-SDZCR/L11	△	△	48	40	38	350	27				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**USF** A93	**HF** A93	**HM** A94	**HR** A95	**LH** A95	Without chipbreaker A95	A140
	SF A93	**EF** A94	**EM** A94		**LC** A95		A145
Tool holder type **□□-SDZCR/L11**	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DC□□11T3□□	DCGX11T3□□	DC□□11T3□□	DC□□11T3□□

Corresponding tool holders of insert SC□□ S-type clamping

SSKCR/L

Kr:75°

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S12M- SSKCR/L09	▲	△	16	12	11	150	9	I60M3.5×8	WT15IP	---	---
S16Q- SSKCR/L09	△	△	20	16	15	180	11				
S20R- SSKCR/L09	△	△	25	20	19	200	13				
S25S- SSKCR/L12	△	△	32	25	24	250	17	I60M4×11X	WT15IP	---	---
S32T- SSKCR/L12	△	△	40	32	30	300	22		WT15IP WH40L	S12BS	SM6×10XA

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining
Inserts shape	**HF** A98	**HM** A98	**HR** A99	**LH** A99	Without chipbreaker A99
	EF A98	**EM** A98		**LC** A99	
Tool holder type **□□-SSKCR/L09**	SC□□09T3□□	SC□□09T3□□	SC□□09T3□□	SCGX09T3□□	SC□□09T3□□
□□-SSKCR/L12		SC□□1204□□	SC□□1204□□	SCGX1204□□	SC□□1204□□

Corresponding tool holders of insert TC□□ S-type clamping

STFCR/L
Kr:90°

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S12M-STFCR/L11	▲	▲	16	12	11	150	9	I60M2.5×6.5	WT07IP	---	---
S16Q-STFCR/L11	△	△	20	16	15	180	10				
S20R-STFCR/L11	△	△	25	20	19	200	12				
S25S-STFCR/L16	△	△	32	25	24	250	16	I60M3.5×10	WT15IP	---	---
S32T-STFCR/L16	△	△	40	32	30	300	21	I60M3.5×12	WT15IP WH35L	T16BS	SM5×8.65XA
S40U-STFCR/L16	△	△	50	40	38	350	25				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**HF** A101	**HM** A103	**HR** A103	**LH** A104	Without chipbreaker A104	A141
	EF A102	**EM** A102		**LC** A103		
Tool holder type **□□-STFCR/L11**	TC□□1102□□	TC□□1102□□	TC□□1102□□	TCGX1102□□	TC□□1102□□	TC□□1102□□
□□-STFCR/L16	TC□□16T3□□	TC□□16T3□□	TC□□16T3□□	TCGX16T3□□	TC□□16T3□□	TC□□16T3□□

Corresponding tool holders of insert VC□□ S-type clamping

SVQCR/L
Kr:107°30'

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S16Q-SVQCR/L11	▲	▲	22	16	15	180	13	I60M2.5×6.5	WT07IP	---	---
S20R-SVQCR/L16	△	△	27	16	19	200	14	I60M3.5×12	WT15IP WH35L	V16BSC	SM5×8.65×A
S25S-SVQCR/L16	△	△	35	25	24	250	20				
S32T-SVQCR/L16	△	△	42	32	30	300	23				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For Al machining	PCBN/PCD inserts
Inserts shape	**USF** A105	**HF** A105	**LH** A106	A143
	SF A105	**NF** A105	**LC** A106	A148
Tool holder type **□□-SVQCR/L11**	VC□□1103□□	VC□□1103□□	VCGX1103□□	
□□-SVQCR/L16		VC□□1604□□	VCGX1604□□	VC□□1604□□

Corresponding tool holders of insert VC□□ S-type clamping

SVUCR/L
Kr:93°

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S16Q-SVUCR/L11	△	△	24	16	15	180	15	I60M2.5×6.5	WT07IP	---	---
S20R-SVUCR/L11	△	△	28	20	19	200	17				
S25S-SVUCR/L16	△	△	35	25	24	250	20	I60M3.5×12	WT15IP		
S32T-SVUCR/L16	△	△	42	32	30	300	23		WT15IP WH35L	V16BS	SM5×8.65×A

▲Stock available △Make-to-order



Applicable inserts

Application	For extra finishing	For finishing	For Al machining	PCBN/PCD inserts
Inserts shape	**USF** A105	**HF** A105	**LH** A106	A143
	SF A105	**NF** A105	**LC** A106	A148
Tool holder type **□□-SVUCR/L11**	VC□□1103□□	VC□□1103□□	VCGX1103□□	
□□-SVUCR/L16		VC□□1604□□	VC□□1604□□	VC□□1604□□

Corresponding tool holders of insert VB□□ S-type clamping

SVQBR/L
Kr:107°30'



R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S20R-SVQBR/L16	△	△	27	20	19	200	14	I60M3.5×12	WT15IP WH35L	V16BS	SM5×8.65XA
S25S-SVQBR/L16	△	△	35	25	24	250	20				
S32T-SVQBR/L16	▲	▲	42	32	30	300	23				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	PCBN/PCD inserts
Inserts shape	**EF** A108	**HM** A109	**HR** A109	A147
	NF A108	**EM** A109	**SNR** A109	A147
	NGF A108			
Tool holder type **□□-SVQBR/L16**	VB□□1604□□	VB□□1604□□	VB□□1604□□	VB□□1604□□

Corresponding tool holders of insert VB□□ S-type clamping

SVUBR/L
Kr:93°

R-type shown



Type	Stock		Basic dimensions(mm)					Screw	Wrench	Shim	Shim screw
	R	L	Dmin	ød	h	L	S				
S25S- SVUBR/L16	△	△	35	25	24	250	20	I60M3.5×12	WT15IP WH35L	V16BS	SM5×8.65XA
S32T-SVUBR/L16	△	△	42	32	30	300	23				

▲Stock available △Make-to-order

Applicable inserts

Application	For finishing	For semi-finishing	For roughing	PCBN/PCD inserts
Inserts shape	**EF** A108	**HM** A109	**HR** A109	A147
	NF A108	**EM** A109	**SNR** A109	A147
	NGF A108			
Tool holder type: **□□-SVUBR/L16**	VB□□1604□□	VB□□1604□□	VB□□1604□□	VB□□1604□□

Corresponding tool holders of insert CP□□ S-type clamping

SCLPR/L

Kr:95°

R-type shown





Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S	θ	e			---	---
S10K-SCLPR/L06	▲	▲	12	10	9	125	6	-7°	17	I60M2.5×5.5	WT07IP	---	---
S12M-SCLPR/L06	▲	▲	16	12	11	150	8	-4°	20				
S16Q-SCLPR/L09	▲	▲	20	16	15	180	10	-4°	29	I60M3.5×8	WT15IP	---	---
S20R-SCLPR/L09	△	△	25	20	18	200	13	-4°	35				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	SF A110
Tool holder type **□□-SCLPR/L06**	CP□□0602□□
Tool holder type **□□-SCLPR/L09**	CP□□09T3□□

Corresponding tool holders of insert DP□□ S-type clamping

SDQPR/L

Kr:107°30'

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S	θ	e			---	---
S10K-SDQPR/L07	△	△	13	10	9	125	7	-8°	20	I60M2.5×5.5	WT07IP	---	---
S12M-SDQPR/L07	▲	△	16	12	11	150	9	-8°	22				
S16Q-SDQPR/L07	▲	△	20	16	15	180	11	-6°	27	I60M2.5×6.5			
S16Q-SDQPR/L11	▲	△	20	16	15	180	11	-6°	32	I60M3.5×8	WT15IP	---	---
S16Q-SDQPR/L11	△	△	25	20	18	200	13	-6°	33				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	**USF** A111
	SF A111
Tool holder type **□□-SDQPR/L07**	DP□□0702□□
Tool holder type **□□-SDQPR/L11**	DP□□11T3□□

Corresponding tool holders of insert DP□□ S-type clamping

SDUPR/L

Kr:93°



R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S	θ	e			---	---
S10K-SDUPR/L07	▲	▲	15	10	9	125	9	-8°	18	I60M2.5×5.5	WT07IP	---	---
S12M-SDUPR/L07	▲	△	16	12	11	150	9	-8°	19				
S16Q-SDUPR/L07	△	△	20	16	15	180	11	-6°	25	I60M2.5×6.5			

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	SF A111
Tool holder type □□-SDUPR/L07	DP□□0702□□

Corresponding tool holders of insert TP□□ S-type clamping

STUPR/L
Kr:93°

R-type shown





Type	Stock		Basic dimensions(mm)					Screw	Wrench	---	---
	R	L	Dmin	ød	h	L	S			---	---
S10M-STUPR/L09	△	△	13	10	9.4	150	6	I60M2.2×5.5	WT07IP	---	---
S10M-STUPR/L11	△	△	13	10	9.4	150	6				
S12Q-STUPR/L11	△	△	16	12	11.4	180	7.5	I60M2.5×6.5	WT07IP	---	---
S16R-STUPR/L11	△	△	20	16	15	200	10				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	**SF** A113
Tool holder type □□-STUPR/L09	TP□□0902□□
Tool holder type □□-STUPR/L11	TP□□1103□□

Corresponding tool holders of insert CC□□ S-type clamping

SCFCR/L

Kr:90°

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	L	s	a	b	e			---	---
S10M-SCFCR/L06S25	▲	▲	13	10	150	7	27	25	30	I60M2.5×5.5	WT07IP	---	---
S12P -SCFCR/L06S25	▲	▲	16	12	170	9	27	25	35	I60M2.5×6.5			
S16Q-SCFCR/L09S25	▲	▲	20	16	180	11	27	25	40	I60M3.5×8	WT15IP	---	---
S20R-SCFCR/L09S25	△	△	25	20	200	13	27	25	45				
S25R-SCFCR/L12S25	△	△	30	25	200	16	27	25	50	I60M4×11X		---	---

▲Stock available △Make-to-order

Applicable inserts

Application		For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape		**USF** A89	**HF** A89	**HM** A90	**HR** A91	**LH** A91-92	Without chipbreaker A92	A139
		SF A89	**EF** A90	**EM** A90		**LC** A91		A144
Tool holder type	**□□-SCFCR/L06S25**	CC□□0602□□	CC□□0602□□	CC□□0602□□	CC□□0602□□	CCGX0602□□	CC□□0602□□	CC□□0602□□
	□□-SCFCR/L09S25	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CCGX09T3□□	CC□□09T3□□	CC□□09T3□□
	□□-SCFCR/L12S25		CC□□1204□□	CC□□1204□□	CC□□1204□□	CCGX1204□□	CC□□1204□□	CC□□1204□□

Corresponding tool holders of insert CC□□ S-type clamping

SCLCR/L
Kr:95°

R-type shown





Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	L	s	a	b	e			---	---
S10M-SCLCR/L06S20	▲	▲	13	10	150	7	22	20	30	I60M2.5×5.5	WT07IP	---	---
S12P -SCLCR/L06S20	▲	▲	16	12	170	9	22	20	35				
S16Q-SCLCR/L09S20	▲	▲	20	16	180	11	22	20	40	I60M3.5×8	WT15IP	---	---
S20R-SCLCR/L09S20	△	△	25	20	200	13	22	20	60				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For semi-finishing	For roughing	For Al machining	For cast iron machining	PCBN/PCD inserts
Inserts shape	**USF** A89	**HF** A89	**HM** A90	**HR** A91	**LH** A91-92	Without chipbreaker A92	A139
	SF A89	**EF** A90	**EM** A90		**LC** A91		A144
Tool holder type **□□-SCLCR/L06S20**	CC□□0602□□	CC□□0602□□	CC□□0602□□	CC□□0602□□	CCGX0602□□	CC□□0602□□	CC□□0602□□
□□-SCLCR/L09S20	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CC□□09T3□□	CCGX09T3□□	CC□□09T3□□	CC□□09T3□□



Damping tool holders for internal turning

Technical features

Increasing material rigidity of tool holder can reduce the amplitude, or obtain larger overhang under the condition of same systemic stability. Therefore, compared with steel tool holder, cemented carbide tool holder has better dampening effect, smaller amplitude and reaches convergence point sooner. As for machining under the condition of long overhang and easy vibration, they can exert excellent performance and achieve higher dimensional accuracy and surface quality.

Under the same machining condition

the maximum overhang of cemented carbide tool holder can reach L≤6D, while the recommended maximum overhang of steel tool holder is L≤3D.



Steel tool holder



Cemented carbide tool holder

Corresponding tool holders of insert CP□□ (Damping tool holder) S-type clamping

SCLPR/L

Kr:95°

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C10M-SCLPR/L06	▲	△	12	10	6	150	17	9	-7°	I60M2.5×5.5	WT07IP	--	--
C12Q-SCLPR/L06	△	△	16	12	8	180	20	11	-4°				
C16R-SCLPR/L09	▲	△	20	16	10	200	29	15	-4°	I60M3.5×8	WT15IP	--	--
C20S-SCLPR/L09	△	△	25	20	13	250	35	18	-4°				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	**SF** A110
Tool holder type **□□-SCLPR/L06**	CP□□0602□□
Tool holder type **□□--SCLPR/L09**	CP□□09T3□□

Corresponding tool holders of insert DP□□ (Damping tool holder) S-type clamping

SDQPR/L

Kr:107°30'

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C10M-SDQPR/L07	▲	△	13	10	7	150	20	9	-8°	I60M2.5×5.5	WT07IP	---	---
C12Q-SDQPR/L07	△	△	16	12	9	180	22	11	-8°				
C16R-SDQPR/L07	△	△	20	16	11	200	27	15	-6°	I60M2.5×6.5			
C16R-SDQPR/L11	△	△	20	16	11	200	32	15	-6°	I60M3.5×8	WT15IP	---	---
C20S-SDQPR/L11	▲	△	25	20	13	250	33	18	-6°				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	**SF** A111
Tool holder type □□-**SDQPR/L07**	DP□□0702□□
Tool holder type □□-**SDQPR/L11**	DP□□11T3□□

Corresponding tool holders of insert DP□□ (Damping tool holder) S-type clamping

SDUPR/L

Kr:93°

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C10M-SDUPR/L07	△	△	15	10	9	150	18	9	-8°	I60M2.5×5.5	WT07IP	---	---
C12Q-SDUPR/L07	△	△	16	12	9	180	19	11	-8°	I60M2.5×6.5		---	---
C16R-SDUPR/L07	△	△	20	16	11	200	25	15	-6°			---	---

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	**SF** A111
Tool holder type □□-SDUPR/L07	DP□□0702□□

Corresponding tool holders of insert TP□□ (Damping tool holder) S-type clamping

STUPR/L

Kr:93°

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C10M-STUPR/L09	▲	△	12	10	6	150	20	9	-6°	I60M2.2×5.5	WT07IP	---	---
C12Q-STUPR/L09	▲	△	16	12	8	180	22	11	-4°				
C12Q-STUPR/L11	▲	△	16	12	8	180	25	11	-4°	I60M2.5×6.5	WT07IP	---	---
C16R-STUPR/L11	▲	△	20	16	10	200	27	15	-3°				

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing
Inserts shape	SF A113
Tool holder type □□-STUPR/L09	TP□□0902□□
Tool holder type □□-STUPR/L11	TP□□1103□□

Corresponding tool holders of insert VC□□(Damping tool holder) S-type clamping

SVQCR/L

Kr:107°30'

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C16R-SVQCR/L11	△	△	22	16	13	200	28	15	-6°	I60M2.5×6.5	WT07IP	---	---
C20S-SVQCR/L11	△	△	26	20	15	250	32	18	-4°			---	---

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For Al machining
Inserts shape	**USF** A105	**HF** A105	**LH** A106
	SF A105		**LC** A106
Tool holder type **□□-SVQCR/L11**	VC□□1103□□	VC□□1103□□	VCGX1103□□

Corresponding tool holders of insert VC□□ (Damping tool holder) S-type clamping

SVUCR/L

Kr:93°

R-type shown



Type	Stock		Basic dimensions(mm)							Screw	Wrench	---	---
	R	L	Dmin	ød	s	L_1	L_2	h	θ			---	---
C16R-SVUCR/L11	△	△	24	16	15	200	25	15	-6°	I60M2.5×6.5	WT07IP	---	---
C20S-SVUCR/L11	△	△	28	20	17	250	30	18	-4°			---	---

▲Stock available △Make-to-order

Applicable inserts

Application	For extra finishing	For finishing	For Al machining
Inserts shape	**USF** A105	**HF** A105	**LH** A106
	SF A105		**LC** A106
Tool holder type **□□-SVUCR/L11**	VC□□1103□□	VC□□1103□□	VCGX1103□□

Table of recommended cutting parameters for general turning

ISO	Materials		Hardness HB	CVD Coating						PVD Coating			Cermet	Coated cermet	Cemented carbide	
				YBC151	YBC251	YBC152	YBC252	YBC351	YBC352	YBG102	YBG202	YBG302	YNG151	YNG151C	YC10	YC40
				Feed rate (mm/rev)												
				0.1-0.6	0.1-0.8	0.1-0.6	0.1-0.8	0.2-1.0	0.2-1.0	0.2-0.4	0.1-0.6	0.05-0.8	0.05-0.2	0.05-0.2	0.1-0.4	0.1-0.5
				Cutting speed (m/min)												
P	Carbon steel	C=0.15%	125	430-200	430-190	500-270	480-240	380-165	430-220	460-220	380-180	360-165	550-350	580-350	360-165	300-145
		C=0.35%	150	380-180	410-180	460-250	460-230	300-150	350-200	440-210	300-170	280-150	500-300	520-300	280-150	220-130
		C=0.60%	200	330-150	350-150	400-220	400-200	260-130	310-180	380-180	260-150	240-130	460-260	480-260	240-130	180-80
	Alloy steel	Anneal	180	350-170	350-150	400-180	400-200	200-100	250-150	380-180	200-120	180-100	410-240	430-240	180-100	160-80
		Hardened	275	230-100	210-100	280-150	260-140	140-70	200-120	240-120	140-90	120-70	300-180	320-180	120-70	120-50
		Hardened	300	210-100	190-70	260-150	240-120	125-60	180-110	220-100	125-80	100-60	250-170	270-170	100-60	80-40
		Hardened	350	180-80	170-70	230-120	220-120	110-55	160-100	200-100	110-75	90-55	230-150	250-150	90-55	70-45
	High alloy steel	Anneal	200	320-150	260-120	360-190	310-170	175-80	220-130	290-150	175-100	155-80	350-200	370-200	155-80	135-60
		Hardene	325	140-90	100-50	190-130	150-100	85-40	140-90	130-80	85-60	65-40	170-110	190-110	65-40	45-30
	Cast steel	Non-Alloy	180	240-120	200-100	280-160	250-140	135-75	190-130	230-125	135-95	115-75	260-170	280-170	115-75	95-55
		Low alloy	200	230-70	170-60	280-110	220-110	120-80	170-130	200-90	120-100	100-80	260-170	280-170	100-80	80-60
		High alloy	225	160-70	140-50	210-110	190-100	95-55	150-110	170-80	95-55	95-55	260-100	280-100	95-55	75-35

ISO	Materials		Hardness HB	CVD Coating				PVD Coating				Cermet	Coated cermet
				YBM151	YBM153	YBM251	YBM253	YBM215	YBG202	YBG205	YBG302	YNG151	YNG151C
				Feed rate (mm/rev)									
				0.2-0.6	0.2-0.6	0.2-0.6	0.2-0.6	0.2-0.4	0.1-0.4	0.2-0.4	0.2-0.6	0.1-0.3	0.1-0.3
				Cutting speed (m/min)									
M	Stainless steel	Ferrite	180	280-180	280-180	250-140	260-140	290-190	300-190	290-190	250-150	330-220	350-210
		Austenite	260	250-150	250-150	200-110	210-110	240-160	250-160	240-160	220-120	250-150	270-140
		Martensite	330	200-140	200-140	210-130	220-130	250-170	260-170	250-170	210-120	270-170	290-160

Recommended table of cutting parameters for general turning

ISO	Materials		Hardness HB	CVD Coating				Cermet	Coated cermet	Ceramics	Cemented carbide	
				YBD052	YBD102	YBD152	YBD252	YNG151	YNG151C	CN3100	YC10	YC40
				Feed rate (mm/rev)								
				0.1-0.4	0.1-0.4	0.1-0.5	0.1-0.8	0.1-0.4	0.1-0.4	0.1-1.5	0.1-0.3	0.1-0.4
				Cutting speed (m/min)								
K	Malleable cast iron	Ferrite	130	350-230	330-220	320-105	250-170	280-160	300-180	800-600	150-90	105-45
		Pearlite	230	250-105	230-100	230-100	180-75	220-120	240-150	700-500	120-70	80-30
	Low cast iron		180	520-200	480-200	480-190	380-150	400-250	420-270	700-500	170-100	130-60
	High cast iron		260	230-120	220-115	210-100	170-90	360-240	380-260	800-600	130-70	95-40
	Nodular cast iron	Ferrite	160	310-150	300-150	290-140	220-110	330-190	350-210	600-450	140-80	115-45
		Pearlite	250	230-110	220-105	210-100	170-90	310-200	330-220	500-350	110-70	80-30

ISO	Materials		Hardness HB	PVD Coating					Cemented carbide	Ceramics
				YBG102	YBG105	YBG202	YBS103	YBG212	YD101	CN3100
				Feed rate (mm/rev)						
				0.05-0.15	0.05-0.15	0.05-0.2	0.05-0.2	0.05-0.2	0.05-0.35	0.05-0.2
				Cutting speed (m/min)						
N	Al alloy	No heat treatment	60						1750-800	
		Heat treatment	100						510-250	
	Cast aluminum alloy	No heat treatment	75						460-175	
		Heat treatment	90						300-110	
	Copper alloy	Lead alloy	110						610-205	
		Copper, pure copper	90						310-195	
		Copper, nonleaded Copper, electrolytic copper	100						225-115	
S	Ni-base alloy	Ni-base alloy	40	90-30	90-40	90-30	90-20	90-30	70-20	15-260

Recommended table of cutting parameters for general turning

ISO	Materials	PCBN											
		BK1011	BK1021	BK2511	BK2541	BH0121	BH1020	BH2011	BH2511	BH3511	BS1011	BS2011	BS3011
		Feed rate (mm/rev)											
		0.02-0.5		0.1-0.5		0.05-0.5				0.05-0.25			
		Cutting speed (m/min)											
K	Gray cast iron	400-1500		300-600									
K	Hard cast iron	80-160		50-150									
S	Powder metallurgy and high temperature alloys										70-180	100-200	50-160
H	Hardened steel					150-250	140-220	100-170	120-180	80-150			

ISO	Materials	PCD			
		DN0121	DN0511	DN1021	DN3021
		Feed rate (mm/rev)			
		0.05~0.4			
		Cutting speed (m/min)			
N	Silumin (si≤12%)	500~1000	900~3500	400~1200	300~700
N	fibre reinforced composite materials	200~1000			
N	Metal base compound		1500~1800		
N	Coppeer and magnesium alloyssilumin		400~1260	400~1260	
N	Cemented carbide		20~40		
N	Unsintered ceramic materials				100~200
N	Sintered Ceramic				20~50

Table of correctional cutting parameters of internal turning

Internal turning tools by P-type clamping

Workpiece material		Hardness HB	Machining category	L/D≤3		L/D=3-4 (Diameter of shank≥Φ16mm)	
				Feed rate (mm/rev)	Cutting depth (mm)	Feed rate (mm/rev)	Cutting depth (mm)
P	Carbon steel, Alloy steel 45#, 42CrMo	HB180—280	For semi-finishing	0.1-**0.25**-0.4	<5.0	0.1-**0.2**-0.3	<4.0
M	Stainless steel 1Cr18Ni9Ti 0Cr18Ni9	≤HB220	For semi-finishing	0.1-**0.2**-0.3	<4.0	0.1-**0.15**-0.25	<3.0
K	Cast iron HT250	HB170—230	For semi-finishing	0.1-**0.25**-0.4	<5.0	0.1-**0.2**-0.3	<4.0

Internal turning tools by S-type clamping

Workpiece material		Hardness HB	Machining category	L/D≤3		L/D=4		L/D=5		L/D=6	
				Feed rate (mm/rev)	Cutting depth (mm)	Feed rate (mm/rev)	Cutting depth (mm)	Feed rate (mm/rev)	Cutting depth (mm)	Feed rate (mm/rev)	Cutting depth (mm)
P	Carbon steel, Alloy steel 45#, 42CrMo	HB180-280	For finishing	0.05-**0.1**-0.15	<0.2	0.05-**0.1**-0.15	<0.2				
			For semi-finishing	0.15-**0.25**-0.35	<3.0	0.1-**0.15**-0.2	<1.5				
M	Stainless steel 1Cr18Ni9Ti 0Cr18Ni9	≤HB220	For finishing	0.05-**0.1**-0.15	<0.2	0.05-**0.1**-0.15	<0.2				
			For semi-finishing	0.15-**0.2**-0.25	<2.0	0.1-**0.15**-0.2	<1.0				
N	Al alloy	---	For finishing	0.05-**0.1**-0.15	<0.2	0.05-**0.1**-0.15	<0.2	0.05-**0.1**-0.15	-0.15	0.05-**0.1**-0.15	<0.1
			For semi-finishing	0.05-**0.1**-0.15	<2.0	0.05-**0.1**-0.15	<1.5	0.05-**0.1**-0.15	-1.0	0.05-**0.1**-0.15	<1.0

Damping internal turning tools

Workpiece material		Machining conditions	Chipbreaker	Inserts material	Feed rate (mm/rev)	Cutting depth (mm)
P	Steel HB180—280	For finishing	SF	YNG151 YNG151C	0.05-**0.2**-0.35	0.05-**0.1-0.3**-0.5
M	Stainless steel ≤HB220				0.05-**0.2**-0.35	0.05-**0.1-0.3**-0.5
K	Cast iron HB170—230				0.05-**0.2**-0.35	0.05-**0.1-0.3**-0.5

Blue words are recommended cutting parameters.

Frequent problems of turning and solutions

Common problem		Cause	Tool material: Harder materials	Tool material: Tougher materials	Cutting conditions: Cutting speed	Cutting conditions: Feed rate	Cutting conditions: Cutting depth	Cutting conditions: Cutting liquid	Tool shape: Change chipbreaker of inserts	Tool shape: Rake face	Tool shape: Nose radius	Tool shape: Approach angle	Tool shape: Cutting edge strength	Tool shape: Increase precision of inserts	Tool shape: Increase rigidity of tool holder	Machine clamping system: Clamping of tool holder and workpiece	Machine clamping system: Overhang of tool holder	Machine clamping system: Power, gap
Over abrasion on nose	Bad precision during machining	Abrasion intensified on flank	✓								↑							
		Unsuitable cutting conditions			↓	↑												
Surface precision deterioration	Bad surface quality	Abrasion intensified and cutting edge not sharp enough	✓		↓			✓		↑	↑		↓	✓				
		Cutting edge breakage		✓		↓	↓		✓		↑		↑			✓	✓	✓
		Unsuitable geometrical shape of cutting edge							✓		↑		↓	✓				
		Unsuitable cutting conditions			↑	↓	↓	✓										
		Vibration		✓	↑↓	↓	↓	✓	✓	↑	↓	↑	↓		✓	✓	✓	✓
		Built-up edge			↑	↑		✓	✓	↑			↓	✓				
Radiation	Effect of cutting heat	Unsuitable cutting conditions			↓	↓	↓											
		Unsuitable geometrical shape of cutting edge	✓						✓	↑			↓					
Bad precision of dimensions	Dimensions fluctuate during cutting	Insert tolerance												✓				
		Offset of workpiece or tools							✓	↑	↓	↑			✓	✓	✓	✓
Breakage	Abrasion on flank and rake face	Abrasion on clearance face	✓		↓				✓	↑	↑		↓					
		Abrasion on rake face	✓		↓	↓	↓		✓	↑		↓						
	Edge chipping	Vibration and impact		✓		↓	↓		✓			↓	↑		✓	✓	✓	✓
	Built-up edge	Unsuitable workpiece hardness for cutting conditions			↑	↑		✓	✓	↑			↓	✓				
	Thermal cracking	Hardness of workpiece material and tool material unsuitable for cutting conditions			↓	↓	↓	✓	✓	↑			↓					
	Cutting edge nose deformation	Occurring during intermittent machining with high feed rate	✓		↑	↓	↓	✓	✓	↑	↑	↓	↓					
	Tool life	Unsuitable materials and cutting conditions		✓		↓	↓		✓		↑	↓	↑		✓	✓	✓	✓
Chip controlling	Long, unbroken and snarled chips	Unsuitable cutting condition			↓	↑	↑	✓										
		Unsuitable geometry							✓		↓	↑						
	Too short and hard chips	Unsuitable cutting condition				↓	↓	✓										
		Unsuitable geometrical shape of cutting edge							✓		↑	↓						
Burr and knockdown flange	Steel and Al, burrs occurring	Unsuitable cutting condition			↑	↓		✓										
		Tool abrasion and unsuitable geometrical shape	✓						✓	↑	↓	↑	↓					
	Edge break out on cast iron	Unsuitable cutting conditions			↓	↑		✓										
		Tool abrasion and unsuitable geometrical shape	✓						✓	✓	↓	↓	↓					
	Heavy burr on soft steel	Unsuitable cutting condition				↓	↓											
		Tool abrasion and unsuitable geometrical shape	✓						✓	↑	↑		↑		✓	✓	✓	✓

Abrasion of tools and various damages

Tool damage type	Phenomenon	Cause	Solution
Flank wear	Cutting resistant force increasing Groove wear on flank	Tool material is too soft. Cutting speed is too high. Clearance angle is too small. Feed rate is too low.	◆Select tool materials with good wear resistance. ◆Reduce cutting speed. ◆Enlarge clearance angle. ◆Increase feed rate.
Rake face wear (Crater wear)	Bad chip controlling Surface quality deterioration	Tool material is too soft. Cutting speed is too hig. Feed rate is too high.	◆Select tool materials with good wear resistance. ◆Reduce cutting speed. ◆Reduce feed rate.
Cutting edge breakage	Occasional breakage Instability of tool life	Tool material is too hard. Feed rate is high. Cutting edge strength is not high enough. Rigidity of tool holder and tool bar is small.	◆Select tool materials with good toughness. ◆Reduce feed rate. ◆Increase land width (if rounding changes into chamfering). ◆Enlarge tool bar size.
Breakage	Cutting resistant force increasing Deterioration of surface roughness	Tool material is too hard. Feed rate is high. Cutting edge strength is not high enough. Rigidity of tool holder and tool bar is low.	◆Select tool materials with good toughness. ◆Reduce feed rate. ◆Increase land width (if rounding changes into chamfering). ◆Enlarge tool bar size.
Plastic deformation (Cutting edge collapse)	Workpiece dimensions change Nose abrasion	Tool material is too soft. Cutting speed is too high. Cutting depth and feed rate are too high. Cutting edge temperature is too high.	◆Select tool material with good wear resistance ◆Reduce cutting speed. ◆Reduce cutting depth and feed rate. ◆Select tool materials with good heat conductivity.
Built-up edge (Bonding)	Surface quality deterioration during finishing Cutting resistant force increasing	Cutting speed is low. Cutting edge is not sharp enough. Tool material is unsuitable.	◆Increase cutting speed. ◆Enlarge rake angle. ◆Select tool materials that are not easy to adhere together (coating, cermet, etc.)
Thermal cracking	Damage because of thermal circulation Normally occurring during intermittent machining	Premature edge failure due to thermal cracks. Tool material is too hard.	◆Adopt dry cutting. ◆Select tool materials with good toughness.
Chattering	burrs occurring Cutting resistant force increasing	Feed rate and cutting speed are too high.	◆Select tool materials with good wear resistance. ◆Sharpen cutting edge by enlarging rake angle. ◆Reduce cutting speed.
Flaking	Usually occurring when machining super hard materials, which is accompanied with vibration	Bonding occurs on cutting edge. Chip flow is obstructed.	◆Sharpen cutting edge by enlarging rake angle. ◆Enlarge chip pocket.

The functions of each part of turning tools

1 The names of each part of turning tools





2 Effects of rake angle

Larger rake angle makes cutting edge sharper, reduces resistant forces of chip flow, diminishes friction and prevent deformation, leading to smaller cutting forces and cutting power, lower cutting temperature, less abrasion and higher surface quality. However, too large rake angle would reduce the rigidity and strength of tool. Heat can't be diffused easily. Serious breakage and abrasion on tool would occur, reducing tool life. Please choose rake angle according to machining conditions.

Value selection	Situations
Small rake angle	●When machining brittle and hard materials ●When roughing and intermittent cutting
Big rake angle	●When machining plastic or soft materials ●When finishing

3 Effects of clearance angle

The main function of clearance angle is to reduce the friction between the clearance face of tool and the surface of workpiece. When the rake angle is fixed, larger clearance angle can increase the sharpness of cutting edge, reduce cutting forces and friction, and then achieve higher surface quality. However, if clearance angle is too large, the strength of cutting edge would decrease. Also, heat can't be diffused easily and serious abrasion would occur, reducing tool life.

The principle of choosing clearance angle: Choose small clearance angle if friction is not serious.

Value Selection	Situations
Small clearance angle	●In order to increase nose strength when roughing ●When machining brittle and hard materials
Large clearance angle	●In order to reduce friction when finishing ●When machining materials easy to be hardened

4 Effects of inclined angle

Positive or negative inclined angle determines the direction of chip flow, and also affects the strength and impact resistance of insert nose.

◆As diagram (1) shows, when the inclined angle is negative, namely nose is in the lowest point as apposed to the bottom of tool, chips flow to the machined surface of workpiece.



Picture (1)

◆ As diagram (2) shows, when inclined angle is positive, namely the nose is in the highest point as apposed to the bottom of the tool, chips flow to the areas of workpiece surface that haven't been machined.

◆ The change of inclined angle also affects insert nose strength and impact resistance. When the inclined angle is negative, the nose is in the lowest point of cutting edge. When the cutting edge enters the workpiece, the contacting point is on the cutting edge or rake face, protecting the nose from impact and increase the strength of the nose. Normally, negative inclined angle should be chosen for tools with big rake angle. This can not only increase nose strength, but also prevent the impact of entry.



Picture (2)

5 Effects of approach angle

Reduced approaching angle increases the strength of tools and enable heat to diffuse easily, improving surface quality. This is because when the approach angle is small, cutting edge width is large, and then the unit width of cutting edge bears less cutting force. Meanwhile, tool life can be improved.

Normally, select 90°approach angle for turning of slender and step shaft; select 45° approach angle for external turning, end surface machining and chamfering. When approach angle is larger, radial force is reduced, cutting is stable, cutting thickness is increased, and chip breaking is excellent.



Value selection	Situations
Small approach angle	For those materials with high intensity, high hardness and hardened layer on the surface
Big approach angle	When rigidity of the machine is not enough

6 Effects of minor angle

Minor angle is the main angle that can affect surface quality, and it can also affect tool strength. If the approach angle is too small, the friction between the secondary flank and machined surface of workpiece will increase, causing vibration.

The principle of selecting minor angle: Select small minor angle when roughing or when the friction is unaffected and there is no vibration. Select large minor angle when finishing.

7 Nose radius

Nose radius significantly affects nose strength and surface quality.

Large nose radius means higher cutting edge strength, and the abrasion on the rake face and clearance face can be reduced to some extent. However, if the nose radius is too large, radial force will increase, and vibration is easy to occur, affecting machining precision and surface quality.

Value selection	Situations
Small nose radius	●Finishing at small cutting depth ●Machining parts such as slender shaft ●When the rigidity of the machine is not enough
Large nose radius	●When roughing ●When machining hard materials (intermittent cutting) ●When the rigidity of the machine is not enough

Calculation method of turning parameters

1 Calculation of cutting speed



$$Vc=\frac{\pi \times D \times n}{1000}\ (m/min)$$

In the formula: Vc: Cutting speed (m/min)
n: Rotating speed of main axle (rev/min)
D: Diameter of workpiece (mm)

For example: When the rotating speed is 280rev/min and the diameter of workpiece is 150mm, the cutting speed should be:

$$Vc=\frac{\pi \times D \times n}{1000}\ (m/min)\ =132(m/min)$$

2 Calculation of feed rate



$$f=\frac{l}{n}\ (mm/rev)$$

In the formula: f: Feed rate per rotation (mm/rev)
l: Cutting length per minute (mm/min)
n: Rotating speed of main axle (rev/min)

For example: When the rotating speed of main axle is 500rev/min, and the cutting length per minute is 100mm/min, the feed rate per rotation should be:

$$f=\frac{l}{n}=\frac{100}{500}=0.2(mm/rev)$$

3 Cutting time calculation of external and internal turning

$$T=\frac{l}{f\times n}\ (min)$$

In the formula: T: Cutting time (min)
l: Length of machined areas (mm)
f: Feed rate (mm/rev)
n: Rotating speed of main axle (rev/min)

For example: When the rotating speed of main axle is 250rev/min, and the feed rate is 0.2mm/rev, the time needed for a cutting length of 150mm should be:

$$T=\frac{l}{f\times n}=\frac{150}{0.2\times 250}=3(min)$$



4 Time calculation for end surface turning (constant linear speed)

$$T=\frac{\pi\times(a^2-b^2)}{4000\times Vc\times f}\ (min)$$

In the formula: T: Cutting time (min)
Vc: Cutting speed (m/min)
f: Feed rate (mm/rev)

For end surface without hole, b=0, the formula is still valid.



5 Theoretical value calculation of machined surface roughness

$$R=\frac{f^2}{8r_c}\times 1000\ (\mu m)$$

In the formula: R: Theoretical roughness value of machined surface
f: Feed rate (mm/rev)
rc: Nose radius (mm)

For example: When the feed rate is 0.2mm/rev, and the nose radius is 0.4mm, the theoretical roughness value of machined surface should be:

$$R=\frac{f^2}{8r_c}\times 1000=\frac{0.2^2}{8\times 0.4}\times 1000=12.5(\mu m)$$



Effect of three main turning parameters on machining

Effects of three main parameters

Normally, short machining time, long tool life and high machining precision are expected in machining, so the material quality, hardness, and shape of the workpiece, and properties of machine should be fully considered, and then we can select suitable tools and adopt high-efficiency cutting parameters, namely three parameters.



Cutting speed (Vc)

When the workpiece is rotating on the machine, the number of its rotation per minute is defined as Rotating speed of main axle (n). Because of its rotation, the cutting speed measured on the contacting point of diameter is defined as linear speed, m/min. Normally, linear speed is considered to measure the effect of cutting speed on machining.

Effect of cutting speed

Cutting speed has significant effect on tool life. When the cutting speed is increased, cutting temperature will increase and tool life will be shortened. Cutting speed varies according to the different types and hardness of workpiece. The below conclusions are reached after many cutting experiments:

(1) Normally tool life would be reduced to half when the cutting speed is increased by 20%. Tool life would be 20% of the original life if the cutting speed is raised by 50%.

(2) Low speed (20-40m/min) cutting could easily cause vibration and shorten tool life.

Feed rate (fn)

Feed rate is defined as the moving distance of tool after workpiece rotates for one circle, measured by mm/rotation.

Effect of feed rate

Feed rate is a key factor that determines surface quality. Meanwhile it also affect the range of chip forming and the thickness of chips during machining.

In term of the effect on tool life, small feed rate leads to serious abrasion on clearance face, greatly reducing tool life.

Cutting depth (ap)

Cutting depth is defined as the difference between machined surface and unmachined surface, measured by mm. It is half the difference value between the original diameter and machined diameter.

Effect of cutting depth

Cutting depth should be determined by the machining allowance and shape of workpiece, power and rigidity of machine, and tool rigidity.

The change of cutting depth has little effect on tool life. If the cutting depth is too low, the cutting nose only scrapes the hardened layer on the workpiece surface, reducing tool life. When there is hardened oxide layer on workpiece surface, higher cutting depth should be adopted within the possible range of machine's power to avoid cutting nose just cutting the hardened layer of workpiece.

Comparison table for turning insert chipbreaker

Negative inserts

ISO	Machining range	ZCCCT	SANDVIK	KORLOY	TaeguTec	WALTER	SECO	MITSUBISHI	SUMITOMO	KENNAMETAL	DIJET	HITACHI	TUNGALOY	KYOCERA	VALANTTE
P	For extra finishing		QF LC	HU	FA FX	FP5	FF1 FF2	PK※ FH, FY FP, FS	FB FA, FL	FF		FE	01※, TF, ZF 11	DP※, GP, PP ,VF, XP XP-T, XF	F1
	For finishing	DF	PF XF	HF	FG FM	MP3, FV5 NF3, NF4	MF2	LP, C SA, SH	FE, SU, LU, SX, SE	LF, FN	PF, UR UA, UT	BE, CE B, BH	NS, 27 TSF, AS, TQ	HQ, CQ PQ	F2(2B), F5(5C)
	For finishing (Soft steel)	SF		HF	FC			SY					17	XQ, XS	
	For finishing (Wiper)	WGF	WL WF	HW	WS	NF	W-MF2	SW	LUW SEW	FW			AFW, ASW FW, SW	WF WP, WQ	
	For semi-finishing	DM PM	PM QM XM	HA HC HM	PC FT MT SM MP	MF3 MV5	MF3 MF5 M3 M5	MP MA MH	GU UG UX GE	P MN	PG UB	CT AB AY AE AH	NM, ZM TM, DM 37, AM 33, 38	PG, CJ, GS, PS HS, PT	F3, F4(8A), M2(2C), M3 M4, M5(5B), M6, M7, 55, M8
	For semi-finishing(Wiper)	WGM	WMX WM		WT	NM	W-M6 W-M3 W-MF5	MW	GUW	MW RW				WE	
	For light roughing	LR(Single-side) DR(Double-side)	PR, HM XMR		RT	NM6, RP5 NM9, RP7	MR7 MR6	RP GH	MU, MX ME, UZ	RN RP	UD, GG	Y, RE	TH	RH, GT	
	For heavy roughing	HDR HPR	QR PR HR MR	HR HH	RX, HD HY, HT RT, RH HZ, EH	NR6 NRF NRR	R5, R56 R4, R6 R7, PR9 R57, RR6 R8	HM, HL HZ, HX HV, HR	MP, HG HP, HU HW, HF	MR, RM RH	UC	TE, UE HX, HE H	TU, TRS TUS	PX	R3, R4, R6(9A) R7(9B), R9(9C)

※ Periphery grinding type

Comparison table for turning insert chipbreaker

Negative inserts

ISO	Machining range	ZCCCT	SANDVIK	KORLOY	TaeguTec	WALTER	SECO	MITSUBISHI	SUMITOMO	KENNAMETAL	DIJET	HITACHI	TUNGALOY	KYOCERA	VALANTTE
M	For finishing	EF	MF	HA	SF	NF4, FM5	MF1	SH, LM	SU, EF	FP, LF※		MP, AB BH	SS	MQ GU	F1, F2(2B), F5(5C)
	For semi-finishing	EM	MM, QM XM, K	HS	ML, EM MM, VF	MM5 RM5 NM4	MF4	MS, ES GM, MM MA	EX, EG UP, GU HM	MP	SF, SG SZ	DE PV SE AH	SF, SA, SM, S	MS, MU SU, HU, ST, TK	F3, F4(8A), M2(2C), M3 M4, M5(5B), M6, M7, 55, M8
	For roughing	ER	MR	GS, HM	MT	NR4 NR5	M5, MR7 RR6	GH, HZ RM, HL	EM, MU MP	UP RP		AE	TH, SH		R3, R4, R6(9A) R7(9B), R9(9C)
K	For finishing	PM	KF			MK5	MF2, M3 MF5, M4	VA AH		FN		VA, AH	CF	KQ	F2(2B)
	For Semi-Finishing	PM	KM	Through chip-breaker, HM	MC	RK5 NM5	M5	V AE	UZ, GZ UX	RP, UN	PG	V, AE	CM	KG, C	M5(5B), M6, M8
	For roughing	Without chip-breaker	KR KRR	GR, HR GH	KT	RK7		RE			GG	RE		KH, GC	R3, R4, R7(9B)
S	For finishing	NF/NGF	SF SGF※		EA	NF4, NFT MS3	MF5, MF1 MF4	FJ※, LS MJ, MJ※	EF, SU※	FS, LF※ MS			HRF	MQ	F5(5C), M2(2C)
	For semi-finishing	NM	NGP※, SM			NMT, NMS	M1	MS	EG, EX SU※, UP	NGP※ UP, P		VI	HRM, SA HMM	SQ, MS MU, TK	M4, M5(5B), M7, 55
	For roughing	SNR	SR SMR		ET	NRS NRT	MR3 MR4	GJ RS	MU	RP				SG SX	

※ Periphery grinding type

Comparison table for turning insert chipbreaker

Positive inserts

ISO	Machining range	ZCCCT	SANDVIK	KORLOY	TaeguTec	WALTER	SECO	MITSUBISHI	SUMITOMO	KENNAMETAL	DIJET	HITACHI	TUNGALOY	KYOCERA	VALANTTE
P	For finishing	SF, HF	PF, UF XF	HFP	FA, FG FX	PF4 FP4	FF1 F1	FV, SV FP, LP	FP, LU SU, SK	11, UF LF, FP		JQ	PF, PSF PS, PSS	GP, XP VF, PP	PF4 JQ, JZ
	For finishing (Wiper)		WF			PF2※ PF, PF5※	W-F1	SW	LUW SDW	FW				WP	
	For semi-finishing	HM	UM, XM PM, PR XR	HMP C25	MT, PC	PS5 PM5 FP6	F2 MF2, M5	MV, MP	MU	MF, MP	FT	JE	PM 23, 24	HQ, XQ GK MF※	PM2 PM4
	For semi-finishing (Wiper)		WM		WT	PM	W-F2 W-M3	MW		MW					
M	For finishing	EF	MF	HFP		FM4	F1, F2	FM, LM	FC※, SI※ LU, SU	MF		MP	PF, PSF PS, PSS	CF※, CK※ GQ※, GF※ MQ, SK	1A, 2A
	For semi-finishing	EM	MM	HMP C25		MM4 RM4		MM	MU	MP			PM	HQ GK	PM2 PM4
K	For semi-finishing	HM, HR without chip-breaker	KF KM KR	HMP C25		FK6	F1 M3, M5	MK Without chip-breaker	MU Without chip-breaker	Without chip-breaker			CM Without chip-breaker	Without chip-breaker※	PM2 PM4
S	For finishing/ For semi-finishing	NGF						FS※, LS※ FJ※, FS-P※ LS-P※	SL※	LF※ HP※				MQ	PM2, 1A 2A
N	For general turning	LH	AL	TA AK MA	FL	PM2, FN2 MN2	AL※	AZ※	AG	HP※	ALU ACB ASF		AL※	AH※	1L, 1A 2A

※ Periphery grinding type

ROLLOMATIC

ZCC·CT

AGATHON
400 COMBI

ZCC·CT

POWER



Detroit (USA)

Düsseldorf (Germany / Europe)

SEDE
Zhuzhou (China)

QUALITY MANAGEMENT SYSTEM
CERTIFICATE
Zhuzhou Cemented Carbide Cutting Tools Co.,Ltd.
Quality Management System
ISO9001:2015
CHINA QUALITY CERTIFICATION CENTRE

ENVIRONMENTAL MANAGEMENT
SYSTEM CERTIFICATE
Zhuzhou Cemented Carbide Cutting Tools Co.,Ltd.
Environmental Management System
GB/T 24001-2016 / ISO 14001:2015
CHINA QUALITY CERTIFICATION CENTRE

bsi.
Certificate of Registration
QUALITY MANAGEMENT SYSTEM - ISO 9001:2015
FS 651501
...making excellence a habit.

Oficina central europea

ZCC Cutting Tools Europe GmbH

www.zccct-europe.com
Wanheimer Str. 57, 40472 Düsseldorf, Germany
Tel.: +49 (0)211-989240-0
Fax: +49 (0)211-989240-111
E-mail: info@zccct-europe.com

Sucursal de Francia

ZCC Cutting Tools Europe GmbH
Succursale Française

www.zccct-europe.com
14, Allée Charles Pathé, 18000 Bourges, France
Tel.: +33 (0)2 45 41 01 40
Fax: +33 (0)800 74 27 27
E-mail: ventes@zccct-europe.com

© Copyright by ZCC Cutting Tools Europe GmbH
Reservados todos los derechos.